

# Package ‘AffyRNADegradation’

October 16, 2024

**Type** Package

**Title** Analyze and correct probe positional bias in microarray data due to RNA degradation

**Version** 1.50.0

**Date** 2023-10-17

**Depends** R (>= 2.9.0), methods, affy

**Suggests** AmpAffyExample, hgu133acdf

**Author** Mario Fasold

**Maintainer** Mario Fasold <fasold@izbi.uni-leipzig.de>

**Description** The package helps with the assessment and correction of RNA degradation effects in Affymetrix 3' expression arrays. The parameter `d` gives a robust and accurate measure of RNA integrity. The correction removes the probe positional bias, and thus improves comparability of samples that are affected by RNA degradation.

**License** GPL-2

**Collate** AllClasses.R decayFunction.R AffyRNADegradation.R probeInfo.R tongs.R

**biocViews** GeneExpression, Microarray, OneChannel, Preprocessing, QualityControl

**git\_url** <https://git.bioconductor.org/packages/AffyRNADegradation>

**git\_branch** RELEASE\_3\_19

**git\_last\_commit** 2be3cbc

**git\_last\_commit\_date** 2024-04-30

**Repository** Bioconductor 3.19

**Date/Publication** 2024-10-16

## Contents

AffyDegradationBatch-class . . . . .	2
AffyRNADegradation . . . . .	3
GetTongs . . . . .	4
RNADegradation . . . . .	5

<b>Index</b>	<b>7</b>
--------------	----------

---

AffyDegradationBatch-class  
*Class AffyDegradationBatch*

---

### Description

This class represents Affymetrix GeneChip probe level data that has been analysed and corrected for the probe location bias.

### Objects from the Class

Objects can be created using the function `RNADegradation`.

### Slots

`location.type`: Object of class `character` describing the type of probe position used for the analysis (probe index or probe location).

`afbatch`: Object of class `AffyBatch` containing corrected probe level data.

`stats`: Object of class `matrix` containing various statistical parameters from the analysis.

`means.pm`: Object of class `matrix` containing the average PM probe intensities for probe locations of expressed genes.

`means.mm`: Object of class `matrix` containing the average MM probe intensities for probe locations of expressed genes.

### Methods

**afbatch** signature(`x = "AffyDegradationBatch"`): returns as `AffyBatch` object containing corrected probe level data.

**d** signature(`x = "AffyDegradationBatch"`): returns a vector with a measure of RNA degradation for each sample

**plotDx** signature(`x = "AffyDegradationBatch"`): plots the probe location bias for all samples of the experiment.

### Author(s)

Mario Fasold

**See Also**

AffyBatch

**Examples**

```
if (require(AmpAffyExample)) {  
  # Get example data  
  data(AmpData)  
  
  affy.deg <- RNADegradation(AmpData[,4])  
  
  ## Plot degradation  
  plotDx(affy.deg)  
  
  ## Get degradation measure  
  d(affy.deg)  
  
  ## Get AffyBatch object with corrected probe intensities  
  afbatch(affy.deg)  
}
```

---

AffyRNADegradation      *AffyRNADegradation: analyze and correct RNA degradation effects*

---

**Description**

The AffyRNADegradation package helps in the assessment of RNA degradation effects in Affymetrix 3' expression arrays. The parameter `d` gives a robust and accurate measure of RNA integrity. The correction removes the probe positional bias, and thus improves comparability of samples that are affected by RNA degradation.

**Details**

Package: AffyRNADegradation  
Type: Package  
Version: 0.1.0  
Date: 2011-10-13  
License: GPL >=2

The RNADegradation function performs both analysis and correction of RNA degradation effects, returning an object of type `AffyDegradationBatch`. The class provides accessor functions to obtain the degradation parameter `d` and a `AffyBatch` object containing corrected probe intensities. A more detailed look on the RNA degradation effects can be gained through the `tongs` plot, the `Dx` plot and further statistics.

**Author(s)**

Mario Fasold

**Examples**

```
if (require(AmpAffyExample)) {  
  # Load example data (AmpData affybatch)  
  data(AmpData)  
  
  ## Compute and correct degradation for a single chip (for speed)  
  affy.deg <- RNADegradation(AmpData[,4])  
  
  ## Show degradation parameter d  
  d(affy.deg)  
  
  ## Replace data with corrected data for further analysis  
  AmpData <- afbatch(affy.deg)  
}
```

---

GetTongs

*Generate and visualize the tongs plot*

---

**Description**

The tongs plot and the related degradation hook show the relationship between expression level and probe location bias. They are required for the correct estimation of RNA degradation effects.

**Usage**

```
GetTongs(affyData, chip.idx = 1)  
PlotTongs(tongs)  
PlotDegradationHooks(affyData, ...)
```

**Arguments**

<code>affyData</code>	an AffyBatch object.
<code>chip.idx</code>	index of the sample to compute the tongs for.
<code>tongs</code>	the tongs plot data table.
<code>...</code>	optional graphical parameters.

**Value**

Tongs a table containing Tongs plot values ordered by expression level.

**Author(s)**

Mario Fasold

**Examples**

```
if (require(AmpAffyExample)) {  
  # Get example data  
  data(AmpData)  
  
  tongs <- GetTongs(AmpData, chip.idx = 4)  
  PlotTongs(tongs)  
  
  PlotDegradationHooks(AmpData[,c(3,4)])  
}
```

---

RNADegradation

*Compute degradation parameters and correct probe intensities*

---

**Description**

Given an AffyBatch object, the function RNADegradation computes the probe positional bias and several statistical parameters, including a robust and accurate measure of RNA degradation. Probe intensities are corrected for the bias for each sample within the AffyBatch object.

**Usage**

```
RNADegradation(affyData,  
               location.type = "index",  
               location.file.dir = NULL,  
               plot.images = FALSE)
```

**Arguments**

`affyData` an AffyBatch object containing the probe level microarray data.

`location.type` index-based probe alignment (x=k) if "index", or location-based alignment (x=L) if "absolute".

`location.file.dir` directory containing the probe location file(s).

`plot.images` if TRUE plots a set of debug images.

**Value**

An AffyDegradationBatch object.

**Author(s)**

Mario Fasold

**See Also**

AffyDegradationBatch

**Examples**

```
if (require(AmpAffyExample)) {  
  # Get example data  
  data(AmpData)  
  
  affy.deg <- RNADegradation(AmpData[,4])  
}
```

# Index

- \* **classes**
  - AffyDegradationBatch-class, [2](#)
- \* **methods**
  - GetTongs, [4](#)
  - RNADegradation, [5](#)
- \* **package**
  - AffyRNADegradation, [3](#)

afbatch (AffyDegradationBatch-class), [2](#)  
afbatch, AffyDegradationBatch-method  
(AffyDegradationBatch-class), [2](#)  
AffyDegradationBatch  
(AffyDegradationBatch-class), [2](#)  
AffyDegradationBatch, ANY  
(AffyDegradationBatch-class), [2](#)  
AffyDegradationBatch-class, [2](#)  
AffyRNADegradation, [3](#)  
AffyRNADegradation-package  
(AffyRNADegradation), [3](#)

d (AffyDegradationBatch-class), [2](#)  
d, AffyDegradationBatch-method  
(AffyDegradationBatch-class), [2](#)

GetTongs, [4](#)

PlotDegradationHooks (GetTongs), [4](#)  
plotDx (AffyDegradationBatch-class), [2](#)  
plotDx, AffyDegradationBatch-method  
(AffyDegradationBatch-class), [2](#)  
PlotTongs (GetTongs), [4](#)

RNADegradation, [5](#)