

# Package ‘BiocWorkflowTools’

October 16, 2024

**Title** Tools to aid the development of Bioconductor Workflow packages

**Version** 1.30.0

**Encoding** UTF-8

**Description** Provides functions to ease the transition between Rmarkdown and LaTeX documents when authoring a Bioconductor Workflow.

**License** MIT + file LICENSE

**Depends** R (>= 3.4)

**Imports** BiocStyle, bookdown, git2r, httr, knitr, rmarkdown, rstudioapi, stringr, tools, utils, usethis

**NeedsCompilation** no

**VignetteBuilder** knitr

**biocViews** Software, ReportWriting

**RoxygenNote** 7.1.0

**Collate** 'createBiocWorkflow.R' 'f1000\_article.R' 'uploadToOverleaf.R' 'utils.R'

**git\_url** <https://git.bioconductor.org/packages/BiocWorkflowTools>

**git\_branch** RELEASE\_3\_19

**git\_last\_commit** dbfe9dc

**git\_last\_commit\_date** 2024-04-30

**Repository** Bioconductor 3.19

**Date/Publication** 2024-10-16

**Author** Mike Smith [aut, cre],  
Andrzej Oleś [aut]

**Maintainer** Mike Smith <[grimbough@gmail.com](mailto:grimbough@gmail.com)>

## Contents

createBiocWorkflow . . . . .	2
f1000_article . . . . .	2
uploadToOverleaf . . . . .	4

**Index****5**


---

createBiocWorkflow	<i>Create a New Bioconductor Workflow Package</i>
--------------------	---

---

**Description**

Uses `create_package` to set up a skeleton for a new Bioconductor workflow package.

**Usage**

```
createBiocWorkflow(
  path,
  description = getOption("devtools.desc"),
  rstudio = TRUE,
  open = rstudio
)
```

**Arguments**

path	location to create new package. The last component of the path will be used as the package name.
description	list of description values to override default values or add additional values.
rstudio	if TRUE, creates an RStudio project file.
open	if TRUE, opens the project in a new RStudio session.

**Value**

File path to the R Markdown vignette (invisibly).

**Examples**

```
createBiocWorkflow(file.path(tempdir(), "MyWorkflow"), open = FALSE)
```

---

f1000_article	<i>F1000Research article format</i>
---------------	-------------------------------------

---

**Description**

Format for creating F1000Research software tool articles.

**Usage**

```
f1000_article(
  toc = FALSE,
  number_sections = FALSE,
  fig_width = 5.67,
  fig_height = fig_width,
  fig_align = "center",
  keep_tex = TRUE,
  citation_package = "natbib",
  md_extensions = "+link_attributes",
  pandoc_args = "--wrap=preserve",
  ...
)
```

**Arguments**

toc	TRUE to include a table of contents in the output
number_sections	TRUE to number section headings
fig_width	Default width (in inches) for figures
fig_height	Default height (in inches) for figures
fig_align	Default alignment of figures. Possible values are "center" (default) "left" and "right".
keep_tex	Keep the intermediate tex file used in the conversion to PDF
citation_package	The LaTeX package to process citations, natbib or biblatex. Use none if neither package is to be used.
md_extensions	Markdown extensions to be added or removed from the default definition or R Markdown. See the <a href="#">rmarkdown_format</a> for additional details.
pandoc_args	Additional command line options to pass to pandoc
...	Arguments to <a href="#">pdf_document</a>

**Details**

Creates LaTeX sources which can be submitted to F1000Research through Overleaf.

**Value**

R Markdown output format to pass to [render](#)

**Citations**

R Markdown supports automatic generation of citations. You can find more information on the markdown citation syntax in the [Bibliographies and Citations](#) article in the R Markdown online documentation.

A bibliography file can be specified using the bibliography metadata field in the document's YAML header. Metadata variables for customizing citation style include:

biblio-style Bibliography style (e.g. "unsrnat", "plainnat")  
natbiboptions Options to natbib LaTeX package (e.g. "number", "super", "round")  
biblatoptions Options to biblatox LaTeX package

### Examples

```
## Not run:  
  
rmarkdown::draft("MyArticle.Rmd", template="f1000_article", package="BiocWorkflowTools")  
  
## End(Not run)
```

---

uploadToOverleaf	<i>Upload a LaTeX project to Overleaf</i>
------------------	---

---

### Description

Upload a LaTeX project to Overleaf

### Usage

```
uploadToOverleaf(path)
```

### Arguments

path                    File path to a directory or a single zip file to be uploaded.

### Value

Does not return any value. The Overleaf project page will automatically open in the default browser.

### Examples

```
## Not run:  
## don't run this code chunk in the example as we don't want to spam Overleaf  
uploadToOverleaf(files = 'MyWorkflow', openInBrowser = TRUE)  
  
## End(Not run)
```

# Index

`create_package`, 2  
`createBiocWorkflow`, 2  
  
`f1000_article`, 2  
  
`pdf_document`, 3  
  
`render`, 3  
`rmarkdown_format`, 3  
  
`uploadToOverleaf`, 4