

# Package ‘ReactomeGSA’

November 13, 2024

**Type** Package

**Title** Client for the Reactome Analysis Service for comparative multi-omics gene set analysis

**Version** 1.20.0

## Description

The ReactomeGSA packages uses Reactome's online analysis service to perform a multi-omics gene set analysis. The main advantage of this package is, that the retrieved results can be visualized using REACTOME's powerful webapplication.

Since Reactome's analysis service also uses R to perform the actual gene set analysis you will get similar results when using the same packages (such as limma and edgeR) locally.

Therefore, if you only require a gene set analysis, different packages are more suited.

**License** MIT + file LICENSE

**Encoding** UTF-8

**LazyData** false

**Imports** jsonlite, httr, progress, ggplot2, methods, gplots,  
RColorBrewer, dplyr, tidyr, Biobase

**RoxygenNote** 7.2.3

**Suggests** testthat, knitr, rmarkdown, ReactomeGSA.data, devtools

**Enhances** limma, edgeR, Seurat (>= 3.0), scater

**VignetteBuilder** knitr

**biocViews** GeneSetEnrichment, Proteomics, Transcriptomics,  
SystemsBiology, GeneExpression, Reactome

**BugReports** <https://github.com/reactome/ReactomeGSA/issues>

**URL** <https://github.com/reactome/ReactomeGSA>

**git\_url** <https://git.bioconductor.org/packages/ReactomeGSA>

**git\_branch** RELEASE\_3\_20

**git\_last\_commit** b1f2efd

**git\_last\_commit\_date** 2024-10-29

**Repository** Bioconductor 3.20

**Date/Publication** 2024-11-12

**Author** Johannes Griss [aut, cre] (<<https://orcid.org/0000-0003-2206-9511>>)

**Maintainer** Johannes Griss <johannes.griss@meduniwien.ac.at>

## Contents

add_dataset . . . . .	3
add_dataset,ReactomeAnalysisRequest,data.frame-method . . . . .	5
add_dataset,ReactomeAnalysisRequest,DGEList-method . . . . .	6
add_dataset,ReactomeAnalysisRequest,EList-method . . . . .	8
add_dataset,ReactomeAnalysisRequest,ExpressionSet-method . . . . .	10
add_dataset,ReactomeAnalysisRequest,matrix-method . . . . .	11
analyse_sc_clusters . . . . .	13
analyse_sc_clusters,Seurat-method . . . . .	14
analyse_sc_clusters,SingleCellExperiment-method . . . . .	15
break_names . . . . .	17
checkRequestValidity . . . . .	17
check_reactome_url . . . . .	18
convert_reactome_result . . . . .	18
data_frame_as_string . . . . .	19
fetch_public_data . . . . .	19
find_public_datasets . . . . .	20
get_dataset_loading_status . . . . .	21
get_fc_for_dataset . . . . .	21
get_is_sig_dataset . . . . .	22
get_public_species . . . . .	22
get_reactome_analysis_result . . . . .	23
get_reactome_analysis_status . . . . .	23
get_reactome_data_types . . . . .	24
get_reactome_methods . . . . .	25
get_result . . . . .	26
get_result,ReactomeAnalysisResult-method . . . . .	27
is_gsva_result . . . . .	28
load_public_dataset . . . . .	28
names,ReactomeAnalysisResult-method . . . . .	29
open_reactome . . . . .	30
open_reactome,ReactomeAnalysisResult-method . . . . .	30
pathways . . . . .	31
pathways,ReactomeAnalysisResult-method . . . . .	32
perform_reactome_analysis . . . . .	33
plot_correlations . . . . .	34
plot_correlations,ReactomeAnalysisResult-method . . . . .	35
plot_gsva_heatmap . . . . .	36
plot_gsva_heatmap,ReactomeAnalysisResult-method . . . . .	37
plot_gsva_pathway . . . . .	38
plot_gsva_pathway,ReactomeAnalysisResult-method . . . . .	39
plot_gsva_pca . . . . .	40
plot_gsva_pca,ReactomeAnalysisResult-method . . . . .	40
plot_heatmap . . . . .	41
plot_heatmap,ReactomeAnalysisResult-method . . . . .	42
plot_volcano . . . . .	43
plot_volcano,ReactomeAnalysisResult-method . . . . .	44
print,ReactomeAnalysisRequest-method . . . . .	45
print,ReactomeAnalysisResult-method . . . . .	46
ReactomeAnalysisRequest . . . . .	46
ReactomeAnalysisResult-class . . . . .	47

<i>add_dataset</i>	3
reactome_links	48
reactome_links,ReactomeAnalysisResult-method	49
remove_dataset	50
remove_dataset,ReactomeAnalysisRequest-method	50
result_types	51
result_types,ReactomeAnalysisResult-method	51
set_method	52
set_method,ReactomeAnalysisRequest-method	53
set_parameters	54
set_parameters,ReactomeAnalysisRequest-method	54
show,ReactomeAnalysisRequest-method	55
show,ReactomeAnalysisResult-method	56
start_reactome_analysis	56
wait_for_loading_dataset	57
<b>Index</b>	<b>58</b>

---

add_dataset	<i>add_dataset</i>
-------------	--------------------

---

## Description

Adds a dataset to the analysis request

## Usage

```
add_dataset(
  request,
  expression_values,
  name,
  type,
  comparison_factor,
  comparison_group_1,
  comparison_group_2,
  sample_data = NULL,
  additional_factors = NULL,
  overwrite = FALSE,
  ...
)
```

## Arguments

request	The request to add the dataset to. Commonly a <a href="#">ReactomeAnalysisRequest</a> object.
expression_values	Object containing the expression values of the dataset to add (multiple types supported).
name	character. Name of the dataset. This must be unique within one request.
type	character. The type of the dataset. Get available types using <a href="#">get_reactome_data_types</a>

comparison_factor	character. The name of the sample property to use for the main comparison. The sample properties are either retrieved from expression_values or from sample_data.
comparison_group_1	character. Name of the first group within comparison_factor to use for the comparison.
comparison_group_2	character. Name of the second group within comparison_factor to use for the comparison.
sample_data	data.frame (optional) data.frame containing the sample metadata of the expression_values. Depending on the object type of expression_values, this information can also be extracted from there.
additional_factors	vector. Vector of additional sample properties that are used as blocking factors (if supported by the chosen analysis method) in the gene set analysis.
overwrite	boolean. If set to TRUE, datasets with the same name will be overwritten
...	Additional parameters passed to downstream functions. See the respective documentation of whether any additional parameters are supported.

### Value

The [ReactomeAnalysisRequest](#) object with the added dataset

### See Also

Other add\_dataset methods: [add\\_dataset, ReactomeAnalysisRequest, DGEList-method](#), [add\\_dataset, ReactomeAnalysisRequest, ExpressionSet-method](#), [add\\_dataset, ReactomeAnalysisRequest, data.frame-method](#), [add\\_dataset, ReactomeAnalysisRequest, matrix-method](#)

### Examples

```
# create a request using Camera as an analysis
library(ReactomeGSA.data)
data(griss_melanoma_proteomics)
library(methods)

my_request <- ReactomeAnalysisRequest(method = "Camera")

# since the expression_values object is a limma EList object, the sample_data is
# retrieved from there

# add the dataset
my_request <- add_dataset(request = my_request,
  expression_values = griss_melanoma_proteomics,
  name = "Proteomics",
  type = "proteomics_int",
  comparison_factor = "condition",
  comparison_group_1 = "MOCK",
  comparison_group_2 = "MCM",
  additional_factors = c("cell.type", "patient.id"))
```

---

add\_dataset, ReactomeAnalysisRequest, data.frame-method  
*add\_dataset - data.frame*

---

## Description

Adds a dataset to the analysis request

## Usage

```
## S4 method for signature 'ReactomeAnalysisRequest,data.frame'  
add_dataset(  
  request,  
  expression_values,  
  name,  
  type,  
  comparison_factor,  
  comparison_group_1,  
  comparison_group_2,  
  sample_data = NULL,  
  additional_factors = NULL,  
  overwrite = FALSE,  
  ...  
)
```

## Arguments

request	ReactomeAnalysisRequest.
expression_values	data.frame. In this case, the sample_data must be set.
name	character. Name of the dataset. This must be unique within one request.
type	character. The type of the dataset. Get available types using <a href="#">get_reactome_data_types</a>
comparison_factor	character. The name of the sample property to use for the main comparison. The sample properties are either retrieved from expression_values or from sample_data.
comparison_group_1	character. Name of the first group within comparison_factor to use for the comparison.
comparison_group_2	character. Name of the second group within comparison_factor to use for the comparison.
sample_data	data.frame (optional) data.frame containing the sample metadata of the expression_values. Depending on the object type of expression_values, this information can also be extracted from there.
additional_factors	vector. Vector of additional sample properties that are used as blocking factors (if supported by the chosen analysis method) in the gene set analysis.
overwrite	boolean. If set to TRUE, datasets with the same name will be overwritten

... Additional parameters passed to downstream functions. See the respective documentation of whether any additional parameters are supported.

### Value

The `ReactomeAnalysisRequest` object with the added dataset

### See Also

Other `add_dataset` methods: [add\\_dataset, ReactomeAnalysisRequest, DGEList-method](#), [add\\_dataset, ReactomeAnalysisRequest, ExpressionSet-method](#), [add\\_dataset, ReactomeAnalysisRequest, mat](#), [add\\_dataset\(\)](#)

### Examples

```
# create a request using Camera as an analysis
library(ReactomeGSA.data)
data(griss_melanoma_proteomics)
library(methods)

my_request <- ReactomeAnalysisRequest(method = "Camera")

# since the expression_values object is a limma EList object, the sample_data is
# retrieved from there

# add the dataset
my_request <- add_dataset(request = my_request,
                          expression_values = griss_melanoma_proteomics,
                          name = "Proteomics",
                          type = "proteomics_int",
                          comparison_factor = "condition",
                          comparison_group_1 = "MOCK",
                          comparison_group_2 = "MCM",
                          additional_factors = c("cell.type", "patient.id"))
```

---

`add_dataset, ReactomeAnalysisRequest, DGEList-method`  
*add\_dataset - DGEList*

---

### Description

Adds a dataset to the analysis request

### Usage

```
## S4 method for signature 'ReactomeAnalysisRequest, DGEList'
add_dataset(
  request,
  expression_values,
  name,
  type,
  comparison_factor,
  comparison_group_1,
```

```

    comparison_group_2,
    sample_data = NULL,
    additional_factors = NULL,
    overwrite = FALSE,
    ...
)

```

## Arguments

request	ReactomeAnalysisRequest.
expression_values	DGEList Here, the sample_data is automaticall extracted from the expression_values object unless sample_data is specified as well.
name	character. Name of the dataset. This must be unique within one request.
type	character. The type of the dataset. Get available types using <a href="#">get_reactome_data_types</a>
comparison_factor	character. The name of the sample property to use for the main comparison. The sample properties are either retrieved from expression_values or from sample_data.
comparison_group_1	character. Name of the first group within comparison_factor to use for the comparison.
comparison_group_2	character. Name of the second group within comparison_factor to use for the comparison.
sample_data	data.frame (optional) data.frame containing the sample metadata of the expression_values. Depending on the object type of expression_values, this information can also be extracted from there.
additional_factors	vector. Vector of additional sample properties that are used as blocking factors (if supported by the chosen analysis method) in the gene set analysis.
overwrite	boolean. If set to TRUE, datasets with the same name will be overwritten
...	Additional parameters passed to downstream functions. See the respective documentation of whether any additional parameters are supported.

## Value

The [ReactomeAnalysisRequest](#) object with the added dataset

## See Also

Other add\_dataset methods: [add\\_dataset, ReactomeAnalysisRequest, EList-method](#), [add\\_dataset, ReactomeAnal](#), [add\\_dataset, ReactomeAnalysisRequest, data.frame-method](#), [add\\_dataset, ReactomeAnalysisRequest, matrix](#), [add\\_dataset\(\)](#)

## Examples

```

# create a request using Camera as an analysis
library(ReactomeGSA.data)
data(griss_melanoma_proteomics)
library(methods)

```

```

my_request <- ReactomeAnalysisRequest(method = "Camera")

# since the expression_values object is a limma EList object, the sample_data is
# retrieved from there

# add the dataset
my_request <- add_dataset(request = my_request,
                          expression_values = griss_melanoma_proteomics,
                          name = "Proteomics",
                          type = "proteomics_int",
                          comparison_factor = "condition",
                          comparison_group_1 = "MOCK",
                          comparison_group_2 = "MCM",
                          additional_factors = c("cell.type", "patient.id"))

```

---

*add\_dataset,ReactomeAnalysisRequest,EList-method*

*add\_dataset - EList*

---

## Description

Adds a dataset to the analysis request

## Usage

```

## S4 method for signature 'ReactomeAnalysisRequest,EList'
add_dataset(
  request,
  expression_values,
  name,
  type,
  comparison_factor,
  comparison_group_1,
  comparison_group_2,
  sample_data = NULL,
  additional_factors = NULL,
  overwrite = FALSE,
  ...
)

```

## Arguments

<code>request</code>	ReactomeAnalysisRequest.
<code>expression_values</code>	EList. Here, the <code>sample_data</code> is automaticall extracted from the <code>expression_values</code> object unless <code>sample_data</code> is specified as well.
<code>name</code>	character. Name of the dataset. This must be unique within one request.
<code>type</code>	character. The type of the dataset. Get available types using <a href="#">get_reactome_data_types</a>



comparison_factor	character. The name of the sample property to use for the main comparison. The sample properties are either retrieved from expression_values or from sample_data.
comparison_group_1	character. Name of the first group within comparison_factor to use for the comparison.
comparison_group_2	character. Name of the second group within comparison_factor to use for the comparison.
sample_data	data.frame (optional) data.frame containing the sample metadata of the expression_values. Depending on the object type of expression_values, this information can also be extracted from there.
additional_factors	vector. Vector of additional sample properties that are used as blocking factors (if supported by the chosen analysis method) in the gene set analysis.
overwrite	boolean. If set to TRUE, datasets with the same name will be overwritten
...	Additional parameters passed to downstream functions. See the respective documentation of whether any additional parameters are supported.

**Value**

The [ReactomeAnalysisRequest](#) object with the added dataset

**See Also**

Other add\_dataset methods: [add\\_dataset, ReactomeAnalysisRequest, DGEList-method](#), [add\\_dataset, ReactomeAnalysisRequest, data.frame-method](#), [add\\_dataset, ReactomeAnalysisRequest, matrix-method](#), [add\\_dataset\(\)](#)

**Examples**

```
# create a request using Camera as an analysis
library(ReactomeGSA.data)
data(griss_melanoma_proteomics)
library(methods)

my_request <- ReactomeAnalysisRequest(method = "Camera")

# since the expression_values object is a limma EList object, the sample_data is
# retrieved from there

# add the dataset
my_request <- add_dataset(request = my_request,
  expression_values = griss_melanoma_proteomics,
  name = "Proteomics",
  type = "proteomics_int",
  comparison_factor = "condition",
  comparison_group_1 = "MOCK",
  comparison_group_2 = "MCM",
  additional_factors = c("cell.type", "patient.id"))
```

---

*add\_dataset,ReactomeAnalysisRequest,ExpressionSet-method*  
*add\_dataset - ExpressionSet*

---

## Description

Adds a dataset to the analysis request

## Usage

```
## S4 method for signature 'ReactomeAnalysisRequest,ExpressionSet'
add_dataset(
  request,
  expression_values,
  name,
  type,
  comparison_factor,
  comparison_group_1,
  comparison_group_2,
  sample_data = NULL,
  additional_factors = NULL,
  overwrite = FALSE,
  ...
)
```

## Arguments

<code>request</code>	ReactomeAnalysisRequest.
<code>expression_values</code>	ExpressionSet. Here, the <code>sample_data</code> is automatically extracted from the <code>expression_values</code> object unless <code>sample_data</code> is specified as well.
<code>name</code>	character. Name of the dataset. This must be unique within one request.
<code>type</code>	character. The type of the dataset. Get available types using <a href="#">get_reactome_data_types</a>
<code>comparison_factor</code>	character. The name of the sample property to use for the main comparison. The sample properties are either retrieved from <code>expression_values</code> or from <code>sample_data</code> .
<code>comparison_group_1</code>	character. Name of the first group within <code>comparison_factor</code> to use for the comparison.
<code>comparison_group_2</code>	character. Name of the second group within <code>comparison_factor</code> to use for the comparison.
<code>sample_data</code>	data.frame (optional) data.frame containing the sample metadata of the <code>expression_values</code> . Depending on the object type of <code>expression_values</code> , this information can also be extracted from there.
<code>additional_factors</code>	vector. Vector of additional sample properties that are used as blocking factors (if supported by the chosen analysis method) in the gene set analysis.

overwrite      boolean. If set to TRUE, datasets with the same name will be overwritten  
 ...            Additional parameters passed to downstream functions. See the respective doc-  
                   umentation of whether any additional parameters are supported.

### Value

The [ReactomeAnalysisRequest](#) object with the added dataset

### See Also

Other add\_dataset methods: [add\\_dataset, ReactomeAnalysisRequest, DGEList-method](#), [add\\_dataset, ReactomeAn](#), [add\\_dataset, ReactomeAnalysisRequest, data.frame-method](#), [add\\_dataset, ReactomeAnalysisRequest, matrix](#), [add\\_dataset\(\)](#)

### Examples

```

# create a request using Camera as an analysis
library(ReactomeGSA.data)
data(griss_melanoma_proteomics)
library(methods)

my_request <- ReactomeAnalysisRequest(method = "Camera")

# since the expression_values object is a limma EList object, the sample_data is
# retrieved from there

# add the dataset
my_request <- add_dataset(request = my_request,
                          expression_values = griss_melanoma_proteomics,
                          name = "Proteomics",
                          type = "proteomics_int",
                          comparison_factor = "condition",
                          comparison_group_1 = "MOCK",
                          comparison_group_2 = "MCM",
                          additional_factors = c("cell.type", "patient.id"))

```

---

add\_dataset, ReactomeAnalysisRequest, matrix-method  
*add\_dataset - matrix*

---

### Description

Adds a dataset to the analysis request

### Usage

```

## S4 method for signature 'ReactomeAnalysisRequest, matrix'
add_dataset(
  request,
  expression_values,
  name,
  type,
  comparison_factor,

```

```

    comparison_group_1,
    comparison_group_2,
    sample_data = NULL,
    additional_factors = NULL,
    overwrite = FALSE,
    ...
)

```

## Arguments

<code>request</code>	ReactomeAnalysisRequest.
<code>expression_values</code>	matrix. In this case, the <code>sample_data</code> must be set.
<code>name</code>	character. Name of the dataset. This must be unique within one request.
<code>type</code>	character. The type of the dataset. Get available types using <a href="#">get_reactome_data_types</a>
<code>comparison_factor</code>	character. The name of the sample property to use for the main comparison. The sample properties are either retrieved from <code>expression_values</code> or from <code>sample_data</code> .
<code>comparison_group_1</code>	character. Name of the first group within <code>comparison_factor</code> to use for the comparison.
<code>comparison_group_2</code>	character. Name of the second group within <code>comparison_factor</code> to use for the comparison.
<code>sample_data</code>	data.frame (optional) data.frame containing the sample metadata of the <code>expression_values</code> . Depending on the object type of <code>expression_values</code> , this information can also be extracted from there.
<code>additional_factors</code>	vector. Vector of additional sample properties that are used as blocking factors (if supported by the chosen analysis method) in the gene set analysis.
<code>overwrite</code>	boolean. If set to TRUE, datasets with the same name will be overwritten
<code>...</code>	Additional parameters passed to downstream functions. See the respective documentation of whether any additional parameters are supported.

## Value

The [ReactomeAnalysisRequest](#) object with the added dataset

## See Also

Other `add_dataset` methods: [add\\_dataset, ReactomeAnalysisRequest, DGEList-method](#), [add\\_dataset, ReactomeAnalysisRequest, ExpressionSet-method](#), [add\\_dataset, ReactomeAnalysisRequest, data.frame-method](#), [add\\_dataset\(\)](#)

## Examples

```

# create a request using Camera as an analysis
library(ReactomeGSA.data)
data(griss_melanoma_proteomics)
library(methods)

```

```
my_request <- ReactomeAnalysisRequest(method = "Camera")

# since the expression_values object is a limma EList object, the sample_data is
# retrieved from there

# add the dataset
my_request <- add_dataset(request = my_request,
                          expression_values = griss_melanoma_proteomics,
                          name = "Proteomics",
                          type = "proteomics_int",
                          comparison_factor = "condition",
                          comparison_group_1 = "MOCK",
                          comparison_group_2 = "MCM",
                          additional_factors = c("cell.type", "patient.id"))
```

---

analyse\_sc\_clusters    *analyse\_sc\_clusters*

---

## Description

Analyses cell clusters of a single-cell RNA-sequencing experiment to get pathway-level expressions for every cluster of cells.

## Usage

```
analyse_sc_clusters(
  object,
  use_interactors = TRUE,
  include_disease_pathways = FALSE,
  create_reactome_visualization = FALSE,
  create_reports = FALSE,
  report_email = NULL,
  verbose = FALSE,
  ...
)
```

## Arguments

<code>object</code>	The object containing the single-cell RNA-sequencing data.
<code>use_interactors</code>	If set (default), protein-protein interactors from IntAct are used to extend Reactome pathways.
<code>include_disease_pathways</code>	If set, disease pathways are included as well. Disease pathways in Reactome follow a different annotation approach and can therefore lead to inaccurate results.
<code>create_reactome_visualization</code>	If set, the interactive visualization in Reactome's PathwayBrowser is created.
<code>create_reports</code>	If set, PDF and Microsoft Excel reports are created. Links to these report files are sent to the supplied e-mail address.

report_email	The e-mail address to which reports should be sent to.
verbose	If set, additional status messages are printed.
...	Parameters passed to the specific implementation. Detailed documentations can be found there.

### Details

There are currently two specific implementations of this function, one to support Seurat objects and one to support Bioconductor's SingleCellExperiment class.

### Value

A [ReactomeAnalysisResult](#) object.

### Examples

```
# This example shows how a Seurat object can be analysed
# the approach is identical for SingleCellExperiment objects
library(ReactomeGSA.data)
data(jerby_b_cells)

# perform the GSVA analysis
gsva_result <- analyse_sc_clusters(jerby_b_cells, verbose = FALSE)
```

---

analyse\_sc\_clusters, Seurat-method  
*analyse\_sc\_clusters - Seurat*

---

### Description

Analyses cell clusters of a single-cell RNA-sequencing experiment to get pathway-level expressions for every cluster of cells.

### Usage

```
## S4 method for signature 'Seurat'
analyse_sc_clusters(
  object,
  use_interactors = TRUE,
  include_disease_pathways = FALSE,
  create_reactome_visualization = FALSE,
  create_reports = FALSE,
  report_email = NULL,
  verbose = FALSE,
  assay = "RNA",
  slot = "counts",
  ...
)
```

**Arguments**

object	The Seurat object containing the single cell RNA-sequencing data.
use_interactors	If set (default), protein-protein interactors from IntAct are used to extend Reactome pathways.
include_disease_pathways	If set, disease pathways are included as well. Disease pathways in Reactome follow a different annotation approach and can therefore lead to inaccurate results.
create_reactome_visualization	If set, the interactive visualization in Reactome's PathwayBrowser is created.
create_reports	If set, PDF and Microsoft Excel reports are created. Links to these report files are sent to the supplied e-mail address.
report_email	The e-mail address to which reports should be sent to.
verbose	If set, additional status messages are printed.
assay	By default, the "RNA" assay is used, which contains the original read counts.
slot	The slot in the Seurat object to use. Default and recommended approach is to use the raw counts.
...	Parameters passed to the specific implementation. Detailed documentations can be found there.

**Details**

There are currently two specific implementations of this function, one to support Seurat objects and one to support Bioconductor's SingleCellExperiment class.

**Value**

A `ReactomeAnalysisResult` object.

**Examples**

```
# This example shows how a Seurat object can be analysed
# the approach is identical for SingleCellExperiment objects
library(ReactomeGSA.data)
data(jerby_b_cells)

# perform the GSVA analysis
gsva_result <- analyse_sc_clusters(jerby_b_cells, verbose = FALSE)
```

---

analyse\_sc\_clusters, SingleCellExperiment-method  
*analyse\_sc\_clusters - SingleCellExperiment*

---

**Description**

Analyses cell clusters of a single-cell RNA-sequencing experiment to get pathway-level expressions for every cluster of cells.

**Usage**

```
## S4 method for signature 'SingleCellExperiment'
analyse_sc_clusters(
  object,
  use_interactors = TRUE,
  include_disease_pathways = FALSE,
  create_reactome_visualization = FALSE,
  create_reports = FALSE,
  report_email = NULL,
  verbose = FALSE,
  cell_ids,
  ...
)
```

**Arguments**

object	The SingleCellExperiment object containing the single cell RNA-sequencing data.
use_interactors	If set (default), protein-protein interactors from IntAct are used to extend Reactome pathways.
include_disease_pathways	If set, disease pathways are included as well. Disease pathways in Reactome follow a different annotation approach and can therefore lead to inaccurate results.
create_reactome_visualization	If set, the interactive visualization in Reactome's PathwayBrowser is created.
create_reports	If set, PDF and Microsoft Excel reports are created. Links to these report files are send to the supplied e-mail address.
report_email	The e-mail address to which reports should be sent to.
verbose	If set, additional status messages are printed.
cell_ids	A factor specifying the group to which each cell belongs. For example, object\$cluster. Alternatively, a string specifying the metada field's name may be passed.
...	Parameters passed to scater's aggregateAcrossCells function.

**Details**

There are currently two specific implementations of this function, one to support Seurat objects and one to support Bioconductor's SingleCellExperiment class.

**Value**

A [ReactomeAnalysisResult](#) object.

**Examples**

```
# This example shows how a Seurat object can be analysed
# the approach is identical for SingleCellExperiment objects
library(ReactomeGSA.data)
data(jerby_b_cells)

# perform the GSVA analysis
gsva_result <- analyse_sc_clusters(jerby_b_cells, verbose = FALSE)
```



---

break_names	<i>break_names</i>
-------------	--------------------

---

**Description**

Introduce a line break in the middle of a long name.

**Usage**

```
break_names(the_names, long_name_limit = 46)
```

**Arguments**

the_names	A vector of names
long_name_limit	The limit to define a long name (default 46 chars.)

**Value**

The list of adapted names

---

checkRequestValidity	<i>Check's if a ReactomeAnalysisRequest object is valid</i>
----------------------	---

---

**Description**

Check's if a ReactomeAnalysisRequest object is valid

**Usage**

```
checkRequestValidity(object)
```

**Arguments**

object	The request object to check.
--------	------------------------------

**Value**

TRUE if the object is valid or a string with the reason why it is not

---

check_reactome_url	<i>check_reactome_url</i>
--------------------	---------------------------

---

**Description**

Makes sure the passed URL is valid. If not URL is passed, the one stored in the options is retrieved

**Usage**

```
check_reactome_url(reactome_url)
```

**Arguments**

reactome\_url    character The URL to test. If NULL the URL is retrieved from the options.

**Value**

character The potentially cleaned / retrieved URL with a trailing "/"

---

convert_reactome_result	<i>Convert the Reactome JSON result to a ReactomeAnalysisResult object</i>
-------------------------	--

---

**Description**

Convert the Reactome JSON result to a ReactomeAnalysisResult object

**Usage**

```
convert_reactome_result(reactome_result)
```

**Arguments**

reactome\_result  
                  The JSON result already converted to R objects (name list)

**Value**

A `ReactomeAnalysisResult` object

---

data\_frame\_as\_string    *Converts a data.frame to a string representation*

---

**Description**

A data.frame is converted into a single string using ‘\t’ (the characters, not tab) as field delimiter and ‘\n’ (the characters, not newline) as line delimiter

**Usage**

```
data_frame_as_string(data)
```

**Arguments**

data                    The data.frame to convert

**Value**

A string representing the passed data.frame

---

fetch\_public\_data    *fetch\_public\_data*

---

**Description**

Loads an already available public dataset from ReactomeGSA and returns it as a Biobase::ExpressionSet object.

**Usage**

```
fetch_public_data(dataset_entry, reactome_url)
```

**Arguments**

dataset\_entry    The entry of the respective dataset as returned by the [find\\_public\\_datasets](#) function.

reactome\_url    URL of the Reactome API Server. Overwrites the URL set in the ‘reactome\_gsa.url’ option. Specific ports can be set using the standard URL specification (for example <http://your.service:1234>)

**Value**

The loaded data as an ExpressionSet object.

---

find\_public\_datasets    *find\_public\_datasets*

---

## Description

Search for a public dataset in the resources supported by ReactomeGSA as external data sources.

## Usage

```
find_public_datasets(  
  search_term,  
  species = "Homo sapiens",  
  reactome_url = NULL  
)
```

## Arguments

search_term	The search terms as a single string. Multiple words (seperated by a space) are combined by an "AND".
species	Limit the search to selected species. The complete list of available species can be retrieved through <a href="#">get_public_species</a> . By default, entries as limited to human datasets.
reactome_url	URL of the Reactome API Server. Overwrites the URL set in the 'reactome_gsa.url' option. Specific ports can be set using the standard URL specification (for example <a href="http://your.service:1234">http://your.service:1234</a> )

## Value

A data.frame containing a list of datasets found through the search.

## Examples

```
# search for any public dataset relating to BRAF in melanoma  
melanoma_datasets <- find_public_datasets("melanoma braf")  
  
# it is also possible to limit this to another species than human  
melanoma_mouse <- find_public_datasets("melanoma", species = "Mus musculus")  
  
# the list of available species can be retrieved using get_public_species  
all_species <- get_public_species()  
  
# datasets can then be loaded using the load_public_dataset function
```

---

`get_dataset_loading_status`*Retrieves the status of the submitted dataset loading request*

---

**Description**

Retrieves the status of the submitted dataset loading request

**Usage**

```
get_dataset_loading_status(loading_id, reactome_url = NULL)
```

**Arguments**

<code>loading_id</code>	The dataset loading process' id
<code>reactome_url</code>	URL of the Reactome API Server. Overwrites the URL set in the 'reactome_gsa.url' option. Specific ports can be set using the standard URL specification (for example <code>http://your.service:1234</code> )

**Value**

A list containing the id, status (can be "running", "complete", "failed"), description, and completed (numeric between 0 - 1)

---

`get_fc_for_dataset`     *get\_fc\_for\_dataset*

---

**Description**

Retrieve the fold-changes for all pathways of the defined dataset

**Usage**

```
get_fc_for_dataset(dataset, pathway_result)
```

**Arguments**

<code>dataset</code>	Name of the dataset to retrieve the fold changes for.
<code>pathway_result</code>	The data.frame created by the pathways function.

**Value**

A vector of fold-changes

---

get\_is\_sig\_dataset     *get\_is\_sig\_dataset*

---

**Description**

Determines how significant a pathway is across the datasets. Returns the lowest significance.

**Usage**

```
get_is_sig_dataset(dataset, pathway_result)
```

**Arguments**

dataset             Name of the dataset  
pathway\_result     data.frame created by the pathways function

**Value**

A vector with 3=non-significant, 2= $p \leq 0.05$ , 1= $p < 0.01$

---

get\_public\_species     *get\_public\_species*

---

**Description**

Return the list of found species labels in the supported public data resources

**Usage**

```
get_public_species(reactome_url = NULL)
```

**Arguments**

reactome\_url        URL of the Reactome API Server. Overwrites the URL set in the 'reactome\_gsa.url' option. Specific ports can be set using the standard URL specification (for example `http://your.service:1234`)

**Value**

A vector of species strings.

**Examples**

```
# get the available species
available_species <- get_public_species()

# inspect the first 1 - 3 entries
available_species[1:3]
```

---

`get_reactome_analysis_result`

*Retrieves the result of the submitted analysis using [perform\\_reactome\\_analysis](#)*

---

**Description**

The result is only available if [get\\_reactome\\_analysis\\_status](#) indicates that the analysis is complete.

**Usage**

```
get_reactome_analysis_result(analysis_id, reactome_url = NULL)
```

**Arguments**

<code>analysis_id</code>	The running analysis' id
<code>reactome_url</code>	URL of the Reactome API Server. Overwrites the URL set in the 'reactome_gsa.url' option. Specific ports can be set using the standard URL specification (for example <a href="#">http://your.service:1234</a> )

**Value**

The result object

---

`get_reactome_analysis_status`

*Retrieves the status of the submitted analysis using [start\\_reactome\\_analysis](#)*

---

**Description**

Retrieves the status of the submitted analysis using [start\\_reactome\\_analysis](#)

**Usage**

```
get_reactome_analysis_status(analysis_id, reactome_url = NULL)
```

**Arguments**

<code>analysis_id</code>	The running analysis' id
<code>reactome_url</code>	URL of the Reactome API Server. Overwrites the URL set in the 'reactome_gsa.url' option. Specific ports can be set using the standard URL specification (for example <a href="#">http://your.service:1234</a> )

**Value**

A list containing the id, status (can be "running", "complete", "failed"), description, and completed (numeric between 0 - 1)

---

`get_reactome_data_types`*ReactomeGSA supported data types*

---

**Description**

ReactomeGSA supported data types

**Usage**

```
get_reactome_data_types(  
  print_types = TRUE,  
  return_result = FALSE,  
  reactome_url = NULL  
)
```

**Arguments**

<code>print_types</code>	If set to TRUE (default) a (relatively) nice formatted version of the result is printed.
<code>return_result</code>	If set to TRUE, the result is returned as a data.frame (see below)
<code>reactome_url</code>	URL of the Reactome API Server. Overwrites the URL set in the 'reactome_gsa.url' option. Specific ports can be set using the standard URL specification (for example <code>http://your.service:1234</code> )

**Value**

A data.frame containing one row per data type with its id and description.

**Author(s)**

Johannes Griss

**See Also**

Other Reactome Service functions: [get\\_reactome\\_methods\(\)](#)

**Examples**

```
# retrieve the available data types  
available_types <- get_reactome_data_types(print_types = FALSE, return_result = TRUE)  
  
# print all data type ids  
available_types$id  
  
# simply print the available methods  
get_reactome_data_types()
```



---

get\_reactome\_methods    *get\_reactome\_methods*

---

## Description

Returns all available analysis methods from the Reactome analysis service.

## Usage

```
get_reactome_methods(  
    print_methods = TRUE,  
    print_details = FALSE,  
    return_result = FALSE,  
    method = NULL,  
    reactome_url = NULL  
)
```

## Arguments

<code>print_methods</code>	If set to TRUE (default) a (relatively) nice formatted version of the result is printed.
<code>print_details</code>	If set to TRUE detailed information about every method, including available parameters and description are displayed. This does not affect the data returned if <code>return_result</code> is TRUE.
<code>return_result</code>	If set to TRUE, the result is returned as a data.frame (see below)
<code>method</code>	If set to a method's id, only information for this method will be shown. This is especially useful if detailed information about a single method should be retrieved. This does not affect the data returned if <code>return_result</code> is TRUE.
<code>reactome_url</code>	URL of the Reactome API Server. Overwrites the URL set in the 'reactome_gsa.url' option. Specific ports can be set using the standard URL specification (for example <code>http://your.service:1234</code> )

## Details

Every method has a type, a scope, and sometimes a list of allowed values. The type (string, int = integer, float) define the expected data type. The **scope** defines at what level the parameter can be set. *dataset* level parameters can be set at the dataset level (using the [add\\_dataset](#) function) or at the analysis request level (using [set\\_parameters](#)). If these parameters are set at the analysis request level, this overwrites the default value for all datasets. *analysis* and *global* level parameters must only be set at the analysis request level using [set\\_parameters](#). The difference between these two types of parameters is that while *analysis* parameters influence the results, *global* parameters only influence the behaviour of the analysis system (for example whether a Reactome visualization is created).

## Value

If `return_result` is set to TRUE, a data.frame with one row per method. Each method has a name, description, and (optional) a list of parameters. Parameters again have a name, type, and description.

**Author(s)**

Johannes Griss

**See Also**

Other Reactome Service functions: [get\\_reactome\\_data\\_types\(\)](#)

**Examples**

```
# retrieve the available methods only in an object
available_methods <- get_reactome_methods(print_methods = FALSE, return_result = TRUE)

# print all method names
available_methods$name

# list all parameters for the first method
first_method_parameters <- available_methods[1, "parameters"]
first_method_parameters

# simply print the available methods
get_reactome_methods()

# get the details for PADOG
get_reactome_methods(print_details = TRUE, method = "PADOG")
```

---

get\_result

*get\_result*

---

**Description**

Retrieves a result from a [ReactomeAnalysisResult](#) object.

**Usage**

```
get_result(x, type, name)
```

**Arguments**

x	ReactomeAnalysisResult.
type	the type of result. Use <a href="#">result_types</a> to retrieve all available types.
name	the name of the result. Use <a href="#">names</a> to retrieve all available results.

**Value**

A data.frame containing the respective result.

**See Also**

Other ReactomeAnalysisResult functions: [names](#), [ReactomeAnalysisResult-method](#), [open\\_reactome\(\)](#), [pathways\(\)](#), [plot\\_correlations\(\)](#), [plot\\_gsva\\_heatmap\(\)](#), [plot\\_gsva\\_pathway\(\)](#), [plot\\_heatmap\(\)](#), [plot\\_volcano\(\)](#), [reactome\\_links\(\)](#), [result\\_types\(\)](#)

## Examples

```
# load an example result object
library(ReactomeGSA.data)
data(griss_melanoma_result)

# get the available result types
result_types(griss_melanoma_result)

# get the dataset names
names(griss_melanoma_result)

# get the fold_changes for the first dataset
prot_fc <- get_result(griss_melanoma_result, type = "fold_changes", name = "proteomics")

head(prot_fc)
```

---

get\_result,ReactomeAnalysisResult-method  
*ReactomeAnalysisResult - get\_result*

---

## Description

Retrieves a result from a [ReactomeAnalysisResult](#) object.

## Usage

```
## S4 method for signature 'ReactomeAnalysisResult'
get_result(x, type, name)
```

## Arguments

x	ReactomeAnalysisResult.
type	the type of result. Use <a href="#">result_types</a> to retrieve all available types.
name	the name of the result. Use <a href="#">names</a> to retrieve all available results.

## Value

A data.frame containing the respective result.

## See Also

Other ReactomeAnalysisResult functions: [names](#), [ReactomeAnalysisResult-method](#), [open\\_reactome\(\)](#), [pathways\(\)](#), [plot\\_correlations\(\)](#), [plot\\_gsva\\_heatmap\(\)](#), [plot\\_gsva\\_pathway\(\)](#), [plot\\_heatmap\(\)](#), [plot\\_volcano\(\)](#), [reactome\\_links\(\)](#), [result\\_types\(\)](#)

## Examples

```
# load an example result object
library(ReactomeGSA.data)
data(griss_melanoma_result)

# get the available result types
```

```

result_types(griss_melanoma_result)

# get the dataset names
names(griss_melanoma_result)

# get the fold_changes for the first dataset
prot_fc <- get_result(griss_melanoma_result, type = "fold_changes", name = "proteomics")

head(prot_fc)

```

---

is_gsva_result	<i>is_gsva_result</i>
----------------	-----------------------

---

### Description

is\_gsva\_result

### Usage

```
is_gsva_result(object)
```

### Arguments

object            A [ReactomeAnalysisResult](#) object

### Value

Boolean indicating whether the object is a GSVA result.

---

load_public_dataset	<i>load_public_dataset</i>
---------------------	----------------------------

---

### Description

Loads a public dataset that was found through the [find\\_public\\_datasets](#) function. The dataset is returned as a Biobase ExpressionSet object.

### Usage

```
load_public_dataset(dataset_entry, verbose = FALSE, reactome_url = NULL)
```

### Arguments

dataset_entry	The entry of the respective dataset as returned by the <a href="#">find_public_datasets</a> function.
verbose	If set to TRUE, status messages and a status bar are displayed.
reactome_url	URL of the Reactome API Server. Overwrites the URL set in the 'reactome_gsa.url' option. Specific ports can be set using the standard URL specification (for example <a href="http://your.service:1234">http://your.service:1234</a> )

**Value**

The loaded data as an ExpressionSet object.

**Examples**

```
# As a first step, you need to find available datasets
available_datasets <- find_public_datasets("psoriasis tnf")

# have a quick look at the found datasets
available_datasets[, c("id", "title")]

# load the first one, use the whole row of the found datasets
# data.frame as the parameter
dataset_1 <- load_public_dataset(available_datasets[1,], verbose = TRUE)
```

---

names,ReactomeAnalysisResult-method

*ReactomeAnalysisResult - names*

---

**Description**

Retrieves the names of the contained datasets within an [ReactomeAnalysisResult](#) object.

**Usage**

```
## S4 method for signature 'ReactomeAnalysisResult'
names(x)
```

**Arguments**

x                    ReactomeAnalysisResult.

**Value**

character vector with the names of the contained datasets

**See Also**

Other ReactomeAnalysisResult functions: [get\\_result\(\)](#), [open\\_reactome\(\)](#), [pathways\(\)](#), [plot\\_correlations\(\)](#), [plot\\_gsva\\_heatmap\(\)](#), [plot\\_gsva\\_pathway\(\)](#), [plot\\_heatmap\(\)](#), [plot\\_volcano\(\)](#), [reactome\\_links\(\)](#), [result\\_types\(\)](#)

**Examples**

```
# load an example result object
library(ReactomeGSA.data)
data(griss_melanoma_result)

# get the names of the available datasets
names(griss_melanoma_result)
```

---

open_reactome	<i>open_reactome</i>
---------------	----------------------

---

**Description**

Opens the specified Reactome visualization in the system's default browser.

**Usage**

```
open_reactome(x, ...)
```

**Arguments**

x	ReactomeAnalysisResult.
...	Additional parameters passed to downstream functions.

**Value**

The opened link

**See Also**

Other ReactomeAnalysisResult functions: [get\\_result\(\)](#), [names](#), [ReactomeAnalysisResult-method](#), [pathways\(\)](#), [plot\\_correlations\(\)](#), [plot\\_gsva\\_heatmap\(\)](#), [plot\\_gsva\\_pathway\(\)](#), [plot\\_heatmap\(\)](#), [plot\\_volcano\(\)](#), [reactome\\_links\(\)](#), [result\\_types\(\)](#)

**Examples**

```
# Note: This function only works with a newly created result
# since the visualization links only stay active for 7 days

# load an example result
library(ReactomeGSA.data)
data(griss_melanoma_result)

# get the reactome link - this does only work
# with new results
# open_reactome(griss_melanoma_result)
```

---

open_reactome, ReactomeAnalysisResult-method
<i>open_reactome - ReactomeAnalysisResult</i>

---

**Description**

Opens the specified Reactome visualization in the system's default browser.

**Usage**

```
## S4 method for signature 'ReactomeAnalysisResult'
open_reactome(x, n_visualization = 1, ...)
```

**Arguments**

`x` ReactomeAnalysisResult.

`n_visualization` numeric The index of the visualization to display (default 1). Use [reactome\\_links](#) to retrieve all available visualizations and their index. By default, the first visualization is opened.

`...` Additional parameters passed to downstream functions.

**Value**

The opened link

**See Also**

Other ReactomeAnalysisResult functions: [get\\_result\(\)](#), [names](#), [ReactomeAnalysisResult-method](#), [pathways\(\)](#), [plot\\_correlations\(\)](#), [plot\\_gsva\\_heatmap\(\)](#), [plot\\_gsva\\_pathway\(\)](#), [plot\\_heatmap\(\)](#), [plot\\_volcano\(\)](#), [reactome\\_links\(\)](#), [result\\_types\(\)](#)

**Examples**

```
# Note: This function only works with a newly created result
# since the visualization links only stay active for 7 days

# load an example result
library(ReactomeGSA.data)
data(griss_melanoma_result)

# get the reactome link - this does only work
# with new results
# open_reactome(griss_melanoma_result)
```

---

pathways

*pathways*

---

**Description**

Combines and returns the pathways of all analysed datasets.

**Usage**

```
pathways(x, ...)
```

**Arguments**

`x` ReactomeAnalysisResult.

`...` Additional parameters for specific implementations.

**Value**

A `data.frame` containing all merged pathways.

**See Also**

Other ReactomeAnalysisResult functions: [get\\_result\(\)](#), [names, ReactomeAnalysisResult-method](#), [open\\_reactome\(\)](#), [plot\\_correlations\(\)](#), [plot\\_gsva\\_heatmap\(\)](#), [plot\\_gsva\\_pathway\(\)](#), [plot\\_heatmap\(\)](#), [plot\\_volcano\(\)](#), [reactome\\_links\(\)](#), [result\\_types\(\)](#)

**Examples**

```
# load an example result
library(ReactomeGSA.data)
data(griss_melanoma_result)

# get the combined pathway result
pathway_result <- pathways(griss_melanoma_result)

head(pathway_result)
```

---

pathways, ReactomeAnalysisResult-method  
*ReactomeAnalysisResult - pathways*

---

**Description**

Combines and returns the pathways of all analysed datasets.

**Usage**

```
## S4 method for signature 'ReactomeAnalysisResult'
pathways(x, p = 0.01, order_by = NULL, ...)
```

**Arguments**

x	ReactomeAnalysisResult.
p	Minimum p-value to accept a pathway as significantly regulated. Default is 0.01.
order_by	Name of the dataset to sort the result list by. By default, the results are sorted based on the first dataset.
...	Additional parameters for specific implementations.

**Value**

A data.frame containing all merged pathways.

**See Also**

Other ReactomeAnalysisResult functions: [get\\_result\(\)](#), [names, ReactomeAnalysisResult-method](#), [open\\_reactome\(\)](#), [plot\\_correlations\(\)](#), [plot\\_gsva\\_heatmap\(\)](#), [plot\\_gsva\\_pathway\(\)](#), [plot\\_heatmap\(\)](#), [plot\\_volcano\(\)](#), [reactome\\_links\(\)](#), [result\\_types\(\)](#)



## Examples

```
# load an example result
library(ReactomeGSA.data)
data(griss_melanoma_result)

# get the combined pathway result
pathway_result <- pathways(griss_melanoma_result)

head(pathway_result)
```

---

```
perform_reactome_analysis
      Perform a Reactome Analysis
```

---

## Description

This function wraps all steps required to perform an Analysis using the Reactome Analysis Service. It submits the passed [ReactomeAnalysisRequest](#) object to the Reactome Analysis Service API, checks the submitted analysis' status and returns the result once the analysis is complete.

## Usage

```
perform_reactome_analysis(
  request,
  verbose = TRUE,
  compress = TRUE,
  reactome_url = NULL
)
```

## Arguments

request	<a href="#">ReactomeAnalysisRequest</a> to submit.
verbose	logical. If FALSE status messages are not printed to the console.
compress	logical. If TRUE (default) the request data is compressed before submitting it to the ReactomeGSA API. This is the generally recommended way and should only be disabled for debugging purposes.
reactome_url	URL of the Reactome API Server. Overwrites the URL set in the 'reactome_gsa.url' option. Specific ports can be set using the standard URL specification (for example <code>http://your.service:1234</code> )

## Value

The analysis' result

## Examples

```
# create a request using Camera as an analysis
library(ReactomeGSA.data)
data(griss_melanoma_proteomics)

my_request <- ReactomeAnalysisRequest(method = "Camera")
```

```
# set maximum missing values to 0.5 and do not create any reactome visualizations
my_request <- set_parameters(request = my_request,
                             max_missing_values = 0.5,
                             create_reactome_visualization = FALSE)

# add the dataset
my_request <- add_dataset(request = my_request,
                          expression_values = griss_melanoma_proteomics,
                          name = "Proteomics",
                          type = "proteomics_int",
                          comparison_factor = "condition",
                          comparison_group_1 = "MOCK",
                          comparison_group_2 = "MCM",
                          additional_factors = c("cell.type", "patient.id"))

# perform the analysis
my_result <- perform_reactome_analysis(request = my_request, verbose = FALSE)
```

---

plot\_correlations      *plot\_correlations*

---

## Description

Plots correlations of the average fold-changes of all pathways between the different datasets. This function is only available to GSA based results (not GSVA ones).

## Usage

```
plot_correlations(x, hide_non_sig = FALSE)
```

## Arguments

**x**                      ReactomeAnalysisResult. The result object to use as input  
**hide\_non\_sig**        If set, non-significant pathways are not shown.

## Value

A list of ggplot2 plot objects representing one plot per combination

## See Also

Other ReactomeAnalysisResult functions: [get\\_result\(\)](#), [names, ReactomeAnalysisResult-method](#), [open\\_reactome\(\)](#), [pathways\(\)](#), [plot\\_gsva\\_heatmap\(\)](#), [plot\\_gsva\\_pathway\(\)](#), [plot\\_heatmap\(\)](#), [plot\\_volcano\(\)](#), [reactome\\_links\(\)](#), [result\\_types\(\)](#)

## Examples

```
# load an example result
library(ReactomeGSA.data)
data(griss_melanoma_result)

# create the correlation plots
```

```
plot_objs <- plot_correlations(griss_melanoma_result)

# only one plot created for this result as it contains two datasets
length(plot_objs)

# show the plot using `print(plot_objs[[1]])`
```

---

*plot\_correlations, ReactomeAnalysisResult-method*  
*plot\_correlations - ReactomeAnalysisResult*

---

### **Description**

Plots correlations of the average fold-changes of all pathways between the different datasets. This function is only available to GSA based results (not GSVA ones).

### **Usage**

```
## S4 method for signature 'ReactomeAnalysisResult'
plot_correlations(x, hide_non_sig = FALSE)
```

### **Arguments**

`x` ReactomeAnalysisResult. The result object to use as input  
`hide_non_sig` If set, non-significant pathways are not shown.

### **Value**

A list of ggplot2 plot objects representing one plot per combination

### **See Also**

Other ReactomeAnalysisResult functions: [get\\_result\(\)](#), [names, ReactomeAnalysisResult-method](#), [open\\_reactome\(\)](#), [pathways\(\)](#), [plot\\_gsva\\_heatmap\(\)](#), [plot\\_gsva\\_pathway\(\)](#), [plot\\_heatmap\(\)](#), [plot\\_volcano\(\)](#), [reactome\\_links\(\)](#), [result\\_types\(\)](#)

### **Examples**

```
# load an example result
library(ReactomeGSA.data)
data(griss_melanoma_result)

# create the correlation plots
plot_objs <- plot_correlations(griss_melanoma_result)

# only one plot created for this result as it contains two datasets
length(plot_objs)

# show the plot using `print(plot_objs[[1]])`
```

---

plot\_gsva\_heatmap      *plot\_gsva\_heatmap*

---

### Description

Plots pathway expression values / sample as a heatmap. Ranks pathways based on their expression difference.

### Usage

```
plot_gsva_heatmap(
  object,
  pathway_ids = NULL,
  max_pathways = 20,
  truncate_names = TRUE,
  ...
)
```

### Arguments

object	The <a href="#">ReactomeAnalysisResult</a> object.
pathway_ids	A vector of pathway ids. If set, only these pathways are included in the plot.
max_pathways	The maximum number of pathways to include. Only takes effect if pathway_ids is not set.
truncate_names	If set, long pathway names are truncated.
...	Additional parameters passed to specific implementations.

### Value

None

### See Also

Other [ReactomeAnalysisResult](#) functions: [get\\_result\(\)](#), [names](#), [ReactomeAnalysisResult-method](#), [open\\_reactome\(\)](#), [pathways\(\)](#), [plot\\_correlations\(\)](#), [plot\\_gsva\\_pathway\(\)](#), [plot\\_heatmap\(\)](#), [plot\\_volcano\(\)](#), [reactome\\_links\(\)](#), [result\\_types\(\)](#)

### Examples

```
# load the scRNA-seq example data
library(ReactomeGSA.data)
data(jerby_b_cells)

# perform the GSEA analysis
gsva_result <- analyse_sc_clusters(jerby_b_cells, verbose = FALSE)

# plot the heatmap
relevant_pathways <- c("R-HSA-983170", "R-HSA-388841", "R-HSA-2132295",
  "R-HSA-983705", "R-HSA-5690714")
plot_gsva_heatmap(gsva_result,
  pathway_ids = relevant_pathways, # limit to these pathways
```

```
margins = c(6,30), # adapt the figure margins in heatmap.2
dendrogram = "col", # only plot column dendrogram
scale = "row", # scale for each pathway
key = FALSE, # don't display the color key
lwid=c(0.1,4) # remove the white space on the left
```

---

plot\_gsva\_heatmap,ReactomeAnalysisResult-method

*plot\_gsva\_heatmap - ReactomeAnalysisResult function*

---

## Description

Plots pathway expression values / sample as a heatmap. Ranks pathways based on their expression difference.

## Usage

```
## S4 method for signature 'ReactomeAnalysisResult'
plot_gsva_heatmap(
  object,
  pathway_ids = NULL,
  max_pathways = 20,
  truncate_names = TRUE,
  ...
)
```

## Arguments

object	The <a href="#">ReactomeAnalysisResult</a> object.
pathway_ids	A vector of pathway ids. If set, only these pathways are included in the plot.
max_pathways	The maximum number of pathways to include. Only takes effect if pathway_ids is not set.
truncate_names	If set, long pathway names are truncated.
...	Additional parameters passed to the heatmap.2 function.

## Value

None

## See Also

Other ReactomeAnalysisResult functions: [get\\_result\(\)](#), [names,ReactomeAnalysisResult-method](#), [open\\_reactome\(\)](#), [pathways\(\)](#), [plot\\_correlations\(\)](#), [plot\\_gsva\\_pathway\(\)](#), [plot\\_heatmap\(\)](#), [plot\\_volcano\(\)](#), [reactome\\_links\(\)](#), [result\\_types\(\)](#)

## Examples

```
# load the scRNA-seq example data
library(ReactomeGSA.data)
data(jerby_b_cells)

# perform the GSEA analysis
gsva_result <- analyse_sc_clusters(jerby_b_cells, verbose = FALSE)

# plot the heatmap
relevant_pathways <- c("R-HSA-983170", "R-HSA-388841", "R-HSA-2132295",
                      "R-HSA-983705", "R-HSA-5690714")
plot_gsva_heatmap(gsva_result,
                  pathway_ids = relevant_pathways, # limit to these pathways
                  margins = c(6,30), # adapt the figure margins in heatmap.2
                  dendrogram = "col", # only plot column dendrogram
                  scale = "row", # scale for each pathway
                  key = FALSE, # don't display the color key
                  lwid=c(0.1,4)) # remove the white space on the left
```

---

plot\_gsva\_pathway      *plot\_gsva\_pathway*

---

## Description

Plots the expression of a specific pathway from a ssGSEA result.

## Usage

```
plot_gsva_pathway(object, pathway_id, ...)
```

## Arguments

object	The <a href="#">ReactomeAnalysisResult</a> object.
pathway_id	The pathway's id
...	Additional parameters for specific implementations.

## Value

A ggplot2 plot object

## See Also

Other [ReactomeAnalysisResult](#) functions: [get\\_result\(\)](#), [names, ReactomeAnalysisResult-method](#), [open\\_reactome\(\)](#), [pathways\(\)](#), [plot\\_correlations\(\)](#), [plot\\_gsva\\_heatmap\(\)](#), [plot\\_heatmap\(\)](#), [plot\\_volcano\(\)](#), [reactome\\_links\(\)](#), [result\\_types\(\)](#)

### Examples

```
# load the scRNA-seq example data
library(ReactomeGSA.data)
data(jerby_b_cells)

# perform the GSVA analysis
gsva_result <- analyse_sc_clusters(jerby_b_cells, verbose = FALSE)

# create the plot
plot_obj <- plot_gsva_pathway(gsva_result, "R-HSA-389542")
```

---

plot\_gsva\_pathway, ReactomeAnalysisResult-method  
*ReactomeAnalysisResult - plot\_gsva\_pathway*

---

### Description

Plots the expression of a specific pathway from a ssGSEA result.

### Usage

```
## S4 method for signature 'ReactomeAnalysisResult'
plot_gsva_pathway(object, pathway_id, ...)
```

### Arguments

object	The <a href="#">ReactomeAnalysisResult</a> object.
pathway_id	The pathway's id
...	Additional parameters for specific implementations.

### Value

A ggplot2 plot object

### See Also

Other ReactomeAnalysisResult functions: [get\\_result\(\)](#), [names, ReactomeAnalysisResult-method](#), [open\\_reactome\(\)](#), [pathways\(\)](#), [plot\\_correlations\(\)](#), [plot\\_gsva\\_heatmap\(\)](#), [plot\\_heatmap\(\)](#), [plot\\_volcano\(\)](#), [reactome\\_links\(\)](#), [result\\_types\(\)](#)

### Examples

```
# load the scRNA-seq example data
library(ReactomeGSA.data)
data(jerby_b_cells)

# perform the GSVA analysis
gsva_result <- analyse_sc_clusters(jerby_b_cells, verbose = FALSE)

# create the plot
plot_obj <- plot_gsva_pathway(gsva_result, "R-HSA-389542")
```

---

plot_gsva_pca	<i>plot_gsva_pca</i>
---------------	----------------------

---

**Description**

Runs a Principal Component analysis (using `prcomp`) on the samples based on the pathway analysis results.

**Usage**

```
plot_gsva_pca(object, pathway_ids = NULL, ...)
```

**Arguments**

<code>object</code>	A <a href="#">ReactomeAnalysisResult</a> object containing a ssGSEA result
<code>pathway_ids</code>	A character vector of pathway ids. If set, only these pathways will be used for the PCA analysis.
<code>...</code>	Additional paramters passed to specific implementations.

**Value**

A `ggplot2` object representing the plot.

**Examples**

```
# load the scRNA-seq example data
library(ReactomeGSA.data)
data(jerby_b_cells)

# perform the GSVa analysis
gsva_result <- analyse_sc_clusters(jerby_b_cells, verbose = FALSE)
```

---

plot_gsva_pca, ReactomeAnalysisResult-method	<i>plot_gsva_pca - ReactomeAnalysisResult</i>
--	---

---

**Description**

Runs a Principal Component analysis (using `prcomp`) on the samples based on the pathway analysis results.

**Usage**

```
## S4 method for signature 'ReactomeAnalysisResult'
plot_gsva_pca(object, pathway_ids = NULL, ...)
```



**Arguments**

object	A <a href="#">ReactomeAnalysisResult</a> object containing a ssGSEA result
pathway_ids	A character vector of pathway ids. If set, only these pathways will be used for the PCA analysis.
...	Additional parameters are passed to prcomp

**Value**

A ggplot2 object representing the plot.

**Examples**

```
# load the scRNA-seq example data
library(ReactomeGSA.data)
data(jerby_b_cells)

# perform the GSVA analysis
gsva_result <- analyse_sc_clusters(jerby_b_cells, verbose = FALSE)
```

---

plot\_heatmap

*plot\_heatmap*


---

**Description**

Creates a heatmap to show which pathways are up- and down-regulated in different datasets

**Usage**

```
plot_heatmap(
  x,
  fdr = 0.01,
  max_pathways = 30,
  break_long_names = TRUE,
  return_data = FALSE
)
```

**Arguments**

x	<a href="#">ReactomeAnalysisResult</a> . The result object to use as input
fdr	numeric. The minimum FDR to consider a pathways as significantly regulated. (Default 0.01)
max_pathways	numeric. The maximum number of pathways to plot. Pathways are sorted based on in how many datasets they are significantly regulated. This has no effect if return_data is set to TRUE.
break_long_names	logical. If set, long pathway names are broken into two lines.
return_data	logical. If set, only the plotting data, but not the plot object itself is returned. This can be used to create customized plots that use the same data structure.

**Value**

A ggplot2 plot object representing the heatmap of pathways

**See Also**

Other ReactomeAnalysisResult functions: [get\\_result\(\)](#), [names, ReactomeAnalysisResult-method](#), [open\\_reactome\(\)](#), [pathways\(\)](#), [plot\\_correlations\(\)](#), [plot\\_gsva\\_heatmap\(\)](#), [plot\\_gsva\\_pathway\(\)](#), [plot\\_volcano\(\)](#), [reactome\\_links\(\)](#), [result\\_types\(\)](#)

**Examples**

```
# load an example result
library(ReactomeGSA.data)
data(griss_melanoma_result)

# create the heatmap plot
plot_obj <- plot_heatmap(griss_melanoma_result)

# show the plot
print(plot_obj)
```

---

`plot_heatmap, ReactomeAnalysisResult-method`

*plot\_heatmap - ReactomeAnalysisResult*

---

**Description**

Creates a heatmap to show which pathways are up- and down-regulated in different datasets

**Usage**

```
## S4 method for signature 'ReactomeAnalysisResult'
plot_heatmap(
  x,
  fdr = 0.01,
  max_pathways = 30,
  break_long_names = TRUE,
  return_data = FALSE
)
```

**Arguments**

<code>x</code>	ReactomeAnalysisResult. The result object to use as input
<code>fdr</code>	numeric. The minimum FDR to consider a pathways as significantly regulated. (Default 0.01)
<code>max_pathways</code>	numeric. The maximum number of pathways to plot. Pathways are sorted based on in how many datasets they are significantly regulated. This has no effect if <code>return_data</code> is set to TRUE.
<code>break_long_names</code>	logical. If set, long pathway names are broken into two lines.
<code>return_data</code>	logical. If set, only the plotting data, but not the plot object itself is returned. This can be used to create customized plots that use the same data structure.

**Value**

A ggplot2 plot object representing the heatmap of pathways

**See Also**

Other ReactomeAnalysisResult functions: [get\\_result\(\)](#), [names, ReactomeAnalysisResult-method](#), [open\\_reactome\(\)](#), [pathways\(\)](#), [plot\\_correlations\(\)](#), [plot\\_gsva\\_heatmap\(\)](#), [plot\\_gsva\\_pathway\(\)](#), [plot\\_volcano\(\)](#), [reactome\\_links\(\)](#), [result\\_types\(\)](#)

**Examples**

```
# load an example result
library(ReactomeGSA.data)
data(griss_melanoma_result)

# create the heatmap plot
plot_obj <- plot_heatmap(griss_melanoma_result)

# show the plot
print(plot_obj)
```

---

plot\_volcano

*plot\_volcano*

---

**Description**

Creates a volcano plot for the pathway analysis result. Every point represents one pathway, the x-axis the log fold-change and the y-axis the adjusted p-value (-log10).

**Usage**

```
plot_volcano(x, ...)
```

**Arguments**

**x** ReactomeAnalysisResult. The analysis result to plot the volcano plot for.  
**...** Additional parameters for specific implementations.

**Details**

This function is only available for GSA-based analysis results.

**Value**

A ggplot2 plot object representing the volcano plot.

**See Also**

Other ReactomeAnalysisResult functions: [get\\_result\(\)](#), [names, ReactomeAnalysisResult-method](#), [open\\_reactome\(\)](#), [pathways\(\)](#), [plot\\_correlations\(\)](#), [plot\\_gsva\\_heatmap\(\)](#), [plot\\_gsva\\_pathway\(\)](#), [plot\\_heatmap\(\)](#), [reactome\\_links\(\)](#), [result\\_types\(\)](#)

## Examples

```
# load an example result
library(ReactomeGSA.data)
data(griss_melanoma_result)

# create the volcano plot for the first dataset
plot_obj <- plot_volcano(griss_melanoma_result)

# display the plot using `print(plot_obj)`
```

---

plot\_volcano, ReactomeAnalysisResult-method  
*ReactomeAnalysisResult - plot\_volcano*

---

## Description

Creates a volcano plot for the pathway analysis result. Every point represents one pathway, the x-axis the log fold-change and the y-axis the adjusted p-value ( $-\log_{10}$ ).

## Usage

```
## S4 method for signature 'ReactomeAnalysisResult'
plot_volcano(x, dataset = 1, ...)
```

## Arguments

x	ReactomeAnalysisResult. The analysis result to plot the volcano plot for.
dataset	The name or index of the dataset to plot (first one by default).
...	Additional parameters for specific implementations.

## Details

This function is only available for GSA-based analysis results.

## Value

A ggplot2 plot object representing the volcano plot.

## See Also

Other ReactomeAnalysisResult functions: [get\\_result\(\)](#), [names, ReactomeAnalysisResult-method](#), [open\\_reactome\(\)](#), [pathways\(\)](#), [plot\\_correlations\(\)](#), [plot\\_gsva\\_heatmap\(\)](#), [plot\\_gsva\\_pathway\(\)](#), [plot\\_heatmap\(\)](#), [reactome\\_links\(\)](#), [result\\_types\(\)](#)

### Examples

```
# load an example result
library(ReactomeGSA.data)
data(griss_melanoma_result)

# create the volcano plot for the first dataset
plot_obj <- plot_volcano(griss_melanoma_result)

# display the plot using `print(plot_obj)`
```

---

`print,ReactomeAnalysisRequest-method`  
*print - ReactomeAnalysisRequest*

---

### Description

Shows a [ReactomeAnalysisRequest](#) object summary.

### Usage

```
## S4 method for signature 'ReactomeAnalysisRequest'
print(x, ...)
```

### Arguments

<code>x</code>	<a href="#">ReactomeAnalysisRequest</a>
<code>...</code>	Not used

### Value

The classname of the object

### Examples

```
library(methods)

request <- ReactomeAnalysisRequest(method = "Camera")
print(request)

# add additional parameters
request <- set_parameters(request, "max_missing_values" = 0.5)
show(request)
```

---

```
print, ReactomeAnalysisResult-method
      print - ReactomeAnalysisResult
```

---

**Description**

Displays basic information about the [ReactomeAnalysisResult](#) object.

**Usage**

```
## S4 method for signature 'ReactomeAnalysisResult'
print(x, ...)
```

**Arguments**

x	ReactomeAnalysisResult.
...	Not used

**Value**

character classname of the object

**Examples**

```
library(ReactomeGSA.data)
data(griss_melanoma_result)

print(griss_melanoma_result)
```

---

```
ReactomeAnalysisRequest
      ReactomeAnalysisRequest class
```

---

**Description**

This class is used to collect all information required to submit an analysis request to the Reactome Analysis System.

**Usage**

```
ReactomeAnalysisRequest(method)

ReactomeAnalysisRequest(method)
```

**Arguments**

method	character. Name of the method to use.
--------	---------------------------------------

**Value**

A ReactomeAnalysisRequest object.

**Slots**

method character. Name of the method to use

request\_object list. This slot should not be set manually. It stores the internal request representation and should be modified using the classes' functions. To add parameters, use [set\\_parameters, ReactomeAnalysisRequest-method](#)

**Examples**

```
library(ReactomeGSA.data)
library(methods)

# create the request method and specify its method
request <- ReactomeAnalysisRequest(method = "Camera")

# add a dataset to the request
data(griss_melanoma_proteomics)

request <- add_dataset(request = request,
  expression_values = griss_melanoma_proteomics,
  name = "Proteomics",
  type = "proteomics_int",
  comparison_factor = "condition",
  comparison_group_1 = "MOCK",
  comparison_group_2 = "MCM",
  additional_factors = c("cell.type", "patient.id"))

# to launch the actual analysis use the perform_reactome_analysis function
```

---

ReactomeAnalysisResult-class

*ReactomeAnalysisResult class*

---

**Description**

A ReactomeAnalysisResult object contains the pathway analysis results of all submitted datasets at once.

**Details**

This class represents a result retrieved from the Reactome Analysis Service. It is returned by [get\\_reactome\\_analysis\\_result](#) and its wrapper [perform\\_reactome\\_analysis](#). Generally, object of this class should not be created manually.

**Value**

A ReactomeAnalysisResult object.

**Slots**

reactome\_release The Reactome version used to create this result.

mappings Stores the mapping results that were generated for this analysis.

**results** A named list containing the actual analysis results for every dataset and possibly combined results as well.

**reactome\_links** Links pointing to reactome results as a list.

## Methods

**names**: Retrieves the names of all datasets in the result object

**result\_types**: Retrieves the available result types

**pathways**: Merges the pathway results of all analysed datasets.

**get\_result**: Retrieve a specific result as data.frame

**reactome\_links**: Displays / retrieves the URLs to the available visualizations in Reactome's pathway browser.

**open\_reactome**: Opens the specified Reactome visualization in the system's default browser.

## Examples

```
# load an example result object
library(ReactomeGSA.data)
data(griss_melanoma_result)

# retrieve the names of all datasets in the result
names(griss_melanoma_result)

# get the combined pathway result
pathway_result <- pathways(griss_melanoma_result)

# check which result types are available
result_types(griss_melanoma_result)

# get the fold changes for the first dataset
first_dataset_name <- names(griss_melanoma_result)[1]

first_fc <- get_result(griss_melanoma_result, "fold_changes", first_dataset_name)
```

---

reactome_links	<i>reactome_links</i>
----------------	-----------------------

---

## Description

Displays detailed information about the result visualizations in Reactome.

## Usage

```
reactome_links(x, ...)
```

## Arguments

x	ReactomeAnalysisResult.
...	Additional parameters for specific implementations.



**Value**

If return\_result is set to TRUE, a vector of the available visualizations.

**See Also**

Other ReactomeAnalysisResult functions: [get\\_result\(\)](#), [names, ReactomeAnalysisResult-method](#), [open\\_reactome\(\)](#), [pathways\(\)](#), [plot\\_correlations\(\)](#), [plot\\_gsva\\_heatmap\(\)](#), [plot\\_gsva\\_pathway\(\)](#), [plot\\_heatmap\(\)](#), [plot\\_volcano\(\)](#), [result\\_types\(\)](#)

**Examples**

```
# Note: This function only works with a newly created result
# since the visualization links only stay active for 7 days

# load an example result
library(ReactomeGSA.data)
data(griss_melanoma_result)

# get the reactome link - this does only work
# with new results
reactome_links(griss_melanoma_result)
```

---

reactome\_links, ReactomeAnalysisResult-method  
*ReactomeAnalysisResult - reactome\_links*

---

**Description**

Displays detailed information about the result visualizations in Reactome.

**Usage**

```
## S4 method for signature 'ReactomeAnalysisResult'
reactome_links(x, print_result = TRUE, return_result = FALSE)
```

**Arguments**

x	ReactomeAnalysisResult.
print_result	If set to FALSE the links are not printed to the console.
return_result	If TRUE the available visualizations are returned as a list containing named vectors for every visualization. These vectors' have a url, name, and optionally a description slot.

**Value**

If return\_result is set to TRUE, a vector of the available visualizations.

**See Also**

Other ReactomeAnalysisResult functions: [get\\_result\(\)](#), [names, ReactomeAnalysisResult-method](#), [open\\_reactome\(\)](#), [pathways\(\)](#), [plot\\_correlations\(\)](#), [plot\\_gsva\\_heatmap\(\)](#), [plot\\_gsva\\_pathway\(\)](#), [plot\\_heatmap\(\)](#), [plot\\_volcano\(\)](#), [result\\_types\(\)](#)

**Examples**

```
# Note: This function only works with a newly created result
# since the visualization links only stay active for 7 days

# load an example result
library(ReactomeGSA.data)
data(griss_melanoma_result)

# get the reactome link - this does only work
# with new results
reactome_links(griss_melanoma_result)
```

---

```
remove_dataset      remove_dataset
```

---

**Description**

Remove the dataset from the [ReactomeAnalysisRequest](#) object.

**Usage**

```
remove_dataset(x, dataset_name)
```

**Arguments**

x                    The [ReactomeAnalysisRequest](#) to remove the dataset from  
dataset\_name        character The dataset's name

**Value**

The updated [ReactomeAnalysisRequest](#)

---

```
remove_dataset, ReactomeAnalysisRequest-method
      remove_dataset - ReactomeAnalysisRequest
```

---

**Description**

Remove the dataset from the [ReactomeAnalysisRequest](#) object.

**Usage**

```
## S4 method for signature 'ReactomeAnalysisRequest'
remove_dataset(x, dataset_name)
```

**Arguments**

x                    The [ReactomeAnalysisRequest](#) to remove the dataset from  
dataset\_name        character The dataset's name

**Value**

The updated [ReactomeAnalysisRequest](#)

---

result_types	<i>result_types</i>
--------------	---------------------

---

### Description

Retrieves the available result types for the [ReactomeAnalysisResult](#) object. Currently, the Reactome Analysis System supports pathways and gene level fold\_changes as result types. Not all analysis methods return both data types though. Use the names function to find out which datasets are available in the result object.

### Usage

```
result_types(x)
```

### Arguments

x                    [ReactomeAnalysisResult](#).

### Value

A character vector of result types.

### See Also

Other [ReactomeAnalysisResult](#) functions: [get\\_result\(\)](#), [names](#), [ReactomeAnalysisResult-method](#), [open\\_reactome\(\)](#), [pathways\(\)](#), [plot\\_correlations\(\)](#), [plot\\_gsva\\_heatmap\(\)](#), [plot\\_gsva\\_pathway\(\)](#), [plot\\_heatmap\(\)](#), [plot\\_volcano\(\)](#), [reactome\\_links\(\)](#)

### Examples

```
# load an example result object
library(ReactomeGSA.data)
data(griss_melanoma_result)

# get the available result types
result_types(griss_melanoma_result)
```

---

result\_types, [ReactomeAnalysisResult-method](#)  
*ReactomeAnalysisResult - result\_types*

---

### Description

Retrieves the available result types for the [ReactomeAnalysisResult](#) object. Currently, the Reactome Analysis System supports pathways and gene level fold\_changes as result types. Not all analysis methods return both data types though. Use the names function to find out which datasets are available in the result object.

**Usage**

```
## S4 method for signature 'ReactomeAnalysisResult'
result_types(x)
```

**Arguments**

x                    ReactomeAnalysisResult.

**Value**

A character vector of result types.

**See Also**

Other ReactomeAnalysisResult functions: [get\\_result\(\)](#), [names](#), [ReactomeAnalysisResult-method](#), [open\\_reactome\(\)](#), [pathways\(\)](#), [plot\\_correlations\(\)](#), [plot\\_gsva\\_heatmap\(\)](#), [plot\\_gsva\\_pathway\(\)](#), [plot\\_heatmap\(\)](#), [plot\\_volcano\(\)](#), [reactome\\_links\(\)](#)

**Examples**

```
# load an example result object
library(ReactomeGSA.data)
data(griss_melanoma_result)

# get the available result types
result_types(griss_melanoma_result)
```

---

set\_method

*set\_method*

---

**Description**

Set the analysis method used by the [ReactomeAnalysisRequest](#)

**Usage**

```
set_method(request, method, ...)
```

**Arguments**

request            The [ReactomeAnalysisRequest](#) to adjust

method            The name of the method to use. Use [get\\_reactome\\_methods](#) to retrieve all available methods

...                Additional parameters passed to specific implementations

**Value**

The [ReactomeAnalysisRequest](#) with the adapted method

### Examples

```
# create a request using Camera as an analysis
data(griss_melanoma_proteomics)
library(methods)

my_request <- ReactomeAnalysisRequest(method = "Camera")

print(my_request)

# change the method to ssGSEA
my_request <- set_method(my_request, "ssGSEA")

print(my_request)
```

---

set\_method,ReactomeAnalysisRequest-method  
*set\_method - ReactomeAnalysisRequest*

---

### Description

Set the analysis method used by the [ReactomeAnalysisRequest](#)

### Usage

```
## S4 method for signature 'ReactomeAnalysisRequest'
set_method(request, method, ...)
```

### Arguments

request	The <a href="#">ReactomeAnalysisRequest</a> to adjust
method	The name of the method to use. Use <a href="#">get_reactome_methods</a> to retrieve all available methods
...	Additional parameters passed to specific implementations

### Value

The [ReactomeAnalysisRequest](#) with the adapted method

### Examples

```
# create a request using Camera as an analysis
data(griss_melanoma_proteomics)
library(methods)

my_request <- ReactomeAnalysisRequest(method = "Camera")

print(my_request)

# change the method to ssGSEA
my_request <- set_method(my_request, "ssGSEA")

print(my_request)
```

---

set_parameters	<i>set_parameters</i>
----------------	-----------------------

---

### Description

Sets the analysis parameters for the given [ReactomeAnalysisRequest](#). If the parameter is already set, it is overwritten. Use [get\\_reactome\\_methods](#) to get a list of all available parameters for each available method.

### Usage

```
set_parameters(request, ...)
```

### Arguments

request	The <a href="#">ReactomeAnalysisRequest</a> to set the parameters for.
...	Any name / value pair to set a parameter (see example). For a complete list of available parameters use <a href="#">get_reactome_methods</a>

### Details

Both, parameters with the scope "dataset" as well as "analysis" can be set on the analysis level. In this case, these parameters overwrite the system's default values. If a parameter with the scope "dataset" is defined again at the dataset level, this value will overwrite the analysis' scope value for the given dataset.

### Value

The modified [ReactomeAnalysisRequest](#) object

### Examples

```
library(methods)

# create a request object
request <- ReactomeAnalysisRequest(method = "Camera")

# add a parameter
request <- set_parameters(request, max_missing_values = 0.5, discrete_norm_function = "TMM")
```

---

set_parameters, ReactomeAnalysisRequest-method
<i>ReactomeAnalysisRequest - set_parameters</i>

---

### Description

Sets the analysis parameters for the given [ReactomeAnalysisRequest](#). If the parameter is already set, it is overwritten. Use [get\\_reactome\\_methods](#) to get a list of all available parameters for each available method.

**Usage**

```
## S4 method for signature 'ReactomeAnalysisRequest'  
set_parameters(request, ...)
```

**Arguments**

request	The <a href="#">ReactomeAnalysisRequest</a> to set the parameters for.
...	Any name / value pair to set a parameter (see example). For a complete list of available parameters use <a href="#">get_reactome_methods</a>

**Details**

Both, parameters with the scope "dataset" as well as "analysis" can be set on the analysis level. In this case, these parameters overwrite the system's default values. If a parameter with the scope "dataset" is defined again at the dataset level, this value will overwrite the analysis' scope value for the given dataset.

**Value**

The modified [ReactomeAnalysisRequest](#) object

**Examples**

```
library(methods)  
  
# create a request object  
request <- ReactomeAnalysisRequest(method = "Camera")  
  
# add a parameter  
request <- set_parameters(request, max_missing_values = 0.5, discrete_norm_function = "TMM")
```

---

show,ReactomeAnalysisRequest-method

*print - ReactomeAnalysisRequest*

---

**Description**

Shows a [ReactomeAnalysisRequest](#) object summary.

**Usage**

```
## S4 method for signature 'ReactomeAnalysisRequest'  
show(object)
```

**Arguments**

object	<a href="#">ReactomeAnalysisRequest</a>
--------	---

**Value**

The classname of the object

### Examples

```
library(methods)

request <- ReactomeAnalysisRequest(method = "Camera")
print(request)

# add additional parameters
request <- set_parameters(request, "max_missing_values" = 0.5)
show(request)
```

---

show, ReactomeAnalysisResult-method  
*show - ReactomeAnalysisResult*

---

### Description

Displays basic information about the [ReactomeAnalysisResult](#) object.

### Usage

```
## S4 method for signature 'ReactomeAnalysisResult'
show(object)
```

### Arguments

object            ReactomeAnalysisResult.

### Value

character classname of the object

### Examples

```
library(ReactomeGSA.data)
data(griss_melanoma_result)

show(griss_melanoma_result)
```

---

start\_reactome\_analysis  
*Start Reactome Analysis*

---

### Description

Submits a [ReactomeAnalysisRequest](#) to the Reactome Analysis Service API and returns the analysis id of the submitted job.

### Usage

```
start_reactome_analysis(request, compress = TRUE, reactome_url = NULL)
```



**Arguments**

request	<a href="#">ReactomeAnalysisRequest</a> object to submit.
compress	If set (default) the JSON request data is compressed using gzip.
reactome_url	URL of the Reactome API Server. Overwrites the URL set in the 'reactome_gsa.url' option. Specific ports can be set using the standard URL specification (for example <code>http://your.service:1234</code> )

**Details**

This function should only be used for very large requests that likely take a long time to complete. By default, users should use the [perform\\_reactome\\_analysis](#) function to run an analysis.

**Value**

character The analysis job's id.

```
#' @examples # create a request using Camera as an analysis library(ReactomeGSA.data) data(griss_melanoma_proteomics)
my_request <- ReactomeAnalysisRequest(method = "Camera")
# set maximum missing values to 0.5 and do not create any reactome visualizations my_request <-
set_parameters(request = my_request, max_missing_values = 0.5, create_reactome_visualization =
FALSE)
# add the dataset my_request <- add_dataset(request = my_request, expression_values = griss_melanoma_proteomics,
name = "Proteomics", type = "proteomics_int", comparison_factor = "condition", comparison_group_1
= "MOCK", comparison_group_2 = "MCM", additional_factors = c("cell.type", "patient.id")) #
start the analysis analysis_id <- start_reactome_analysis(my_request)
```

---

```
wait_for_loading_dataset
      wait_for_loading_dataset
```

---

**Description**

This function loops until the dataset is available. If verbose is set to TRUE, the progress is displayed in a status bar.

**Usage**

```
wait_for_loading_dataset(request, verbose, reactome_url)
```

**Arguments**

request	The http request object of the dataset loading request.
verbose	If set to TRUE, the progress is displayed as a status bar.
reactome_url	URL of the Reactome API Server. Overwrites the URL set in the 'reactome_gsa.url' option. Specific ports can be set using the standard URL specification (for example <code>http://your.service:1234</code> )

# Index

- \* **Reactome Service functions**
  - get\_reactome\_data\_types, 24
  - get\_reactome\_methods, 25
- \* **ReactomeAnalysisResult functions**
  - get\_result, 26
  - names, ReactomeAnalysisResult-method, 29
  - open\_reactome, 30
  - pathways, 31
  - plot\_correlations, 34
  - plot\_gsva\_heatmap, 36
  - plot\_gsva\_pathway, 38
  - plot\_heatmap, 41
  - plot\_volcano, 43
  - reactome\_links, 48
  - result\_types, 51
- \* **add\_dataset methods**
  - add\_dataset, 3
  - add\_dataset, ReactomeAnalysisRequest, data.frame-method, 5
  - add\_dataset, ReactomeAnalysisRequest, DGEList-method, 6
  - add\_dataset, ReactomeAnalysisRequest, EList-method, 8
  - add\_dataset, ReactomeAnalysisRequest, ExpressionSet-method, 10
  - add\_dataset, ReactomeAnalysisRequest, matrix-method, 11
- add\_dataset, 3, 6, 7, 9, 11, 12, 25
- add\_dataset, ReactomeAnalysisRequest, data.frame-method, 5
- add\_dataset, ReactomeAnalysisRequest, DGEList-method, 6
- add\_dataset, ReactomeAnalysisRequest, EList-method, 8
- add\_dataset, ReactomeAnalysisRequest, ExpressionSet-method, 10
- add\_dataset, ReactomeAnalysisRequest, matrix-method, 11
- analyse\_sc\_clusters, 13
- analyse\_sc\_clusters, Seurat-method, 14
- analyse\_sc\_clusters, SingleCellExperiment-method, 15
- break\_names, 17
- check\_reactome\_url, 18
- checkRequestValidity, 17
- convert\_reactome\_result, 18
- data\_frame\_as\_string, 19
- fetch\_public\_data, 19
- find\_public\_datasets, 19, 20, 28
- get\_dataset\_loading\_status, 21
- get\_fc\_for\_dataset, 21
- get\_is\_sig\_dataset, 22
- get\_public\_species, 20, 22
- get\_reactome\_analysis\_result, 23, 47
- get\_reactome\_analysis\_status, 23, 23
- get\_reactome\_data\_types, 3, 5, 7, 8, 10, 12, 24, 26
- get\_reactome\_methods, 24, 25, 52–55
- get\_result, 26, 29–32, 34–39, 42–44, 48, 49, 51, 52
- get\_result, ReactomeAnalysisResult-method, 27
- is\_gsva\_result, 28
- load\_public\_dataset, 28
- names, 26, 27, 48
- names, ReactomeAnalysisResult-method, 29
- open\_reactome, 26, 27, 29, 30, 32, 34–39, 42–44, 48, 49, 51, 52
- open\_reactome, ReactomeAnalysisResult-method, 30
- pathways, 26, 27, 29–31, 31, 34–39, 42–44, 48, 49, 51, 52
- pathways, ReactomeAnalysisResult-method, 32
- perform\_reactome\_analysis, 23, 33, 47, 57
- plot\_correlations, 26, 27, 29–32, 34, 36–39, 42–44, 49, 51, 52

- plot\_correlations, ReactomeAnalysisResult-method, 35
- plot\_gsva\_heatmap, 26, 27, 29–32, 34, 35, 36, 38, 39, 42–44, 49, 51, 52
- plot\_gsva\_heatmap, ReactomeAnalysisResult-method, 37
- plot\_gsva\_pathway, 26, 27, 29–32, 34–37, 38, 42–44, 49, 51, 52
- plot\_gsva\_pathway, ReactomeAnalysisResult-method, 39
- plot\_gsva\_pca, 40
- plot\_gsva\_pca, ReactomeAnalysisResult-method, 40
- plot\_heatmap, 26, 27, 29–32, 34–39, 41, 43, 44, 49, 51, 52
- plot\_heatmap, ReactomeAnalysisResult-method, 42
- plot\_volcano, 26, 27, 29–32, 34–39, 42, 43, 43, 49, 51, 52
- plot\_volcano, ReactomeAnalysisResult-method, 44
- print, ReactomeAnalysisRequest-method, 45
- print, ReactomeAnalysisResult-method, 46
  
- reactome\_links, 26, 27, 29–32, 34–39, 42–44, 48, 48, 51, 52
- reactome\_links, ReactomeAnalysisResult-method, 49
- ReactomeAnalysisRequest, 3, 4, 6, 7, 9, 11, 12, 33, 45, 46, 50, 52–57
- ReactomeAnalysisResult, 14–16, 18, 26–29, 36–41, 46, 51, 56
- ReactomeAnalysisResult  
(ReactomeAnalysisResult-class), 47
- ReactomeAnalysisResult-class, 47
- remove\_dataset, 50
- remove\_dataset, ReactomeAnalysisRequest-method, 50
- result\_types, 26, 27, 29–32, 34–39, 42–44, 48, 49, 51
- result\_types, ReactomeAnalysisResult-method, 51
  
- set\_method, 52
- set\_method, ReactomeAnalysisRequest-method, 53
- set\_parameters, 25, 54
- set\_parameters, ReactomeAnalysisRequest-method, 54