

# Package ‘easyreporting’

November 13, 2024

**Type** Package

**Title** Helps creating report for improving Reproducible Computational Research

**Version** 1.18.0

**Description** An S4 class for facilitating the automated creation of rmarkdown files inside other packages/software even without knowing rmarkdown language. Best if implemented in functions as ``recursive" style programming.

**License** Artistic-2.0

**Encoding** UTF-8

**biocViews** ReportWriting

**LazyData** false

**BugReports** <https://github.com/drighelli/easyreporting/issues>

**Imports** rmarkdown, methods, tools, shiny, rlang

**Suggests** distill, BiocStyle, knitr, readxl, edgeR, limma, EDASeq, statmod

**RoxygenNote** 7.1.1

**VignetteBuilder** knitr

**git\_url** <https://git.bioconductor.org/packages/easyreporting>

**git\_branch** RELEASE\_3\_20

**git\_last\_commit** 6762dd5

**git\_last\_commit\_date** 2024-10-29

**Repository** Bioconductor 3.20

**Date/Publication** 2024-11-12

**Author** Dario Righelli [cre, aut]

**Maintainer** Dario Righelli <dario.righelli@gmail.com>

## Contents

addResource . . . . .	2
addResource,easyreporting-method . . . . .	3
compile . . . . .	4
compile,easyreporting-method . . . . .	4
easyreporting . . . . .	5

erGUIVolcano . . . . .	6
getBibliography . . . . .	6
getBibliography,easyreporting-method . . . . .	7
getOptionsList . . . . .	8
getOptionsList,easyreporting-method . . . . .	8
getReportFilename . . . . .	9
getReportFilename,easyreporting-method . . . . .	9
initReportFilename . . . . .	10
initReportFilename,easyreporting-method . . . . .	11
makeOptionsList . . . . .	12
mkdCodeChunkCommented . . . . .	13
mkdCodeChunkCommented,easyreporting-method . . . . .	14
mkdCodeChunkComplete . . . . .	15
mkdCodeChunkComplete,easyreporting-method . . . . .	15
mkdCodeChunkEnd . . . . .	16
mkdCodeChunkEnd,easyreporting-method . . . . .	17
mkdCodeChunkSt . . . . .	18
mkdCodeChunkSt,easyreporting-method . . . . .	19
mkdCodeChunkTitledCommented . . . . .	20
mkdCodeChunkTitledCommented,easyreporting-method . . . . .	21
mkdGeneralMsg . . . . .	22
mkdGeneralMsg,easyreporting-method . . . . .	22
mkdGeneralTitledMsg . . . . .	23
mkdGeneralTitledMsg,easyreporting-method . . . . .	24
mkdSetGlobalOpts . . . . .	24
mkdSetGlobalOpts,easyreporting-method . . . . .	25
mkdSourceFiles . . . . .	25
mkdSourceFiles,easyreporting-method . . . . .	26
mkdTitle . . . . .	26
mkdTitle,easyreporting-method . . . . .	27
mkdVariableAssignment . . . . .	28
mkdVariableAssignment,easyreporting-method . . . . .	28
setBibliography . . . . .	29
setBibliography,easyreporting-method . . . . .	30
setOptionsList . . . . .	31
setOptionsList,easyreporting-method . . . . .	32

**Index** **34**

---

addResource	<i>addResource</i>
-------------	--------------------

---

**Description**

addResource

**Usage**

addResource(object, source, reference, description)

**Arguments**

object	an easyreporting class instance
source	a string indicating the reference (i.e. "GEO")
reference	a string indicanting the reference of the source (i.e. "GSE60231")
description	a natural language description

**Value**

an easyreporting class instance

**Examples**

```
rd <- easyreporting(filenamePath="./project_report",
                    title="example_report", author=c("It's me"))
rd <- addResource(rd, source="GEO", "GSE60231", "Transcriptome of BMDC to different antigen delivery systems")
## Not run:
compile(rd)

## End(Not run)
```

---

addResource,easyreporting-method  
*addResource*

---

**Description**

addResource

**Usage**

```
## S4 method for signature 'easyreporting'
addResource(object, source, reference, description)
```

**Arguments**

object	an easyreporting class instance
source	a string indicating the reference (i.e. "GEO")
reference	a string indicanting the reference of the source (i.e. "GSE60231")
description	a natural language description

**Value**

an easyreporting class instance

**Examples**

```
rd <- easyreporting(filenamePath="./project_report",
                    title="example_report", author=c("It's me"))
rd <- addResource(rd, source="GEO", "GSE60231", "Transcriptome of BMDC to different antigen delivery systems")
## Not run:
compile(rd)

## End(Not run)
```

compile

*compile*

---

**Description**

prints the sessionInfo and compiles the produced rmarkdown file into an HTML report.

**Usage**

```
compile(object)
```

**Arguments**

object            an easyreporting class object

**Value**

none

**Examples**

```
## Not run:
rd <- easyreporting(filenamePath="./project_report", title="example_report",
                    author=c("It's me"))
compile(rd)
## End(Not run)
```

---

compile,easyreporting-method*compile*

---

**Description**

prints the sessionInfo and compiles the rmarkdown file

**Usage**

```
## S4 method for signature 'easyreporting'
compile(object)
```

**Arguments**

object            an easyreporting class object

**Value**

none

## Examples

```
## Not run:
rd <- easyreporting(filenamePath="./project_report", title="example_report",
                    author=c("It's me"))
compile(rd)

## End(Not run)
```

---

easyreporting

*easyreporting*

---

## Description

An S4 class for managing rmarkdown report. Each instance describes an rmarkdown file.

## Usage

```
easyreporting(
  filenamePath,
  title,
  author,
  optionList = NULL,
  documentType = "rmarkdown::html_document",
  bibfile = ""
)

easyreporting(
  filenamePath,
  title,
  author,
  optionList = NULL,
  documentType = "rmarkdown::html_document",
  bibfile = ""
)
```

## Arguments

filenamePath	the path with the name of the rmarkdown.
title	the title of the report section.
author	the author(s) of the report.
optionList	a list of options for the general rmarkdown document.
documentType	type of report final document, if author(s) is a person it will be <code>distill::distill_article</code> ( <code>rmarkdown::html_document</code> default)
bibfile	a bibfile for bibliography.

## Value

an S4 `easyreporting` class instance

**Slots**

filenamePath the path with the name of the rmarkdown.  
 title the title of the report section.  
 author the author(s) of the report.  
 type of report final document, if author(s) is a person it will be `distill::distill_article`  
 (`rmarkdown::html_document` default)  
 bibfile a bibfile for bibliography.  
 optionList a list of options for the general rmarkdown document.

**Examples**

```
rd <- easyreporting(filenamePath="./project_report",
                    title="example_report", author="It's me")
```

---

erGUIVolcano	<i>erGUIVolcano</i>
--------------	---------------------

---

**Description**

executes a Shiny GUI to perform a volcano plot and trace its executed functions.

**Usage**

```
erGUIVolcano()
```

**Value**

none

**Examples**

```
## Not run:
erGUIVolcano()

## End(Not run)
```

---

getBibliography	<i>getBibliography</i>
-----------------	------------------------

---

**Description**

returns the bibfile name attached to the object

**Usage**

```
getBibliography(object)
```

**Arguments**

object            an easyreporting class object

**Value**

none

**Examples**

```
## Not run:  
TBD  
  
## End(Not run)
```

---

*getBibliography,easyreporting-method*  
*getBibliography*

---

**Description**

returns the bibfile name attached to the object

**Usage**

```
## S4 method for signature 'easyreporting'  
getBibliography(object)
```

**Arguments**

object            an easyreporting class object

**Value**

none

**Examples**

```
example(easyreporting)  
getBibliography(rd)
```

---

`getOptionsList`            *getOptionsList*

---

**Description**

returns the optionList from the easyreporting class (see the makeOptionList function for more details).

**Usage**

```
getOptionsList(object)
```

**Arguments**

object            an easyreporting class object

**Value**

a list of options

**Examples**

```
## Not run:
rd <- easyreporting(filenamePath="./project_report", title="example_report",
                    author=c("It's me"))
optList <- getOptionsList(rd)

## End(Not run)
```

---

`getOptionsList,easyreporting-method`  
*getOptionsList*

---

**Description**

returns the optionList from the easyreporting class

**Usage**

```
## S4 method for signature 'easyreporting'
getOptionsList(object)
```

**Arguments**

object            an easyreporting class object

**Value**

a list of options



**Examples**

```
## Not run:
rd <- easyreporting(filenamePath="./project_report", title="example_report",
                    author=c("It's me"))
optList <- getOptionsList(rd)

## End(Not run)
```

---

`getReportFilename`      *getReportFilename*

---

**Description**

returns the filename with its path of the report generated by easyreporting

**Usage**

```
getReportFilename(object)
```

**Arguments**

object                  an easyreporting class object

**Value**

a string of report file name with path

**Examples**

```
## Not run:
rd <- easyreporting(filenamePath="./project_report",
                    title="example_report", author=c("It's me"))
(rep <- getReportFilename(rd))

## End(Not run)
```

---

`getReportFilename`, easyreporting-method  
*getReportFilename*

---

**Description**

returns the report filename with path

**Usage**

```
## S4 method for signature 'easyreporting'
getReportFilename(object)
```

**Arguments**

object            an easyreporting class object

**Value**

a string of report file name with path

**Examples**

```
## Not run:
rd <- easyreporting(filenamePath="./project_report",
                    title="example_report", author=c("It's me"))
(rep <- getReportFilename(rd))

## End(Not run)
```

---

`initReportFilename`    *initReportFilename*

---

**Description**

`initReportFilename`

**Usage**

```
initReportFilename(
  object,
  filepath = NULL,
  title = NULL,
  author = NULL,
  optionList = NULL,
  bibfile = NULL,
  documentType = NULL,
  resources = NULL
)
```

**Arguments**

object            an easyreporting class object

filepath         the name of the report with or without the path

author            the name of the report author

documentType    type of report final document. (html is default)

mainTitle        the title of the report

**Value**

an easyreporting class object

---

initReportFilename,easyreporting-method  
*initReportFilename*

---

## Description

internal funtion usefull to init the report for the first time.

## Usage

```
## S4 method for signature 'easyreporting'  
initReportFilename(  
  object,  
  filepath = NULL,  
  title = NULL,  
  author = NULL,  
  optionList = NULL,  
  bibfile = "",  
  documentType = "rmarkdown::html_document"  
)
```

## Arguments

object	an easyreporting class object
filepath	the name of the report with or without the path
author	the name of the report author as a <a href="#">person</a> format (where expected comment named fields are ORCID, url, affiliation, affiliation_url). In case author is a character, it will be reported as it is.
bibfile	a bibfile for bibliography.
documentType	type of report final document, if author(s) is a person it will be <code>distill::distill_article</code> ( <code>rmarkdown::html_document</code> default)
mainTitle	the title of the report

## Value

an easyreporting class object

## See Also

[person](#)

---

makeOptionsList	<i>makeOptionsList</i>
-----------------	------------------------

---

## Description

makes an list of rmarkdown options

## Usage

```
makeOptionsList(
  cacheFlag = TRUE,
  evalFlag = TRUE,
  echoFlag = TRUE,
  warningFlag = FALSE,
  showMessages = FALSE,
  includeFlag = TRUE,
  collapseFlag = FALSE,
  purlFlag = TRUE,
  errorFlag = TRUE,
  messageFlag = TRUE,
  highlightFlag = TRUE,
  promptFlag = FALSE,
  stripWhiteFlag = TRUE,
  tidyFlag = FALSE
)
```

## Arguments

cacheFlag	boolean for caching chunk data (default TRUE)
evalFlag	boolean for evaluating the code chunk in the compiled version (default TRUE)
echoFlag	boolean for showing the code chunk (default TRUE)
warningFlag	boolean for showing the chunk warnings (default FALSE)
showMessages	boolean for showing the chunk warnings in compiled version (default FALSE)
includeFlag	boolean for including the code chunk in the compiled version (default TRUE)
collapseFlag	boolean for collapsing the code chunk in the compiled version (default FALSE),
purlFlag	boolean for extracting the code chunk as R code in a separate R file (default TRUE),
errorFlag	boolean for including the error generated by the code chunk in the compiled version (default TRUE),
messageFlag	boolean for including the code chunk messages in the compiled version (default TRUE),
highlightFlag	boolean for highlighting the code chunk in the compiled version (default TRUE),
promptFlag	boolean for including a ">" for the code chunk in the compiled version (default FALSE),
stripWhiteFlag	boolean for removing the white spaces at beginning/end of the code chunk in the compiled version (default TRUE),
tidyFlag	boolean for creating a tidy code chunk in the compiled version (default FALSE).

**Value**

list of rmarkdown options

**Examples**

```
optList <- makeOptionsList()
```

---

```
mkdCodeChunkCommented mkdCodeChunkCommented
```

---

**Description**

it creates a complete code chunk, adding a natural language comment before of it.

**Usage**

```
mkdCodeChunkCommented(
  object,
  comment = NULL,
  code,
  optionList = getOptionsList(object),
  sourceFilesList = NULL
)
```

**Arguments**

object	an easyreporting class object
comment	a string with the natural language comment for the chunk.
code	a string within the code.
optionList	a list of options (default is the class options).
sourceFilesList	a optional list of files to source inside the chunk.

**Value**

none

**Examples**

```
## Not run:
rd <- easyreporting(filenamePath="./project_report",
  title="example_report", author=c("It's me"))
optList <- makeOptionsList(includeFlag=TRUE, cacheFlag=TRUE)
mkdCodeChunkCommented(rd,
  comment="This is the comment of the following code chunk",
  code="a <- 1\n b <- 2\n (c <- a+b)\n", optionList=optList,
  sourceFilesList=NULL)

## End(Not run)
```

---

*mkdCodeChunkCommented, easyreporting-method*  
*mkdCodeChunkCommented*

---

### Description

it creates a complete code chunk, adding a natural language comment before of it.

### Usage

```
## S4 method for signature 'easyreporting'
mkdCodeChunkCommented(
  object,
  comment = NULL,
  code,
  optionList = getOptionsList(object),
  sourceFilesList = NULL
)
```

### Arguments

<code>object</code>	an easyreporting class object
<code>comment</code>	a string with the natural language comment for the chunk.
<code>code</code>	a string within the code.
<code>optionList</code>	a list of options (default is the class options).
<code>sourceFilesList</code>	a optional list of files to source inside the chunk.

### Value

none

### Examples

```
## Not run:
rd <- easyreporting(filenamePath="./project_report",
                    title="example_report", author=c("It's me"))
optList <- makeOptionsList(includeFlag=TRUE, cacheFlag=TRUE)
mkdCodeChunkCommented(rd,
                      comment="This is the comment of the following code chunk",
                      code=c(quote(a <- 1), quote(b <- 2), quote(c <- a+b)),
                      optionList=optList, sourceFilesList=NULL)
mkdCodeChunkCommented(rd,
                      comment="This is the comment of the following code chunk",
                      code="a <- 1\n b <- 2\n(c <- a+b)\n", optionList=optList,
                      sourceFilesList=NULL)

## End(Not run)
```

---

mkdCodeChunkComplete *mkdCodeChunkComplete*

---

### Description

it creates a complete code chunk.

### Usage

```
mkdCodeChunkComplete(  
  object,  
  code,  
  optionList = getOptionsList(object),  
  sourceFilesList = NULL  
)
```

### Arguments

object	an easyreporting class object
code	a string or an expression generated with <a href="#">quote</a> containing a function call or the entire code chunk to trace.
optionList	a list of options.
sourceFilesList	a list of files to source.

### Value

none

### Examples

```
## Not run:  
rd <- easyreporting(filenamePath="./project_report",  
                    title="example_report", author=c("It's me"))  
mkdCodeChunkComplete(rd, code="a <- 1\n b <- 2\n c <- a+b\n print(c)")  
  
## End(Not run)
```

---

mkdCodeChunkComplete, easyreporting-method  
*mkdCodeChunkComplete*

---

### Description

it creates a complete code chunk.

**Usage**

```
## S4 method for signature 'easyreporting'
mkdCodeChunkComplete(
  object,
  code,
  optionList = getOptionsList(object),
  sourceFilesList = NULL
)
```

**Arguments**

`object` an easyreporting class object

`code` a string or an expression (or a list of expressions) generated with `quote` containing a function call or the entire code chunk to trace.

`optionList` a list of options.

`sourceFilesList` a list of files to source.

**Value**

none

**Examples**

```
## Not run:
rd <- easyreporting(filenamePath="./project_report",
  title="example_report", author=c("It's me"))
mkdCodeChunkComplete(rd, code=c(quote(a <- 1), quote(b <- 2), quote(c<- a+b),
  quote(print(c))))
mkdCodeChunkComplete(rd, code="a <- 1\n b <- 2\n c <- a+b\n print(c)")

## End(Not run)
```

---

mkdCodeChunkEnd

*mkdCodeChunkEnd*


---

**Description**

it creates a code chunk end. Always use it after a `mkdCodeChunkSt()`

**Usage**

```
mkdCodeChunkEnd(object)
```

**Arguments**

`object` an easyreporting class object

**Value**

none



**Examples**

```
## Not run:
rd <- easyreporting(filenamePath="./project_report",
                    title="example_report", author=c("It's me"))
mkdCodeChunkSt(rd)
## just leaving empty
mkdCodeChunkEnd(rd)

## End(Not run)
```

---

mkdCodeChunkEnd,easyreporting-method  
*mkdCodeChunkEnd*

---

**Description**

it creates a code chunk end. Always use it after a mkdCodeChunkSt()

**Usage**

```
## S4 method for signature 'easyreporting'
mkdCodeChunkEnd(object)
```

**Arguments**

object            an easyreporting class object

**Value**

none

**Examples**

```
## Not run:
rd <- easyreporting(filenamePath="./project_report",
                    title="example_report", author=c("It's me"))
mkdCodeChunkSt(rd)
## just leaving empty
mkdCodeChunkEnd(rd)

## End(Not run)
```

---

mkdCodeChunkSt	<i>mkdCodeChunkSt</i>
----------------	-----------------------

---

## Description

it creates a code chunk start. A list of options and files to source for the chunk can optionally be passed to the function.

## Usage

```
mkdCodeChunkSt(  
  object,  
  optionList = getOptionsList(object),  
  sourceFilesList = NULL,  
  isComplete = FALSE  
)
```

## Arguments

object	an easyreporting class object
optionList	a list of options
sourceFilesList	a list of files that can be sourced inside the code chunk.
isComplete	a flag determining if the chunk is already a complete chunk

## Value

none

## Examples

```
## Not run:  
rd <- easyreporting(filenamePath="./project_report",  
                    title="example_report", author=c("It's me"))  
  
## no options  
mkdCodeChunkSt(rd)  
## just leaving empty  
mkdCodeChunkEnd(rd)  
  
## setting options  
optList <- makeOptionsList(includeFlag=TRUE)  
mkdCodeChunkSt(rd, optionList=optList)  
## just leaving empty  
mkdCodeChunkEnd(rd)  
  
## End(Not run)
```

---

```
mkdCodeChunkSt,easyreporting-method  
mkdCodeChunkSt
```

---

## Description

it creates a code chunk start. A list of options and files to source for the chunk can optionally be passed to the function.

## Usage

```
## S4 method for signature 'easyreporting'  
mkdCodeChunkSt(  
  object,  
  optionList = getOptionsList(object),  
  sourceFilesList = NULL,  
  isComplete = FALSE  
)
```

## Arguments

object	an easyreporting class object
optionList	a list of options
sourceFilesList	a list of files that can be sourced inside the code chunk.
isComplete	a flag determining if the chunk is already a complete chunk

## Value

none

## Examples

```
## Not run:  
rd <- easyreporting(filenamePath="./project_report",  
                    title="example_report", author=c("It's me"))  
  
## no options  
mkdCodeChunkSt(rd)  
## just leaving empty  
mkdCodeChunkEnd(rd)  
  
## setting options  
optList <- makeOptionsList(includeFlag=TRUE)  
mkdCodeChunkSt(rd, optionList=optList)  
## just leaving empty  
mkdCodeChunkEnd(rd)  
  
## End(Not run)
```

---

mkdCodeChunkTitledCommented  
*mkdCodeChunkCommented*

---

### Description

it creates a complete code chunk, adding a natural language comment before of it.

### Usage

```
mkdCodeChunkTitledCommented(  
  object,  
  title = NULL,  
  level = 1,  
  comment = NULL,  
  code,  
  optionList = getOptionsList(object),  
  sourceFilesList = NULL  
)
```

### Arguments

object	an easyreporting class object
title	the title to assign to the code chunk section
level	the level of the title (default is 1)
comment	a string with the natural language comment for the chunk.
code	a string within the code.
optionList	a list of options (default is the class options).
sourceFilesList	a optional list of files to source inside the chunk.

### Value

none

### Examples

```
## Not run:  
rd <- easyreporting(filenamePath="./project_report",  
                    title="example_report", author=c("It's me"))  
optList <- makeOptionsList(includeFlag=TRUE, cacheFlag=TRUE)  
mkdCodeChunkCommented(rd,  
                      comment="This is the comment of the following code chunk",  
                      code="a <- 1\n b <- 2\n (c <- a+b)\n", optionList=optList,  
                      sourceFilesList=NULL)  
  
## End(Not run)
```

---

```
mkdCodeChunkTitledCommented,easyreporting-method
      mkdCodeChunkTitledCommented
```

---

## Description

it creates a complete code chunk, adding a natural language comment before of it.

## Usage

```
## S4 method for signature 'easyreporting'
mkdCodeChunkTitledCommented(
  object,
  title = NULL,
  level = 1,
  comment = NULL,
  code,
  optionList = getOptionsList(object),
  sourceFilesList = NULL
)
```

## Arguments

object	an easyreporting class object
title	the title to assign to the code chunk section
level	the level of the title (default is 1)
comment	a string with the natural language comment for the chunk.
code	a string within the code.
optionList	a list of options (default is the class options).
sourceFilesList	a optional list of files to source inside the chunk.

## Value

none

## Examples

```
## Not run:
rd <- easyreporting(filenamePath="./project_report",
  title="example_report", author=c("It's me"))
optList <- makeOptionsList(includeFlag=TRUE, cacheFlag=TRUE)
mkdCodeChunkTitledCommented(rd, title="Title Example", level=1,
  comment="This is the comment of the following code chunk",
  code="a <- 1\n b <- 2\n(c <- a+b)\n", optionList=optList,
  sourceFilesList=NULL)

## End(Not run)
```

---

mkdGeneralMsg	<i>mkdGeneralMsg</i>
---------------	----------------------

---

**Description**

It appends a general message to the report, useful for describing a code chunk or a part of the report. Useful for adding natural language comments.

**Usage**

```
mkdGeneralMsg(object, message)
```

**Arguments**

object	an easyreporting class object
message	the message to append to the report

**Value**

none

**Examples**

```
## Not run:
rd <- easyreporting(filenamePath="./project_report",
                    title="example_report", author=c("It's me"))
mkdGeneralMsg(rd, message="Writing a paragraph to describe my code chunk")

## End(Not run)
```

---

mkdGeneralMsg,easyreporting-method	<i>mkdGeneralMsg</i>
------------------------------------	----------------------

---

**Description**

It appends a general message to the report. Useful for adding natural language comments.

**Usage**

```
## S4 method for signature 'easyreporting'
mkdGeneralMsg(object, message)
```

**Arguments**

object	an easyreporting class object
message	the message to append to the report

**Value**

none

## Examples

```
## Not run:
rd <- easyreporting(filenamePath="./project_report",
                    title="example_report", author=c("It's me"))
mkdGeneralMsg(rd, "Writing a paragraph to describe my code chunk")

## End(Not run)
```

---

mkdGeneralTitledMsg    *mkdGeneralTitledMsg*

---

## Description

It appends a a titled section followed by a general message to the report. Useful for adding natural language comments.

## Usage

```
mkdGeneralTitledMsg(object, title = NULL, level = 1, message)
```

## Arguments

object	an easyreporting class object
title	the title of the report section.
level	the level (1 to 6) of the title (default is 1)
message	the message to append to the report

## Value

none

## Examples

```
## Not run:
rd <- easyreporting(filenamePath="./project_report",
                    title="example_report", author=c("It's me"))
mkdGeneralTitledMsg(rd, title="Generic SubTitle for this message", level=2,
                    message="Writing a paragraph to describe my code chunk")

## End(Not run)
```

---

```
mkdGeneralTitledMsg, easyreporting-method
      mkdGeneralTitledMsg
```

---

**Description**

It appends a a titled section followed by a general message to the report. Useful for adding natural language comments.

**Usage**

```
## S4 method for signature 'easyreporting'
mkdGeneralTitledMsg(object, title = NULL, level = 1, message)
```

**Arguments**

object	an easyreporting class object
title	the optional title to give to the message section
level	the level (1 to 6) of the title (default is 1)
message	the message to append to the report

**Value**

none

**Examples**

```
## Not run:
rd <- easyreporting(filenamePath="./project_report",
                    title="example_report", author=c("It's me"))
mkdGeneralTitledMsg(rd, title="Generic SubTitle for this message", level=2,
                    message="Writing a paragraph to describe my code chunk")

## End(Not run)
```

---

```
mkdSetGlobalOpts      mkdSetGlobalOpts
```

---

**Description**

mkdSetGlobalOpts

**Usage**

```
mkdSetGlobalOpts(object, optionList = list())
```

**Arguments**

object	an easyreporting class object
optionList	a list of options



**Value**

an easyreporting class object

---

*mkdSetGlobalOpts, easyreporting-method*  
*mkdSetGlobalOpts*

---

**Description**

internal function for appending to the report the initial options setup

**Usage**

```
## S4 method for signature 'easyreporting'  
mkdSetGlobalOpts(object, optionList = list())
```

**Arguments**

object            an easyreporting class object  
optionList        a list of options

**Value**

an easyreporting class object

---

*mkdSourceFiles*            *mkdSourceFiles*

---

**Description**

includes a list of source files inside the rmarkdown

**Usage**

```
mkdSourceFiles(object, ...)
```

**Arguments**

object            an easyreporting class object  
...                a list of files to source

**Value**

none

---

mkdSourceFiles, easyreporting-method  
*mkdSourceFiles*

---

**Description**

includes a list of source files inside the rmarkdown

**Usage**

```
## S4 method for signature 'easyreporting'
mkdSourceFiles(object, ...)
```

**Arguments**

object	an easyreporting class object
...	a list of files to source with path

**Value**

none

---

mkdTitle                      *mkdTitle*

---

**Description**

Inserts an rmarkdown title inside the report, useful for create distinct sections inside the final respot.

**Usage**

```
mkdTitle(object, title, level = 1)
```

**Arguments**

object	an easyreporting class object
title	a string within the title.
level	a numeric from 1 to 6 (default is 1).

**Value**

none

**Examples**

```
## Not run:
rd <- easyreporting(filenamePath="./project_report",
                    title="example_report", author=c("It's me"))

mkdTitle(rd, "First Level Title")
mkdTitle(rd, "Sub-Title", level=2)

## End(Not run)
```

---

mkdTitle,easyreporting-method  
*mkdTitle*

---

**Description**

Inserts an rmarkdown title inside the report.

**Usage**

```
## S4 method for signature 'easyreporting'
mkdTitle(object, title, level = 1)
```

**Arguments**

object	an easyreporting class object
title	a string within the title.
level	a numeric from 1 to 6 (default is 1).

**Value**

none

**Examples**

```
## Not run:
rd <- easyreporting(filenamePath="./project_report",
                    title="example_report", author=c("It's me"))

mkdTitle(rd, "First Level Title")
mkdTitle(rd, "Sub-Title", level=2)

## End(Not run)
```

---

 mkdVariableAssignment *mkdVariableAssignment*


---

### Description

it includes a variable assignment in the report. NB: a call to the "mkdCodeChunkSt" has to be done before using it.

### Usage

```
mkdVariableAssignment(object, variable.name, variable.object.name, show)
```

### Arguments

object	an easyreporting class object
variable.name	a string indicating the name of the variabe to store in the report. (This can be changed here, but further uses of the variable needs to take into account the variable name change).
variable.object.name	the name of the already existing variable. (This cannot be canged.)
show	a boolean indicating if to show the message before writing it into the rmarkdown file.

### Value

none

### Examples

```
## Not run:
rd <- easyreporting(filenamePath="./project_report",
                    title="example_report", author=c("It's me"))
## leaving the default options to the code chunk
mkdCodeChunkSt(rd)
## adding a variable assignment
variable <- 1
mkdVariableAssignment(rd, "variable", "variable", show=TRUE)
mkdCodeChunkEnd(rd)

## End(Not run)
```

---

 mkdVariableAssignment,easyreporting-method  
*mkdVariableAssignment*


---

### Description

it includes a variable assignment in the report. NB: a call to the "mkdCodeChunkSt" has to be done before using it.

**Usage**

```
## S4 method for signature 'easyreporting'
mkdVariableAssignment(
  object,
  variable.name,
  variable.object.name,
  show = FALSE
)
```

**Arguments**

object	an easyreporting class object
variable.name	a string indicating the name of the variable to store in the report. (This can be changed here, but further uses of the variable needs to take into account the variable name change).
variable.object.name	the name of the already existing variable. (This cannot be changed.)
show	a boolean indicating if to show the message before writing it into the rmarkdown file.

**Value**

none

**Examples**

```
## Not run:
rd <- easyreporting(filenamePath="./project_report",
                    title="example_report", author=c("It's me"))
## leaving the default options to the code chunk
mkdCodeChunkSt(rd)
## adding a variable assignment
variable <- 1
mkdVariableAssignment(rd, "variable", "variable", show=TRUE)
mkdCodeChunkEnd(rd)

## End(Not run)
```

---

setBibliography

*setBibliography*

---

**Description**

add a bibfile name to the object that will be reflected into the report as a bibliography section

**Usage**

```
setBibliography(object, bibfile = NULL)
```

**Arguments**

object            an easyreporting class object  
bibfile           a path string with the name of the bib file

**Value**

none

**Examples**

```
## Not run:  
TBD  
  
## End(Not run)
```

---

setBibliography,easyreporting-method  
*setBibliography*

---

**Description**

add a bibfile name to the object that will be reflected into the report as a bibliography section

**Usage**

```
## S4 method for signature 'easyreporting'  
setBibliography(object, bibfile = NULL)
```

**Arguments**

object            an easyreporting class object  
bibfile           a string with the name of the bib file

**Value**

none

**Examples**

```
## Not run:  
# TBD  
  
## End(Not run)
```

---

setOptionsList	<i>setOptionsList</i>
----------------	-----------------------

---

### Description

set an optionList to the class, it automatically sets the options for the rmarkdown file. Are useful for the interpretation/execution of the code chunks.

### Usage

```
setOptionsList(
  object,
  cacheFlag = TRUE,
  evalFlag = TRUE,
  echoFlag = TRUE,
  warningFlag = FALSE,
  showMessages = FALSE,
  includeFlag = TRUE,
  collapseFlag = FALSE,
  purlFlag = TRUE,
  errorFlag = TRUE,
  messageFlag = TRUE,
  highlightFlag = TRUE,
  promptFlag = FALSE,
  stripWhiteFlag = TRUE,
  tidyFlag = FALSE
)
```

### Arguments

object	an easyreporting class object
cacheFlag	boolean for caching chunk data (default TRUE)
evalFlag	boolean for evaluating the code chunk in the compiled version (default TRUE)
echoFlag	boolean for showing the code chunk (default TRUE)
warningFlag	boolean for showing the chunk warnings (default FALSE)
showMessages	boolean for showing the chunk warnings in compiled version (default FALSE)
includeFlag	boolean for including the code chunk in the compiled version (default TRUE)
collapseFlag	boolean for collapsing the code chunk in the compiled version (default FALSE),
purlFlag	boolean for extracting the code chunk as R code in a separate R file (default TRUE),
errorFlag	boolean for including the error generated by the code chunk in the compiled version (default TRUE),
messageFlag	boolean for including the code chunk messages in the compiled version (default TRUE),
highlightFlag	boolean for highlighting the code chunk in the compiled version (default TRUE),
promptFlag	boolean for including a ">" for the code chunk in the compiled version (default FALSE),

`stripWhiteFlag` boolean for removing the white spaces at beginning/end of the code chunk in the compiled version (default TRUE),

`tidyFlag` boolean for creating a tidy code chunk in the compiled version (default FALSE).

**Value**

none

**Examples**

```
## Not run:
rd <- easyreporting(filenamePath="./project_report",
                    title="example_report", author=c("It's me"))

## setting default option
setOptionsList(rd)

## modifying only some options
rd <- setOptionsList(rd, warningFlag=TRUE,
                    showMessages=TRUE, includeFlag=TRUE)

## End(Not run)
```

---

*setOptionsList,easyreporting-method*  
*setOptionsList*

---

**Description**

set an optionList to the class

**Usage**

```
## S4 method for signature 'easyreporting'
setOptionsList(
  object,
  cacheFlag = TRUE,
  evalFlag = TRUE,
  echoFlag = TRUE,
  warningFlag = FALSE,
  showMessages = FALSE,
  includeFlag = TRUE,
  collapseFlag = FALSE,
  purlFlag = TRUE,
  errorFlag = TRUE,
  messageFlag = TRUE,
  highlightFlag = TRUE,
  promptFlag = FALSE,
  stripWhiteFlag = TRUE,
  tidyFlag = FALSE
)
```



**Arguments**

object	an easyreporting class object
cacheFlag	boolean for caching chunk data (default TRUE)
evalFlag	boolean for evaluating the code chunk in the compiled version (default TRUE)
echoFlag	boolean for showing the code chunk (default TRUE)
warningFlag	boolean for showing the chunk warnings (default FALSE)
showMessages	boolean for showing the chunk warnings in compiled version (default FALSE)
includeFlag	boolean for including the code chunk in the compiled version (default TRUE)
collapseFlag	boolean for collapsing the code chunk in the compiled version (default FALSE),
pur1Flag	boolean for extracting the code chunk as R code in a separate R file (default TRUE),
errorFlag	boolean for including the error generated by the code chunk in the compiled version (default TRUE),
messageFlag	boolean for including the code chunk messages in the compiled version (default TRUE),
highlightFlag	boolean for highlighting the code chunk in the compiled version (default TRUE),
promptFlag	boolean for including a ">" for the code chunk in the compiled version (default FALSE),
stripWhiteFlag	boolean for removing the white spaces at beginning/end of the code chunk in the compiled version (default TRUE),
tidyFlag	boolean for creating a tidy code chunk in the compiled version (default FALSE).

**Value**

none

**Examples**

```
## Not run:
rd <- easyreporting(filenamePath="./project_report",
                    title="example_report", author=c("It's me"))

## setting default option
setOptionsList(rd)

## modifying only some options
rd <- setOptionsList(rd, warningFlag=TRUE,
                    showMessages=TRUE, includeFlag=TRUE)

## End(Not run)
```

# Index

## \* internal

- initReportFilename, [10](#)
  - initReportFilename, easyreporting-method, [11](#)
  - mkdSetGlobalOpts, [24](#)
  - mkdSetGlobalOpts, easyreporting-method, [25](#)
  - mkdSourceFiles, [25](#)
  - mkdSourceFiles, easyreporting-method, [26](#)
  - setBibliography, easyreporting-method, [30](#)
- addResource, [2](#)
- addResource, easyreporting-method, [3](#)
- compile, [4](#)
- compile, easyreporting-method, [4](#)
- easyreporting, [5](#)
- easyreporting-class (easyreporting), [5](#)
- erGUIVolcano, [6](#)
- getBibliography, [6](#)
- getBibliography, easyreporting-method, [7](#)
- getOptionsList, [8](#)
- getOptionsList, easyreporting-method, [8](#)
- getReportFilename, [9](#)
- getReportFilename, easyreporting-method, [9](#)
- initReportFilename, [10](#)
- initReportFilename, easyreporting-method, [11](#)
- makeOptionsList, [12](#)
- mkdCodeChunkCommented, [13](#)
- mkdCodeChunkCommented, easyreporting-method, [14](#)
- mkdCodeChunkComplete, [15](#)
- mkdCodeChunkComplete, easyreporting-method, [15](#)
- mkdCodeChunkEnd, [16](#)
- mkdCodeChunkEnd, easyreporting-method, [17](#)
- mkdCodeChunkSt, [18](#)
- mkdCodeChunkSt, easyreporting-method, [19](#)
- mkdCodeChunkTitledCommented, [20](#)
- mkdCodeChunkTitledCommented, easyreporting-method, [21](#)
- mkdGeneralMsg, [22](#)
- mkdGeneralMsg, easyreporting-method, [22](#)
- mkdGeneralTitledMsg, [23](#)
- mkdGeneralTitledMsg, easyreporting-method, [24](#)
- mkdSetGlobalOpts, [24](#)
- mkdSetGlobalOpts, easyreporting-method, [25](#)
- mkdSourceFiles, [25](#)
- mkdSourceFiles, easyreporting-method, [26](#)
- mkdTitle, [26](#)
- mkdTitle, easyreporting-method, [27](#)
- mkdVariableAssignment, [28](#)
- mkdVariableAssignment, easyreporting-method, [28](#)
- person, [11](#)
- quote, [15](#), [16](#)
- setBibliography, [29](#)
- setBibliography, easyreporting-method, [30](#)
- setOptionsList, [31](#)
- setOptionsList, easyreporting-method, [32](#)