

Package ‘GEWIST’

April 24, 2025

Type Package

Title Gene Environment Wide Interaction Search Threshold

Version 1.53.0

Depends R (>= 2.10), car

Author Wei Q. Deng, Guillaume Pare

Maintainer Wei Q. Deng <dengwq@mcmaster.ca>

Description This 'GEWIST' package provides statistical tools to efficiently optimize SNP prioritization for gene-gene and gene-environment interactions.

License GPL-2

LazyLoad yes

biocViews MultipleComparison, Genetics

git_url <https://git.bioconductor.org/packages/GEWIST>

git_branch devel

git_last_commit bad48a5

git_last_commit_date 2025-04-15

Repository Bioconductor 3.22

Date/Publication 2025-04-24

Contents

GEWIST-package	2
effectPDF	2
gewistLevene	4
Index	6

 GEWIST-package

Gene Environment Wide Interaction Search Threshold

Description

This 'GEWIST' package provides statistical tools to efficiently optimize SNP prioritization for gene-gene and gene-environment interactions.

Details

Package:	PathWei
Type:	Package
Version:	0.99.z
License:	GPL-2
LazyLoad:	yes

Author(s)

Wei Q. Deng <dengwq@mcmaster.ca> Guillaume Pare <pareg@mcmaster.ca>

References

Deng W.Q, Pare G. (2011) A fast algorithm to optimize SNP prioritization for gene-gene and gene-environment interactions. *Genetic Epidemiology*. 35: 729-738. doi: 10.1002/gepi.20624

Pare G, Cook NR, Ridker PM, Chasman DI (2010) On the Use of Variance per Genotype as a Tool to Identify Quantitative Trait Interaction Effects: A Report from the Women's Genome Health Study. *PLoS Genet* 6(6): e1000981. doi:10.1371/journal.pgen.1000981

Levene H. (1960) Robust tests for equality of variances. In *Contributions to Probability and Statistics: Essays in Honor of Harold Hotelling* eds:I. Olkin, S.G. Ghurye, W. Hoeffding, W.G. Madow & H.B.Mann, pp.278-292. Stanford: Stanford University Press.

 effectPDF

Genetic interaction testing given effect size distribution

Description

Compute the optimal Variance Prioritization power and corresponding Levene's test p-value threshold for prioritization given the interaction effect size distribution using GEWIST.

Usage

```
effectPDF(distribution = c("beta", "normal", "uniform", "weibull"),
parameter1, parameter2 = NULL, parameter3 = NULL, p, N, theta_c, M,
K = 20000, nb_incr = 50, range = NULL, verbose = FALSE)
```

Arguments

distribution	distribution of interaction effect size. Possible distributions are: "beta" for beta distribution "normal" for normal distribution "uniform" for uniform distribution "weibull" for weibull distribution
parameter1	the first parameter used in the corresponding distribution
parameter2	the second parameter used in the corresponding distribution, could set to be null
parameter3	the third parameter used in the corresponding distribution, could set to be null
p	minor allele frequency of the SNP, a number between 0 and 0.5
N	sample size
theta_c	proportion of quantitative trait variance explained by the covariate, should be a number between 0 and 1
M	total number of SNPs to be tested
K	number of GEWIST procedures, by default, set to be 20,000
nb_incr	number of effect size points in the range to be prioritized using GEWIST; by default set to be 50.
range	range of variance explained by interaction effect sizes, a vector of length 2
verbose	logical; if TRUE, for each interaction effect size, function returns a data.frame class object listing the VP power at each p-value, from 0.001 to 1 with 0.001 incremental increase.

Value

A list with three components:

Optimal_VP_power	VP power to detect interactions at the optimal VP p-value threshold
Conventional_power	power to detect interactions without prioritization, i.e, VP power at Levene' test p-value of 1
Optimal_pval_threshold	levene'e test p-value at which optimal VP power is achieved

Warning

Computational time is directly proportional to *nb_incr*.

Author(s)

Wei Q. Deng <dengwq@mcmaster.ca> Guillaume Pare <pareg@mcmaster.ca>

References

- Deng W.Q, Pare G. (2011) A fast algorithm to optimize SNP prioritization for gene-gene and gene-environment interactions. *Genetic Epidemiology*. 35: 729-738. doi: 10.1002/gepi.20624
- Pare G, Cook NR, Ridker PM, Chasman DI (2010) On the Use of Variance per Genotype as a Tool to Identify Quantitative Trait Interaction Effects: A Report from the Women's Genome Health Study. *PLoS Genet* 6(6): e1000981. doi:10.1371/journal.pgen.1000981

Levene H. (1960) Robust tests for equality of variances. In *Contributions to Probability and Statistics: Essays in Honor of Harold Hotelling* eds:I. Olkin, S.G. Ghurye, W. Hoeffding, W.G. Madow & H.B.Mann, pp.278-292. Stanford: Stanford University Press.

Examples

```
# Given a SNP with minor allele frequency of 10% and a sample
# of 10,000 individuals, we are interested in testing interactions
# between this SNP and a covariate of effect size 10%. The
# total number of SNP is 500,000. Assume the unknown interaction
# effect size has a Weibull distribution in the range of 0.05%
# and 0.3% variance explained with 50 increments.Repeat GEWIST
# for each of the 50 interaction effect sizes.

library(GEWIST)
effectPDF(distribution = "weibull", parameter1 = 0.8, parameter2 = 0.3,
parameter3 = NULL, p = 0.1 ,N = 10000, theta_c = 0.1, M = 350000,
K = 20000, nb_incr = 50, range = c(0.05/100,0.3/100), verbose = FALSE)

## End of script
```

gewistLevene	<i>Genome Environment Wide Interaction Search Threshold with Levene's test</i>
--------------	--

Description

Compute the optimal Variance Prioritization power and the corresponding Levene's test prioritization p-value threshold for a given interaction effect size

Usage

```
gewistLevene(p, N, theta_gc, theta_c, M, K = 20000, verbose = FALSE)
```

Arguments

p	minor allele frequency of the SNP, a number between 0 and 0.5
N	sample size
theta_gc	proportion of quantitative trait variance explained by the interaction, should be a number between 0 and 1
theta_c	proportion of quantitative trait variance explained by the covariate, should be a number between 0 and 1
M	total number of SNPs to be tested
K	number of procedures, by default, set to be 20,000
verbose	logical; if TRUE, function returns a data.frame class object listing the VP power at each p-value, from 0.001 to 1 with 0.001 incremental increase.

Value

A list with three components:

Optimal_VP_power

VP power to detect interactions at the optimal Levene's test p-value threshold

Conventional_power

power to detect interactions without prioritization, i.e, VP power at Levene's test p-value of 1

Optimal_pval_threshold

levene's test p-value at which optimal VP power is achieved

Author(s)

Wei Q. Deng <dengwq@mcmaster.ca> Guillaume Pare <pareg@mcmaster.ca>

References

Deng W.Q, Pare G. (2011) A fast algorithm to optimize SNP prioritization for gene-gene and gene-environment interactions. *Genetic Epidemiology* 35: 729-738. doi: 10.1002/gepi.20624

Pare G, Cook NR, Ridker PM, Chasman DI (2010) On the Use of Variance per Genotype as a Tool to Identify Quantitative Trait Interaction Effects: A Report from the Women's Genome Health Study. *PLoS Genet* 6(6): e1000981. doi:10.1371/journal.pgen.1000981

Levene H. (1960) Robust tests for equality of variances. In *Contributions to Probability and Statistics: Essays in Honor of Harold Hotelling* eds:I. Olkin, S.G. Ghurye, W. Hoeffding, W.G. Madow & H.B.Mann, pp.278-292. Stanford: Stanford University Press.

Examples

```
# Given a SNP with minor allele frequency of 10% and a sample
# of 15,000 individuals, we are interested in testing interactions
# between this SNP and a covariate of effect size #10%. The
# total number of SNP is 500,000. Assume the interaction
# explains 0.1% of the quantitative trait variance.
```

```
library(GEWIST)
gewistLevene(p = 0.1, N = 15000, theta_gc =0.1/100, theta_c = 0.1 , M = 500000,
K = 20000, verbose=FALSE)
```

Index

- * **Bonferroni correction**

- effectPDF, [2](#)
 - GEWIST-package, [2](#)
 - gewistLevene, [4](#)

- * **Levene's Test**

- effectPDF, [2](#)
 - GEWIST-package, [2](#)
 - gewistLevene, [4](#)

- * **genetic interactions**

- effectPDF, [2](#)
 - GEWIST-package, [2](#)
 - gewistLevene, [4](#)

- * **quantitative trait**

- effectPDF, [2](#)
 - GEWIST-package, [2](#)
 - gewistLevene, [4](#)

- * **variance prioritization**

- effectPDF, [2](#)
 - GEWIST-package, [2](#)
 - gewistLevene, [4](#)

effectPDF, [2](#)

GEWIST (GEWIST-package), [2](#)

GEWIST-package, [2](#)

gewistLevene, [4](#)