

Package ‘FeatSeekR’

September 22, 2026

Type Package

Title FeatSeekR an R package for unsupervised feature selection

Version 1.12.0

Description FeatSeekR performs unsupervised feature selection using replicated measurements. It iteratively selects features with the highest reproducibility across replicates, after projecting out those dimensions from the data that are spanned by the previously selected features. The selected a set of features has a high replicate reproducibility and a high degree of uniqueness.

License GPL-3

Encoding UTF-8

Imports pheatmap, MASS, pracma, stats, SummarizedExperiment, methods

RoxygenNote 7.2.3

Suggests rmarkdown, knitr, BiocStyle, testthat (>= 3.0.0)

VignetteBuilder knitr

BugReports <https://github.com/tcapraz/FeatSeekR/issues>

URL <https://github.com/tcapraz/FeatSeekR>

biocViews Software, StatisticalMethod, FeatureExtraction,
MassSpectrometry

Config/testthat/edition 3

git_url <https://git.bioconductor.org/packages/FeatSeekR>

git_branch RELEASE_3_23

git_last_commit c4f3dc7

git_last_commit_date 2026-04-28

Repository Bioconductor 3.23

Date/Publication 2026-09-22

Author Tuemay Capraz [cre, aut] (ORCID:
<https://orcid.org/0000-0002-2547-067X>)

Maintainer Tuemay Capraz <tuemay.capraz@embl.de>

Contents

calcFstat	2
check_input	2
FeatSeek	3
FeatSeekR	4
fit_lm	5
init_selected	5
plotSelectedFeatures	6
plotVarianceExplained	6
simData	7
variance_explained	8
Index	9

calcFstat	<i>calcFstat</i>
-----------	------------------

Description

calcFstat

Usage

calcFstat(data, fac)

Arguments

- | | |
|------|---|
| data | 2 dimensional array with samples x features, where samples belongs different conditions. The function was adapted from the <i>genefilter</i> package. |
| fac | factor of length samples, indicating which sample belongs to which condition |

Value

F-statistic for all features

check_input	<i>check_input</i>
-------------	--------------------

Description

Checks input data. Input data should be a 2 dimensional array with features x samples or SummarizedExperiment carrying one assay named data and colData indicating which sample belongs to which condition

Usage

```
check_input(data, max_features, conditions = NULL)
```

Arguments

<code>data</code>	input data provided to FeatSeek either SummarizedExperiment or 2 dimensional array with features x samples
<code>conditions</code>	if data is a 2 dimensional array with features x samples a factor indicating which sample corresponds to which condition must be provided

Value

SummarizedExperiment where condition information is stored in `colData`

FeatSeek

FeatSeek

Description

This function ranks features of a 2 dimensional array according to their reproducibility between conditions.

Usage

```
FeatSeek(
  data,
  conditions = NULL,
  max_features = NULL,
  init = NULL,
  verbose = TRUE
)
```

Arguments

<code>data</code>	SummarizedExperiment with assay named <code>data</code> , where samples belongs to different conditions. Which sample belongs to which condition should be indicated in <code>colData</code> slot <code>conditions</code> . Or <code>matrix</code> with features x samples. Each conditions have multiple samples from replicated measurements.
<code>conditions</code>	factor of length samples, indicating which sample belongs to which condition. Only required if <code>data</code> is provided as <code>matrix</code> .
<code>max_features</code>	integer number of features to rank
<code>init</code>	character vector with names of initial features. If <code>NULL</code> the feature with highest F-statistic will be used
<code>verbose</code>	logical indicating whether messages should be printed

Value

SummarizedExperiment containing one assay with the selected features. rowData stores for each selected feature the F-statistic under metric, the cumulative explained variance under explained_variance and the feature names under selected

Examples

```
# run FeatSeek to select the top 20 features
data <- array(rnorm(100*30), dim=c(30, 100),
dimnames <- list(paste("feature", seq_len(30)), NULL))
conds <- rep(seq_len(50), 2)
res <- FeatSeek(data, conds, max_features=20)

# res stores the 20 selected features ranked by their replicate
# reproducibility
```

FeatSeekR*FeatSeekR an R package for unsupervised feature selection*

Description

FeatSeekR performs unsupervised feature selection using replicated measurements. It iteratively selects features with the highest reproducibility across conditions, after projecting out those dimensions from the data that are spanned by the previously selected features. The selected a set of features has a high replicate reproducibility and a high degree of uniqueness.

Details

For information on how to use this package please type vignette("FeatSeekR-vignette").

Please post questions regarding the package to the Bioconductor Support Site:

<https://support.bioconductor.org>

Author(s)

Tümay Capraz

fit_lm	<i>fit_lm</i>
--------	---------------

Description

Fit linear model for each feature as a function of the previously selected features S. The dimensions spanned by the selected features are projected out of the data by setting each feature to its residuals from the linear model fit.

Usage

fit_lm(data, S, k)

Arguments

- | | |
|------|---|
| data | data (2 dimensional array samples x features) |
| S | set of selected features |
| k | current iteration |

Value

data with previously selected features projected out

init_selected	<i>init_selected</i>
---------------	----------------------

Description

Checks if preselected init features are in input data. If init is NULL, it is set to feature with highest condition correlation.

Usage

init_selected(init, se)

Arguments

- | | |
|------|--------------------------------------|
| init | preselected starting set of features |
| data | input data as SummarizedExperiment |

Value

names of initial set of feature

plotSelectedFeatures *plotSelectedFeatures*

Description

plot correlation matrix of selected feature sets

Usage

```
plotSelectedFeatures(res, n_features = NULL, assay = "selected")
```

Arguments

res	result SummarizedExperiment from FeatSeek function
n_features	top n_features to plot. if NULL then the maximum number of features in res will be plotted
assay	assay slot to plot from result SummarizedExperiment object, default is the selected features slot

Value

returns heatmap of selected features

Examples

```
# run FeatSeek to select the top 20 features
data <- array(rnorm(100*30), dim=c(30,100),
             dimnames = list(paste("feature", seq_len(30)), NULL))
conds <- rep(seq_len(50), 2)
res <- FeatSeek(data, conds, max_features=20)

# res stores the 20 selected features ranked by their replicate
# reproducibility
# plot the top 5 features
plotSelectedFeatures(res, n_features=5)
```

plotVarianceExplained *plotVarianceExplained*

Description

plot variance explained from 1 to max_features in res

Usage

```
plotVarianceExplained(res)
```

Arguments

res result SummarizedExperiment from FeatSeek function

Value

returns plot of variance explained vs number of features

Examples

```
# run FeatSeek to select the top 20 features
data <- array(rnorm(100*30), dim=c(30,100),
              dimnames = list(paste("feature", seq_len(30)), NULL))
conds <- rep(seq_len(50), 2)
res <- FeatSeek(data, conds, max_features=20)

# res stores the 20 selected features ranked by their replicate
# reproducibility
plotVarianceExplained(res)
```

simData

*simData***Description**

simulate Data with orthogonal feature clusters and replicated samples. Each feature cluster corresponds to a different latent factor and contains 10 redundant features. E.g. choosing samples = 100, n_latent_factors = 5 and replicates = 2 will simulate a 50 x 200 data matrix, where the first 100 samples belong to replicate 1 and sample 101-200 belong to replicate 2.

Usage

```
simData(conditions, n_latent_factors, replicates)
```

Arguments

conditions number of conditions to generate samples from
n_latent_factors number of latent factors to generate
replicates number of replicates to generate

Details

simData constructs n_latent_factors by generating a random matrix $\mathbf{Q}$ whose row vectors $\mathbf{Q}_i \sim \mathcal{N}(0, 1)$ with n samples and $i \in \{1, \dots, n_latent_factors\}$ are orthonormal, each corresponding to a different latent factor. To simulate a set of redundant feature groups, it generates 10 features X_j for each latent factor $\mathbf{Q}_i$ by scaling each latent factor by a random factor $\delta_j \sim \mathcal{N}(0, 1)$ and adding replicate specific noise $\epsilon_c \sim \mathcal{N}(0, 0.1)$ with $c \in \{1, \dots, replicates\}$ preserving orthogonality.

Value

SummarizedExperiment object carrying simulated data, with colData indicating which sample belongs to which replicate

Examples

```
# simulate data 100 samples from 100 conditions, 20 features generated by 2
# latent factors and 2 replicates
simData(conditions=100, n_latent_factors=2, replicates=2)
```

variance_explained	<i>variance_explained</i>
--------------------	---------------------------

Description

variance_explained

Usage

```
variance_explained(data, selected)
```

Arguments

- data 2 dimensional array samples x features
- selected character vector of selected features

Value

average variance explained by selected features

Index

* **internal**

- calcFstat, [2](#)
- check_input, [2](#)
- fit_lm, [5](#)
- init_selected, [5](#)
- variance_explained, [8](#)

* **package**

- FeatSeekR, [4](#)

- calcFstat, [2](#)
- check_input, [2](#)

- FeatSeek, [3](#)
- FeatSeekR, [4](#)
- fit_lm, [5](#)

- init_selected, [5](#)

- plotSelectedFeatures, [6](#)
- plotVarianceExplained, [6](#)

- simData, [7](#)

- variance_explained, [8](#)