

Package ‘SubCellBarCode’

September 23, 2026

Type Package

Title SubCellBarCode: Integrated workflow for robust mapping and visualizing whole human spatial proteome

Version 1.28.0

Author Taner Arslan

Maintainer Taner Arslan <taner.arslan@ki.se>

Description Mass-Spectrometry based spatial proteomics have enabled the proteome-wide mapping of protein subcellular localization (Orre et al. 2019, Molecular Cell). SubCellBarCode R package robustly classifies proteins into corresponding subcellular localization.

License GPL-2

Encoding UTF-8

LazyData true

Depends R (>= 3.6)

Suggests knitr, rmarkdown, BiocStyle

Imports Rtsne, scatterplot3d, caret, e1071, ggplot2, gridExtra, networkD3, ggrepel, graphics, stats, org.Hs.eg.db, AnnotationDbi

biocViews Proteomics, MassSpectrometry, Classification

RoxygenNote 7.1.1

VignetteBuilder knitr

git_url <https://git.bioconductor.org/packages/SubCellBarCode>

git_branch RELEASE_3_23

git_last_commit a89b14c

git_last_commit_date 2026-04-28

Repository Bioconductor 3.23

Date/Publication 2026-09-22

Contents

applyThresholdCompartment	2
applyThresholdNeighborhood	3
calculateCoveredProtein	4
calRowMean	5
candidateRelocatedProteins	6
compareCls	7
computeThresholdCompartment	8
computeThresholdNeighborhood	9
convert2symbol	10
hcc827Ctrl	11
hcc827CtrlPSMCount	11
hcc827exon	12
hcc827GEF	13
hcc827GEFClass	13
hcc827GefPSMCount	14
loadData	14
markerProteins	15
markerQualityControl	15
mergeCls	16
mergeProbability	17
plotBarcode	18
plotMultipleProtein	20
replacePrediction	20
sankeyPlot	21
sumProbability	22
svmClassification	23
svmExternalData	24
tsneVisualization	25
Index	26

applyThresholdCompartment

Apply thresholds to compartments

Description

Apply thresholds for all predictions to increase the true positive rate and remove poor classification.

Usage

```
applyThresholdCompartment(all.repA, all.repB, threshold.df)
```

Arguments

all.repA data.frame; all predictions and probability vectors for each protein in replicate A
all.repB data.frame; all predictions and probability vectors for each protein in replicate B
threshold.df data.frame; collection of precision and recall values for each compartment

Value

c.cls.df

Examples

```
{
df <- loadData(SubCellBarCode::hcc827Ctrl)

c.prots <- calculateCoveredProtein(rownames(df), markerProteins[,1])

set.seed(7)
c.prots <- sample(c.prots, 550)
cls <- svmClassification(c.prots, df, markerProteins)

test.A <- cls[[1]]$svm.test.prob.out
test.B <- cls[[2]]$svm.test.prob.out

t.c.df <- computeThresholdCompartment(test.A, test.B)

all.A <- cls[[1]]$all.prot.pred
all.B <- cls[[2]]$all.prot.pred

c.cls.df <- applyThresholdCompartment(all.A, all.B, t.c.df)
}
```

applyThresholdNeighborhood

Apply thresholds to neighborhood classification

Description

Apply thresholds for all predictions at the neighborhood level to increase the true positive rate and remove poor classification.

Usage

```
applyThresholdNeighborhood(all.repA, all.repB, threshold.df)
```

Arguments

all.repA data.frame; all predictions and probability vectors for each protein in replicate A
 all.repB data.frame; all predictions and probability vectors for each protein in replicate B
 threshold.df data.frame; collection of precision and recall values for each neighborhood

Value

n.cls.df

Examples

```
{
  df <- loadData(SubCellBarCode::hcc827Ctrl)

  c.prots <- calculateCoveredProtein(rownames(df), markerProteins[,1])

  set.seed(7)
  c.prots <- sample(c.prots, 600)
  cls <- svmClassification(c.prots, df, markerProteins)

  test.A <- cls[[1]]$svm.test.prob.out
  test.B <- cls[[2]]$svm.test.prob.out

  t.n.df <- computeThresholdNeighborhood(test.A, test.B)

  all.A <- cls[[1]]$all.prot.pred
  all.B <- cls[[2]]$all.prot.pred

  n.cls.df <- applyThresholdNeighborhood(all.A, all.B, t.n.df)
}
```

calculateCoveredProtein

Evaluate marker protein coverage

Description

Given the proteomics data, number of overlapped marker proteins is calculated. Bar plot for each compartment is plotted.

Usage

```
calculateCoveredProtein(proteinIDs, markerproteins)
```

Arguments

proteinIDs character; gene symbol id
 markerproteins character; 3365 proteins gene symbol ids

Value

covered.proteins

Examples

```
{  
df <- loadData(SubCellBarCode::hcc827Ctrl)  
  
c.prots <- calculateCoveredProtein(rownames(df), markerProteins[,1])  
}
```

calRowMean

Compute the means of replicates

Description

Duplicated fractions A and B are summarized by taking their mean for each protein. After taking the mean, the data log2 transformed. Further, the 5 main fractions are used to check correlation between input datas. It is a helper function.

Usage

```
calRowMean(d.df)
```

Arguments

d.df data.frame; A data frame of 10 fraction profiles consisting of replicate A and B.

Value

r.df

Examples

```
{  
  
r.df <- calRowMean(SubCellBarCode::hcc827Ctrl)  
  
}
```

candidateRelocatedProteins

Identify candidate relocated proteins

Description

Identify candidate condition-dependent relocated proteins by comparing neighborhood classifications with respect to protein-protein pearson correlation and minumum PSM, peptide spectrum matching, count.

Usage

```
candidateRelocatedProteins(
  sampleCls1,
  s1PSM,
  s1Quant,
  sampleCls2,
  s2PSM,
  s2Quant,
  annotation = FALSE,
  min.psm = 2,
  pearson.cor = 0.8
)
```

Arguments

sampleCls1	data.frame; merged classification, combination of compartment and neighborhood classification.
s1PSM	data.frame; minimum PSM count table across ten TMT channel
s1Quant	data.frame; fractionation quantification data
sampleCls2	data.frame; merged classification, combination of compartment and neighborhood classification.
s2PSM	data.frame; minimum PSM count table across ten TMT channel
s2Quant	data.frame; fractionation quantification data
annotation	boolean; labeling the selected proteins
min.psm	numeric; minimum psm, peptide spectra matching value
pearson.cor	numeric; pearson correlation threshold

Value

candidate.df

Examples

```
{

  candidate.df <- candidateRelocatedProteins(hcc827GEFClass, hcc827GefPSMCount,
  hcc827GEF, hcc827GEFClass, hcc827GefPSMCount, hcc827GEF,
  annotation = FALSE)

}
```

compareCls	<i>Compare exon and gene centric classifications</i>
------------	--

Description

Comparison of the gene centric and exon centric classification. Additionally, correlation analysis is performed using quantification data.

Usage

```
compareCls(geneCls, exonCls)
```

Arguments

geneCls	data frame gene centric classification output
exonCls	data frame exon centric classification output

Value

```
c.df
```

Examples

```
{

  exon.cls <- data.frame(Protein = c("ENSE00000331854",
                                   "ENSE00000331855",
                                   "ENSE00000331859"),
                        NeighborhoodCls = c("Cytosol",
                                             "Cytosol",
                                             "Cytosol"),
                        CompartmentCls = c("C1", "C1", "C1"),
                        Secretory = c(0.1, 0.1, 0.1),
                        Nuclear = c(0.2, 0.2, 0.2),
                        Cytosol = c(0.2, 0.2, 0.2),
                        Mitochondria = c(0.2, 0.2, 0.2),
                        S1 = c(0.2, 0.2, 0.2),
                        S2 = c(0.2, 0.2, 0.2),
                        S3 = c(0.2, 0.2, 0.2),
```

```

      S4 = c(0.2, 0.2, 0.2),
      N1 = c(0.2, 0.2, 0.2),
      N2 = c(0.2, 0.2, 0.2),
      N3 = c(0.2, 0.2, 0.2),
      N4 = c(0.2, 0.2, 0.2),
      C1 = c(0.2, 0.2, 0.2),
      C2 = c(0.2, 0.2, 0.2),
      C3 = c(0.2, 0.2, 0.2),
      C4 = c(0.2, 0.2, 0.2),
      C5 = c(0.2, 0.2, 0.2),
      M1 = c(0.2, 0.2, 0.2),
      M2 = c(0.2, 0.2, 0.2),
      GeneSymbol = c("COPB1", "COPB1", "COPB1"),
      PeptideCount = c(2, 4, 7))

gene.cls <- data.frame(Protein = c("COPB1"),
  NeighborhoodCls = c("Cytosol"),
  CompartmentCls = c("C1"),
  Secretory = c(0.1),
  Nuclear = c(0.2),
  Cytosol = c(0.2),
  Mitochondria = c(0.2),
  S1 = c(0.2),
  S2 = c(0.2),
  S3 = c(0.2),
  S4 = c(0.2),
  N1 = c(0.2),
  N2 = c(0.2),
  N3 = c(0.2),
  N4 = c(0.2),
  C1 = c(0.2),
  C2 = c(0.2),
  C3 = c(0.2),
  C4 = c(0.2),
  C5 = c(0.2),
  M1 = c(0.2),
  M2 = c(0.2))

comp.df <- compareCls(gene.cls, exon.cls)

}

```

```
computeThresholdCompartment
```

Probability threshold for compartment classification

Description

Thresholds for each compartment are decided to get confident predictions.

Usage

```
computeThresholdCompartment(test.repA, test.repB)
```

Arguments

test.repA	data.frame; test predictions, observation and probability vectors for each protein in replicate A
test.repB	data.frame; test predictions, observation and probability vectors for each protein in replicate B

Value

```
threshold.compartment.df
```

Examples

```
{
  df <- loadData(SubCellBarCode::hcc827Ctrl)

  c.prots <- calculateCoveredProtein(rownames(df), markerProteins[,1])

  set.seed(7)
  c.prots <- sample(c.prots, 550)
  cls <- svmClassification(c.prots, df, markerProteins)

  test.A <- cls[[1]]$svm.test.prob.out
  test.B <- cls[[2]]$svm.test.prob.out

  t.c.df <- computeThresholdCompartment(test.A, test.B)
}
```

```
computeThresholdNeighborhood
```

Probability threshold for neighborhood classification

Description

Thresholds for each neighborhood are decided to get confident predictions.

Usage

```
computeThresholdNeighborhood(test.repA, test.repB)
```

Arguments

test.repA	data.frame; test predictions, observation and probability vectors for each protein in replicate A
test.repB	data.frame; test predictions, observation and probability vectors for each protein in replicate B

Value

threshold.neighborhood.df

Examples

```
{
df <- loadData(SubCellBarCode::hcc827Ctrl)

c.prots <- calculateCoveredProtein(rownames(df), markerProteins[,1])

set.seed(7)
c.prots <- sample(c.prots, 600)
cls <- svmClassification(c.prots, df, markerProteins)

test.A <- cls[[1]]$svm.test.prob.out
test.B <- cls[[2]]$svm.test.prob.out

t.n.df <- computeThresholdNeighborhood(test.A, test.B)
}
```

convert2symbol	<i>Convert identifier to gene symbol</i>
----------------	--

Description

Identifier for each feature should be converted into gene symbols unless they are not gene symbols

Usage

```
convert2symbol(df, id = "UNIPROT")
```

Arguments

- df data.frame; fractionated proteomics data where data contains 10 columns of duplicated 5 fractionations and rownames must be identifier e.g. UNIPROT, Entrez ID
- id caharacter; identifier id for each protein

Value

df

Examples

```
{  
  
df <- data.frame(Uniprot = c("A4D0S4", "A8TX70", "000305", "000337"),  
Organism = rep("Homo Sap.", 4))  
  
rownames(df) <- df$Uniprot  
}
```

hcc827Ctrl	<i>HCC827 Control Cell Line</i>
------------	---------------------------------

Description

Subcellular fractionated cell line.

Usage

```
hcc827Ctrl
```

Format

A data frame where 10480 protein gene-centric ids and 5 replicated subcellular fractions.

References

Orre et al. 2019 Cell 73, 1-17

Examples

```
{  
head(hcc827Ctrl)  
}
```

hcc827CtrlPSMCount	<i>Minimum PSM Count in HCC827Ctrl Cell Line.</i>
--------------------	---

Description

Minimum PSM, Peptide Sequence Match, Count table for HCC827Ctrl Cell Line.

Usage

```
hcc827CtrlPSMCount
```

Format

A data frame where 10480 protein gene-centric ids minimum PSM count.

References

Orre et al. 2019 Cell 73, 1-17

Examples

```
{  
  head(hcc827Ctr1PSMCount)  
}
```

hcc827exon

HCC827 Control Exon Cell Line

Description

Exon-centric sub data of hcc827 fractionated data.

Usage

hcc827exon

Format

A data frame where 500 exon-centric ensemble identifiers, corresponding gene symbols, 5 replicated subcellular fractions and number of unique peptides matched to associated exon.

References

Orre et al. 2019 Cell 73, 1-17

Examples

```
{  
  head(hcc827exon)  
}
```

`hcc827GEF`*Gefitinib treated HCC827 Cell Line*

Description

HCC827 cell line was treated with Gefitinib which is EGFR inhibition.

Usage`hcc827GEF`**Format**

A data frame where 10398 protein gene-centric ids and 5 replicated subcellular fractions with duplicates.

References

Orre et al. 2019 Cell 73, 1-17

Examples

```
{  
  head(hcc827GEF)  
}
```

`hcc827GEFClass`*Gefitinib treated HCC827 Cell Line Classification*

Description

Gefitinib treated HCC827 cell line classification contains both neighborhood and compartment level. The data will be used for the relocation analysis.

Usage`hcc827GEFClass`**Format**

A data frame where 10398 protein gene-centric ids and corresponding compartment and neighborhood classification along with classification probabilities.

References

Orre et al. 2019 Cell 73, 1-17

Examples

```
{
  head(hcc827GEFC1ass)
}
```

hcc827GefPSMCount	<i>Minimum PSM Count in HCC827 Gefitinib Cell Line.</i>
-------------------	---

Description

Minimum PSM, Peptide Sequence Match, Count table for HCC827 Gefitinib Cell Line.

Usage

```
hcc827GefPSMCount
```

Format

A data frame where 10398 protein gene-centric ids minimum PSM count.

References

Orre et al. 2019 Cell 73, 1-17

Examples

```
{
  head(hcc827GefPSMCount)
}
```

loadData	<i>Load the fractionated proteomics data</i>
----------	--

Description

Sampled median normalized TMT ratios are checked if there is any "NA" value. If any, the corresponding row is filtered out. Later, the data is normalized by taking log2.

Usage

```
loadData(protein.data)
```

Arguments

protein.data	data.frame; fractionated proteomics data where data contains 10 columns of duplicated 5 fractionations and rownames must be gene-centric protein names
--------------	--

Value

protein.data.df

Examples

```
{  
df <- loadData(SubCellBarCode::hcc827Ctrl[1:20,])  
}
```

markerProteins	<i>Marker Proteins Source</i>
----------------	-------------------------------

Description

Data for the proteins whose localizations were well characterized. It also contains color codes for each compartment and median fractionation profiles for 5 fractions which are Cyto., Nsol., NucI., Horg., Lorg., with replicates A and B. These fractionation profiles will be used for the marker protein quality control.

Usage

```
markerProteins
```

Format

A data frame of 3365 proteins as rows and 13 columns headers.

References

Orre et al. 2019 Cell 73, 1-17

markerQualityControl	<i>Evaluate the quality of the marker proteins</i>
----------------------	--

Description

Given the proteomics data, quality of the overlapped marker proteins are evaluated by correlating replicates of fractions.

Usage

```
markerQualityControl(coveredProteins, protein.data)
```

Arguments

`coveredProteins` character; list of marker proteins, gene symbols, that are covered in 3365 marker proteins.

`protein.data` data.frame; fractionated proteomics data, rownames are gene symbols associated protein.

Value

`robustMarkers`

Examples

```
{
df <- loadData(SubCellBarCode::hcc827Ctrl)

c.prots <- calculateCoveredProtein(rownames(df), markerProteins[,1])

r.markers <- markerQualityControl(c.prots[1:5], df)
}
```

`mergeCls`

Merge compartment and neighborhood classification

Description

Compartment and neighborhood classifications are merged for the single output.

Usage

```
mergeCls(compartmentCls, neighborhoodCls)
```

Arguments

`compartmentCls` data.frame; all predictions, including unclassified as well, and probability vectors for each protein in compartment classification

`neighborhoodCls` data.frame; all predictions, including unclassified as well, and probability vectors for each protein in neighborhood classification

Value

`cls.df`

Examples

```
{
  #create mock data
  com.df <- data.frame(Proteins = "TP53",
    svm.pred = "N1",
    S1 = as.numeric(0.02),
    S2 = as.numeric(0.02),
    S3 = as.numeric(0.02),
    S4 = as.numeric(0.02),
    N1 = as.numeric(0.72),
    N2 = as.numeric(0.02),
    N3 = as.numeric(0.02),
    N4 = as.numeric(0.02),
    C1 = as.numeric(0.02),
    C2 = as.numeric(0.02),
    C3 = as.numeric(0.02),
    C4 = as.numeric(0.02),
    C5 = as.numeric(0.02),
    M1 = as.numeric(0.02),
    M2 = as.numeric(0.02))

  rownames(com.df) <- "TP53"

  neig.df <- data.frame(Proteins = "TP53",
    svm.pred.all = "Nuclear",
    Secretory = as.numeric(0.01),
    Nuclear = as.numeric(0.95),
    Cytosol = as.numeric(0.02),
    Mitochondria = as.numeric(0.02))

  rownames(neig.df) <- "TP53"

  cls.df <- mergeCls(com.df, neig.df)
}
```

mergeProbability

*Merge compartment probabilities to neighborhood probabilities***Description**

Compartment levels classifications are summed up to associated neighborhood levels. It is a helper function.

Usage

```
mergeProbability(df)
```

Arguments

df data.frame; all predictions at the neighborhood level and probability vectors for each protein

Value

merged.df

Examples

```
{
  #create mock data
  df <- data.frame(Protein = "TP53",
    S1 = as.numeric(0.02),
    S2 = as.numeric(0.02),
    S3 = as.numeric(0.02),
    S4 = as.numeric(0.02),
    N1 = as.numeric(0.72),
    N2 = as.numeric(0.02),
    N3 = as.numeric(0.02),
    N4 = as.numeric(0.02),
    C1 = as.numeric(0.02),
    C2 = as.numeric(0.02),
    C3 = as.numeric(0.02),
    C4 = as.numeric(0.02),
    C5 = as.numeric(0.02),
    M1 = as.numeric(0.02),
    M2 = as.numeric(0.02))

  rownames(df) <- "TP53"

  merged.df <- mergeProbability(df)
}
```

plotBarcode

Visualize the SubCellBarCode

Description

Stacked bar plot are plotted for compartment and neighborhood level with respect to classification probabilities.

Usage

```
plotBarcode(sampleClassification, protein, s1PSM)
```

Arguments

sampleClassification	data.frame; merged classification, combination of compartment and neighborhood classification.
protein	character; protein gene symbol name
s1PSM	data.frame; minimum PSM count table. Row names should be gene centric protein id.

Value

proteinPlot

Examples

```
{
#create mock data
plot.df <- data.frame(Protein = "TP53",
NeighborhoodCls = "Nuclear",
CompartmentCls = "N1",
Secretory = as.numeric(0.01),
Nuclear = as.numeric(0.95),
Cytosol = as.numeric(0.02),
Mitochondria = as.numeric(0.02),
S1 = as.numeric(0.02),
S2 = as.numeric(0.02),
S3 = as.numeric(0.02),
S4 = as.numeric(0.02),
N1 = as.numeric(0.72),
N2 = as.numeric(0.02),
N3 = as.numeric(0.02),
N4 = as.numeric(0.02),
C1 = as.numeric(0.02),
C2 = as.numeric(0.02),
C3 = as.numeric(0.02),
C4 = as.numeric(0.02),
C5 = as.numeric(0.02),
M1 = as.numeric(0.02),
M2 = as.numeric(0.02))

rownames(plot.df) <- "TP53"

psm.df <- data.frame(Protein = "TP53",
PSMs.for.quant = as.numeric(31))

rownames(psm.df) <- "TP53"

proteinPlot <- plotBarcode(plot.df, "TP53", psm.df)
}
```

plotMultipleProtein	<i>Visualization of multiple protein localizations</i>
---------------------	--

Description

Distributions of subcellular localizations of multiple proteins both at the compartment and neighborhood level are plotted.

Usage

```
plotMultipleProtein(sampleClassification, proteinList)
```

Arguments

sampleClassification	data.frame; merged classification, combination of compartment and neighborhood classifications per protein.
proteinList	vector; protein gene symbol names.

Value

multipleProt.df

Examples

```
{
  proteasome26s <- c("PSMA7", "PSMC3", "PSMB1", "PSMA1", "PSMA3", "PSMA4",
    "PSMA5", "PSMB4", "PSMB6", "PSMB5", "PSMC2", "PSMC4", "PSMB3", "PSMB2",
    "PSMD4", "PSMA6", "PSMC1", "PSMC5", "PSMC6", "PSMB7", "PSMD13")

  exp.cls.df <- SubCellBarCode::hcc827GEFCClass

  multipleProt.df <- plotMultipleProtein(exp.cls.df, proteasome26s )
}
```

replacePrediction	<i>Replace compartment predictions to neighborhood predictions</i>
-------------------	--

Description

Compartment level classifications are replaced with neighborhood level assignment. It is a helper function.

Usage

```
replacePrediction(df, column = c("svm.pred.all", "Observation", "svm.pred"))
```

Arguments

- df data.frame; all predictions at the compartment level and probability vectors for each protein
- column character; selected column in the data frame, df

Value

replaced.df

Examples

```
{  
  
#define mock data frame  
df <- data.frame(svm.pred.all = c("S1", "S2", "S3", "S4",  
  "N1", "N2", "N3", "N4",  
  "C1", "C2", "C3", "C4", "C5",  
  "M1", "M2"))  
  
df$svm.pred.all <- as.character(df$svm.pred.all)  
df$Prob <- "1"  
  
df <- replacePrediction(df, column = "svm.pred.all")  
}
```

sankeyPlot	<i>Sankey plot for condition-dependent protein relocation</i>
------------	---

Description

Identify candidate condition-dependent relocated proteins by comparing neighborhood classifications.

Usage

```
sankeyPlot(sampleCls1, sampleCls2)
```

Arguments

- sampleCls1 data.frame; merged classification, combination of compartment and neighborhood classification.
- sampleCls2 data.frame; merged classification, combination of compartment and neighborhood classification.

Value

label.link.df

Examples

```
{  
  
exp.cls.df <- SubCellBarCode::hcc827GEFClass  
  
sankeyData <- sankeyPlot(exp.cls.df, exp.cls.df)  
  
}
```

sumProbability	<i>Sum compartment test data probabilities to neighborhood probabilities</i>
----------------	--

Description

Compartment levels classifications on the test data are summed up to associated neighborhood levels. It is a helper function.

Usage

```
sumProbability(df)
```

Arguments

df data.frame; test data classifications at the neighborhood level and probability vectors for each protein.

Value

summed.df

Examples

```
{  
  
#create mock data  
df <- data.frame(Protein = "TP53",  
svm.pred = "N1",  
S1 = as.numeric(0.02),  
S2 = as.numeric(0.02),  
S3 = as.numeric(0.02),  
S4 = as.numeric(0.02),  
N1 = as.numeric(0.72),  
N2 = as.numeric(0.02),  
N3 = as.numeric(0.02),
```

```

N4 = as.numeric(0.02),
C1 = as.numeric(0.02),
C2 = as.numeric(0.02),
C3 = as.numeric(0.02),
C4 = as.numeric(0.02),
C5 = as.numeric(0.02),
M1 = as.numeric(0.02),
M2 = as.numeric(0.02))

rownames(df) <- "TP53"

sum.df <- sumProbability(df)

}

```

svmClassification	<i>Protein subcellular localization classification</i>
-------------------	--

Description

Support Vector Machine classifier is trained and used for prediction of protein subcellular localization

Usage

```
svmClassification(markerProteins, protein.data, markerprot.df)
```

Arguments

markerProteins	character; robust marker proteins along with subcellular localization that are present in the given data.
protein.data	data.frame; fractionated proteomics data
markerprot.df	data.frame; collection of marker proteins along with corresponding subcellular localization

Value

all.classifications

Examples

```

{

df <- loadData(SubCellBarCode::hcc827Ctrl)

c.prots <- calculateCoveredProtein(rownames(df), markerProteins[,1])

set.seed(7)
c.prots <- sample(c.prots, 500)

```

```

cls <- svmClassification(c.prots, df, markerProteins)

}

```

svmExternalData

Peptide/exon/transcript centric or PTM enriched classification

Description

Peptide/exon/transcript centric or PTM enriched classification is applied to predict localization of them.

Usage

```
svmExternalData(df, modelA, modelB)
```

Arguments

df	data frame fractionated additional data
modelA	model for the replicate A classification
modelB	model for the replicate B classification

Value

c.cls.df

Examples

```

{

df <- loadData(SubCellBarCode::hcc827Ctrl)

c.prots <- calculateCoveredProtein(rownames(df), markerProteins[,1])

set.seed(7)
c.prots <- sample(c.prots, 550)
cls <- svmClassification(c.prots, df, markerProteins)
modelA <- cls[[1]]$model
modelB <- cls[[2]]$model

exon.cls <- svmExternalData(SubCellBarCode::hcc827exon,
modelA = modelA, modelB = modelB)

}

```

tsneVisualization	<i>Visualization of marker proteins by t-SNE map</i>
-------------------	--

Description

The marker proteins are visualized in 3D t-SNE map to see the distributions of the marker proteins.

Usage

```
tsneVisualization(protein.data, markerProteins, dims, theta, perplexity)
```

Arguments

protein.data	data.frame; fractionated proteomics data
markerProteins	character; robust marker proteins, gene symbols, that are present in the given data and overlapped with package's marker protein list.
dims	integer; dimensionality
theta	numeric; Speed/accuracy trade-off ,increase for less accuracy
perplexity	integer; Perplexity parameter

Value

tsneMap.df

Examples

```
{  
  
df <- loadData(SubCellBarCode::hcc827Ctrl)  
  
c.prots <- calculateCoveredProtein(rownames(df), markerProteins[,1])  
  
set.seed(21)  
tsneMap.df <- tsneVisualization(protein.data = df,  
markerProteins = c.prots[1:20],  
dims = 2, theta = c(0.4), perplexity = c(5))  
}
```

Index

* datasets

- [hcc827Ctrl](#), [11](#)
- [hcc827CtrlPSMCount](#), [11](#)
- [hcc827exon](#), [12](#)
- [hcc827GEF](#), [13](#)
- [hcc827GEFClass](#), [13](#)
- [hcc827GefPSMCount](#), [14](#)
- [markerProteins](#), [15](#)

- [applyThresholdCompartment](#), [2](#)
- [applyThresholdNeighborhood](#), [3](#)

- [calculateCoveredProtein](#), [4](#)
- [calRowMean](#), [5](#)
- [candidateRelocatedProteins](#), [6](#)
- [compareCls](#), [7](#)
- [computeThresholdCompartment](#), [8](#)
- [computeThresholdNeighborhood](#), [9](#)
- [convert2symbol](#), [10](#)

- [hcc827Ctrl](#), [11](#)
- [hcc827CtrlPSMCount](#), [11](#)
- [hcc827exon](#), [12](#)
- [hcc827GEF](#), [13](#)
- [hcc827GEFClass](#), [13](#)
- [hcc827GefPSMCount](#), [14](#)

- [loadData](#), [14](#)

- [markerProteins](#), [15](#)
- [markerQualityControl](#), [15](#)
- [mergeCls](#), [16](#)
- [mergeProbability](#), [17](#)

- [plotBarcode](#), [18](#)
- [plotMultipleProtein](#), [20](#)

- [replacePrediction](#), [20](#)

- [sankeyPlot](#), [21](#)
- [sumProbability](#), [22](#)

- [svmClassification](#), [23](#)

- [svmExternalData](#), [24](#)

- [tsneVisualization](#), [25](#)