

Package ‘TCGAutils’

September 23, 2026

Title TCGA utility functions for data management

Version 1.32.2

Date 2025-12-11

Description A suite of helper functions for checking and manipulating TCGA data including data obtained from the curatedTCGAData experiment package. These functions aim to simplify and make working with TCGA data more manageable. Exported functions include those that import data from flat files into Bioconductor objects, convert row annotations, and identifier translation via the GDC API.

Depends R (>= 4.5.0)

Imports AnnotationDbi, BiocGenerics, BiocBaseUtils, GenomeInfoDb, GenomicFeatures, GenomicRanges, GenomicDataCommons, glue, IRanges, methods, MultiAssayExperiment, RaggedExperiment, rvest, S4Vectors, Seqinfo, stats, stringr, SummarizedExperiment, utils, xml2

Suggests AnnotationHub, Bioc.gff, BiocFileCache, BiocStyle, curatedTCGAData, ComplexHeatmap, devtools, dplyr, httr, IlluminaHumanMethylation450kanno.ilmn12.hg19, impute, knitr, magrittr, miRNANameConverter, org.Hs.eg.db, RColorBrewer, readr, rmarkdown, RTCGAToolbox, rtracklayer, R.utils, testthat, TxDb.Hsapiens.UCSC.hg18.knownGene, TxDb.Hsapiens.UCSC.hg19.knownGene

License Artistic-2.0

Roxygen list(markdown = TRUE)

Encoding UTF-8

BugReports <https://github.com/waldrnlab/TCGAutils/issues>

biocViews Software, WorkflowStep, Preprocessing, DataImport

VignetteBuilder knitr

Config/roxygen2/version 8.0.0

git_url <https://git.bioconductor.org/packages/TCGAutils>

git_branch RELEASE_3_23

git_last_commit 8508150

git_last_commit_date 2026-07-02

Repository Bioconductor 3.23

Date/Publication 2026-09-22

Author Marcel Ramos [aut, cre] (ORCID:
<https://orcid.org/0000-0002-3242-0582>),
 Lucas Schiffer [aut],
 Sean Davis [ctb],
 Levi Waldron [aut],
 NCI [fnd] (GrantNo.: U24CA289073)

Maintainer Marcel Ramos <marcel.amos@sph.cuny.edu>

Contents

TCGAutils-package	3
builds	3
clinicalNames	5
curatedTCGAData-helpers	6
diseaseCodes	7
findGRangesCols	8
generateMap	9
getFileName	10
hidden-helpers	11
ID-translation	11
imputeAssay	14
makeGRangesListFromCopyNumber	15
makeGRangesListFromExonFiles	16
mergeColData	17
oncoPrintTCGA	18
sampleTypes	19
simplifyTCGA	20
TCGAbarcode	22
TCGAbiospec	23
TCGAprimaryTumors	24
TCGAsampleSelect	24
trimColData	25
Index	26

TCGAutils-package	<i>TCGAutils: Helper functions for working with TCGA and MultiAssay-Experiment data</i>
-------------------	---

Description

TCGAutils is a toolbox to work with TCGA specific datasets. It allows the user to manipulate and translate TCGA barcodes, conveniently convert a list of data files to [GRangesList](#). Take datasets from GISTIC and return a [SummarizedExperiment](#) class object. The package also provides functions for working with data from the curatedTCGAData experiment data package. It provides convenience functions for extracting subtype metadata data and adding clinical data to existing [MultiAssayExperiment](#) objects.

Author(s)

Maintainer: Marcel Ramos <marcel.ramos@sph.cuny.edu> ([ORCID](#))

Authors:

- Marcel Ramos <marcel.ramos@sph.cuny.edu> ([ORCID](#))
- Lucas Schiffer
- Levi Waldron

Other contributors:

- Sean Davis [contributor]
- NCI (GrantNo.: U24CA289073) [funder]

See Also

Useful links:

- Report bugs at <https://github.com/waldronlab/TCGAutils/issues>

builds	<i>Utilities for working with HUMAN genome builds</i>
--------	---

Description

A few functions are available to search for build versions, either from NCBI or UCSC.

- `translateBuild`: translates between UCSC and NCBI build versions
- `extractBuild`: use grep patterns to find the first build within the string input
- `uniformBuilds`: replace build occurrences below a threshold level of occurrence with the alternative build
- `correctBuild`: Ensure that the build annotation is correct based on the NCBI/UCSC website. If not, use `translateBuild` with the indicated 'style' input
- `isCorrect`: Check to see if the build is exactly as annotated

Usage

```

translateBuild(from, to = c("UCSC", "NCBI"))

correctBuild(build, style = c("UCSC", "NCBI"))

isCorrect(build, style = c("UCSC", "NCBI"))

extractBuild(string, build = c("UCSC", "NCBI"))

uniformBuilds(builds, cutoff = 0.2, na = c("", "NA"))

```

Arguments

from	character() A vector of build versions typically from <code>genome()</code> (e.g., "37"). The build vector must be homogenous (i.e., <code>length(unique(x)) == 1L</code>).
to	character(1) The name of the desired build version (either "UCSC" or "NCBI"; default: "UCSC")
build	A vector of build version names (default UCSC, NCBI)
style	character(1) The annotation style, either 'UCSC' or 'NCBI'
string	A single character string
builds	A character vector of builds
cutoff	numeric(1L) An inclusive threshold tolerance value for missing values and translating builds that are below the threshold
na	character() The values to be considered as missing (default: <code>c("", "NA")</code>)

Details

The `correctBuild` function takes the input and ensures that the style specified matches the input. Otherwise, it will return the correct style for use with `seqlevelsStyle`. Currently, the function does not support patched builds (e.g., 'GRCh38.p13') Build names are taken from the website: https://www.ncbi.nlm.nih.gov/assembly/GCF_000001405.26/

Value

`translateBuild`: A character vector of translated genome builds

`extractBuild`: A character string of the build information available

`uniformBuilds`: A character vector of builds where all builds are identical ``identical(length(unique(build)), 1L)``

`correctBuild`: A character string of the 'corrected' build name

`isCorrect`: A logical indicating if the build is exactly as annotated

Examples

```

translateBuild("GRCh35", "UCSC")

correctBuild("grch38", "NCBI")
correctBuild("hg19", "NCBI")

isCorrect("GRCh38", "NCBI")

isCorrect("hg19", "UCSC")

extractBuild(
  "SCENA_p_TCGAb29and30_SNP_N_GenomeWideSNP_6_G05_569110.nocnv_grch38.seg.txt"
)

buildvec <- rep(c("GRCh37", "hg19"), times = c(5, 1))
uniformBuilds(buildvec)

navec <- c(rep(c("GRCh37", "hg19"), times = c(5, 1)), "NA")
uniformBuilds(navec)

```

clinicalNames

Clinical dataset names in TCGA

Description

A dataset of names for each of the TCGA cancer codes available. These names were obtained by the clinical datasets from [getFirehoseData](#). They serve to subset the current datasets provided by `curatedTCGAData`.

Usage

```
data("clinicalNames")
```

Format

A [CharacterList](#) of names for 33 cancer codes

Value

The clinical dataset column names in TCGA as provided by the `RTCGAToolbox`

curatedTCGAData-helpers

Helper functions for managing MultiAssayExperiment from curatedTCGAData

Description

Additional helper functions for cleaning and uncovering metadata within a downloaded MultiAssayExperiment from curatedTCGAData.

Usage

```
getSubtypeMap(multiassayexperiment)
```

```
getClinicalNames(diseaseCode)
```

```
TCGASplitAssays(multiassayexperiment, sampleCodes = NULL, exclusive = FALSE)
```

```
sampleTables(multiassayexperiment, vial = FALSE)
```

Arguments

multiassayexperiment	A MultiAssayExperiment object
diseaseCode	A TCGA cancer code (e.g., "BRCA")
sampleCodes	character (default NULL) A string of sample type codes (refer to data(sampleTypes); TCGASplitAssays section)
exclusive	logical (default FALSE) Whether to return only assays that contain all codes in sampleCodes
vial	(logical default FALSE) whether to display vials in the table output

Details

Note that for getSubtypeMap, the column of in-data variable names may need to go through make.names to be found in the colData of the MultiAssayExperiment.

Value

- getSubtypeMap: A data.frame with explanatory names and their in-data variable names. They may not be present for all cancer types.
- getClinicalNames: A vector of common variable names that may be found across several cancer disease codes.

getSubtypeMap

provides a two column data.frame with interpreted names and in-data variable names. 'Name' usually refers to the colData row names a.k.a. the patientID.

getClinicalNames

provides a vector of common variable names that exist in the colData DataFrame of a curatedTCGAData MultiAssayExperiment object. These variables are directly obtained from the BroadFirehose clinical data (downloaded with [getFirehoseData](#)) and tend to be present across cancer disease codes.

TCGAsplitAssays

Separates samples by indicated sample codes into different assays in a MultiAssayExperiment. Refer to the sampleTypes data object for a list of available codes. This operation generates **n** times the number of assays based on the number of sample codes entered. By default, all assays will be split by samples present in the data.

sampleTables

Display all the available samples in each of the assays

Examples

```
library(curatedTCGAData)

gbm <- curatedTCGAData("GBM", c("RPPA*", "CNA*"), version = "2.0.1", FALSE)

getSubtypeMap(gbm)

sampleTables(gbm)

TCGAsplitAssays(gbm, c("01", "10"))

getClinicalNames("COAD")
```

diseaseCodes	<i>TCGA Cancer Disease Codes Table</i>
--------------	--

Description

A dataset for obtaining the cancer codes in TCGA for about 13 different types of cancers.

Usage

```
data("diseaseCodes")
```

Format

- A data frame with 37 rows and 2 variables:
- Study.Abbreviation: Disease Code used in TCGA
 - Available: Cancer datasets available via curatedTCGAData
 - SubtypeData: Subtype curation data available via curatedTCGAData
 - Study.Name: The full length study name (i.e., type of cancer)

Value

The TCGA diseaseCodes table

Source

<https://gdc.cancer.gov/resources-tcga-users/tcga-code-tables/tcga-study-abbreviations>

findGRangesCols	<i>Obtain minimum necessary names for the creation of a GRangesList object</i>
-----------------	--

Description

This function attempts to match chromosome, start position, end position and strand names in the given character vector. Modified helper from the GenomicRanges package.

Usage

```
findGRangesCols(
  df_colnames,
  seqnames.field = c("seqnames", "seqname", "chromosome", "chrom", "chr",
    "chromosome_name", "seqid", "om"),
  start.field = "start",
  end.field = c("end", "stop"),
  strand.field = "strand",
  ignore.strand = FALSE
)
```

Arguments

df_colnames	A character vector of names in a dataset
seqnames.field	A character vector of the chromosome name
start.field	A character vector that indicates the column name of the start positions of ranged data
end.field	A character vector that indicates the end position of ranged data
strand.field	A character vector of the column name that indicates the strand type
ignore.strand	logical (default FALSE) whether to ignore the strand field in the data

Value

Index positions vector indicating columns with appropriate names

Examples

```
myDataColNames <- c("Start_position", "End_position", "strand",
  "chromosome", "num_probes", "segment_mean")
findGRangesCols(myDataColNames)
```

generateMap	<i>Create a sampleMap from an experiment list and phenoData dataframe</i>
-------------	---

Description

This function helps create a sampleMap in preparation of a MultiAssayExperiment object. This is especially useful when the sample identifiers are not very different, as in the case of TCGA barcodes. An idConverter function can be provided to truncate such sample identifiers and obtain patient identifiers.

Usage

```
generateMap(  
  experiments,  
  colData,  
  idConverter = identity,  
  sampleCol,  
  patientCol,  
  ...  
)
```

Arguments

experiments	A named list of experiments compatible with the MultiAssayExperiment API
colData	A data.frame of clinical data with patient identifiers as rownames
idConverter	A function to be used against the sample or specimen identifiers to match those in the rownames of the colData (default NULL)
sampleCol	A single string indicating the sample identifiers column in the colData dataset
patientCol	A single string indicating the patient identifiers in colData, "row.names" extracts the colData row names
...	Additonal arguments to pass to the 'idConverter' function.

Value

A DataFrame class object of mapped samples and patient identifiers including assays

Author(s)

M. Ramos, M. Morgan, L. Schiffer

Examples

```
## Minimal example
expList <- list(assay1 = matrix(1:6, ncol = 2L,
  dimnames = list(paste0("feature", 1:3), c("A-J", "B-J"))),
  assay2 = matrix(1:4, ncol = 2,
    dimnames = list(paste0("gene", 1:2), c("A-L", "B-L"))))

## Mock colData
myPheno <- data.frame(var1 = c("Yes", "No"), var2 = c("High", "Low"),
  row.names = c("a", "b"))

## A look at the identifiers
vapply(expList, colnames, character(2L))
rownames(myPheno)

## Use 'idConverter' to correspond sample names to patient identifiers
generateMap(expList, myPheno,
  idConverter = function(x) substr(tolower(x), 1L, 1L))
```

getFileName

Find the file names used in RTCGAToolbox

Description

Part of this function is from the RTCGAToolbox. It aims to extract the file name used inside of the [getFirehoseData](#) function. The arguments of the function parallel those in the [getFirehoseData](#) function. It is only available for select data types.

Usage

```
getFileName(
  disease,
  runDate = "20160128",
  dataType = c("CNASNP", "CNVSNP", "CNaseq", "CNACGH", "Mutation")
)
```

Arguments

disease	The TCGA cancer disease code, e.g., "COAD"
runDate	The single string used in the getFirehoseData function (default "20160128")
dataType	A single character vector (default "CNASNP") indicating the data type for which to get the source file name

Value

A single character file name

Examples

```
getFileName("COAD", dataType = "CNASNP")
```

hidden-helpers

*Helper functions to get genomic ranges from different identifiers***Description**

Helper functions to get genomic ranges from different identifiers

Usage

```
.makeListRanges(x, gn)

.makeMiRNAListRanges(x, gn)

.getRangesOfMir(x)

.getRangesOfSYMBOLS(x)

.getRangesOfCpG(x)
```

Arguments

x	character() vector of either micro RNA identifiers (.getRangesOfMir) or gene symbols (.getRangesOfSYMBOLS) or CpG probe identifiers (.getRangesOfCpG)
gn	GRanges() with some of its names found in x or translated x

Value

list of length 2: "unmapped" character() symbols, "mapped" is a GRanges() object with ranges of mapped symbols

ID-translation

*Translate study identifiers from barcode to UUID and vice versa***Description**

These functions allow the user to enter a character vector of identifiers and use the GDC API to translate from TCGA barcodes to Universally Unique Identifiers (UUID) and vice versa. These relationships are not one-to-one. Therefore, a data.frame is returned for all inputs. The UUID to TCGA barcode translation only applies to file and case UUIDs. Two-way UUID translation is available from 'file_id' to 'case_id' and vice versa. Please double check any results before using these features for analysis. Case / submitter identifiers are translated by default, see the from_type argument for details. All identifiers are converted to lower case.

Usage

```
UUIDtoBarcode(id_vector, from_type = c("case_id", "file_id", "aliquot_ids"))
```

```
UUIDtoUUID(id_vector, to_type = c("case_id", "file_id"))
```

```
barcodeToUUID(barcodes)
```

```
filenameToBarcode(filenamees, slides)
```

```
UUIDhistory(id, endpoint = .HISTORY_ENDPOINT)
```

Arguments

<code>id_vector</code>	character() A vector of UUIDs corresponding to either files or cases (default assumes <code>case_ids</code>)
<code>from_type</code>	character(1) Either <code>case_id</code> or <code>file_id</code> indicating the type of <code>id_vector</code> entered (default <code>"case_id"</code>)
<code>to_type</code>	character(1) The desired UUID type to obtain, can either be <code>"case_id"</code> (default) or <code>"file_id"</code>
<code>barcodes</code>	character() A vector of TCGA barcodes
<code>filenamees</code>	character() A vector of file names usually obtained from a GenomicDataCommons query
<code>slides</code>	logical(1L) DEFUNCT : No longer used. See details.
<code>id</code>	character(1) A UUID whose history of versions is sought
<code>endpoint</code>	character(1) Generally a constant pertaining to the location of the history api endpoint. This argument rarely needs to change.

Details

Based on the file UUID supplied, the appropriate `entity_id` (TCGA barcode) is returned. In previous versions of the package, the `'end_point'` parameter would require the user to specify what type of barcode needed. This is no longer supported as `entity_id` returns the appropriate one.

Slides are identified by the `filenamees` input by searching for the `.svs` extension. Slide queries can only be done when **all** `filenamees` inputs are slide file names.

Value

Generally, a `data.frame` of identifier mappings

`UUIDhistory`: A `data.frame` containing a list of associated UUIDs for the given input along with `file_change` status, `data_release` versions, etc.

Author(s)

Sean Davis, M. Ramos

Examples

```
## Translate UUIDs >> TCGA Barcode

uuids <- c("b4bce3ff-7fdc-4849-880b-56f2b348ceac",
"5ca9fa79-53bc-4e91-82cd-5715038ee23e",
"b7c3e5ad-4ffc-4fc4-acbf-1dfcbd2e5382")

UUIDtoBarcode(uuids, from_type = "file_id")

UUIDtoBarcode("ae55b2d3-62a1-419e-9f9a-5ddfacc356db4", from_type = "case_id")

UUIDtoBarcode("d85d8a17-8aea-49d3-8a03-8f13141c163b", "aliquot_ids")

## Translate file UUIDs >> case UUIDs

uuids <- c("b4bce3ff-7fdc-4849-880b-56f2b348ceac",
"5ca9fa79-53bc-4e91-82cd-5715038ee23e",
"b7c3e5ad-4ffc-4fc4-acbf-1dfcbd2e5382")

UUIDtoUUID(uuids)

## Translate TCGA Barcode >> UUIDs

fullBarcodes <- c("TCGA-B0-5117-11A-01D-1421-08",
"TCGA-B0-5094-11A-01D-1421-08",
"TCGA-E9-A295-10A-01D-A16D-09")

sample_ids <- TCGAbarcode(fullBarcodes, sample = TRUE)

barcodeToUUID(sample_ids)

participant_ids <- c("TCGA-CK-4948", "TCGA-D1-A17N",
"TCGA-4V-A9QX", "TCGA-4V-A9QM")

barcodeToUUID(participant_ids)

library(GenomicDataCommons)

### Query CNV data and get file names

cnv <- files() |>
  filter(
    ~ cases.project.project_id == "TCGA-COAD" &
    data_category == "Copy Number Variation" &
    data_type == "Copy Number Segment"
  ) |>
  results(size = 6)

filenameToBarcode(cnv$file_name)

### Query slides data and get file names
```

```

slides <- files() |>
  filter(
    ~ cases.project.project_id == "TCGA-BRCA" &
      cases.samples.sample_type == "Primary Tumor" &
      data_type == "Slide Image" &
      experimental_strategy == "Diagnostic Slide"
  ) |>
  results(size = 3)

filenameToBarcode(slides$file_name)

## Get the version history of a BAM file in TCGA-KIRC
UUIDhistory("0001801b-54b0-4551-8d7a-d66fb59429bf")

```

imputeAssay	<i>This function imputes assays values inside a MultiAssayExperiment</i>
-------------	--

Description

These function allow the user to enter a MultiAssayExperiment and impute all the NA values inside assays.

Usage

```
imputeAssay(multiassayexperiment, i = 1, ...)
```

Arguments

multiassayexperiment	A MultiAssayExperiment with genes in the rows, samples in the columns
i	A numeric, logical, or character vector indicating the assays to perform imputation on (default 1L)
...	Arguments passed on to <code>impute::impute.knn</code>
data	An expression matrix with genes in the rows, samples in the columns
k	Number of neighbors to be used in the imputation (default=10)
rowmax	The maximum percent missing data allowed in any row (default 50%). For any rows with more than rowmax% missing are imputed using the over-all mean per sample.
colmax	The maximum percent missing data allowed in any column (default 80%). If any column has more than colmax% missing data, the program halts and reports an error.
maxp	The largest block of genes imputed using the knn algorithm inside <code>impute.knn</code> (default 1500); larger blocks are divided by two-means clustering (recursively) prior to imputation. If maxp=p, only knn imputation is done.
rng.seed	The seed used for the random number generator (default 362436069) for reproducibility.

Value

A MultiAssayExperiment with imputed assays values

Examples

```
example(getSubtypeMap)

## convert data to matrix and add as experiment
gbm <-
  c(gbm, RPPA_matrix = data.matrix(assay(gbm[["GBM_RPPAArray-20160128"]]))))

imputeAssay(gbm, i = "RPPA_matrix")
```

makeGRangesListFromCopyNumber

Make a GRangesList from TCGA Copy Number data

Description

makeGRangesListFromCopyNumber allows the user to convert objects of class data.frame or [S4Vectors::DataFrame](#) to a [GRangesList](#). It includes additional features specific to TCGA data such as, hugo symbols, probe numbers, segment means, and ucsc build (if available).

Usage

```
makeGRangesListFromCopyNumber(
  df,
  split.field,
  names.field = "Hugo_Symbol",
  ...
)
```

Arguments

df	A data.frame or DataFrame class object. list class objects are coerced to data.frame or DataFrame.
split.field	A character vector of length one indicating the column to be used as sample identifiers
names.field	A character vector of length one indicating the column to be used as names for each of the ranges in the data
...	Additional arguments to pass on to GenomicRanges::makeGRangesListFromDataFrame

Value

A [GRangesList](#) class object

Examples

```
library(GenomicDataCommons)

manif <- files() |>
  filter(~ cases.project.project_id == "TCGA-COAD" &
    data_type == "Copy Number Segment") |>
  manifest(size = 1)

fname <- gdcdata(manif$id)

UUIDtoBarcode(names(fname), from_type = "file_id")

cndata <- read.delim(fname[[1L]])

makeGRangesListFromCopyNumber(
  df = cndata,
  split.field = "GDC_Aliquot",
  keep.extra.columns = TRUE
)
```

```
makeGRangesListFromExonFiles
```

Read exon-level expression files and create a GRangesList

Description

This function serves to read exon-level expression data. It works for exon quantification (raw counts and RPKM) and junction quantification (raw counts) file paths and represents such data as a [GRangesList](#). The data files can be downloaded via the Genomic Data Commons (GDC) Legacy Archive.

Usage

```
makeGRangesListFromExonFiles(
  filepaths,
  sampleNames = NULL,
  fileNames = basename(filepaths),
  getBarcodes = TRUE,
  rangesColumn = "exon",
  nrows = Inf
)
```

Arguments

filepaths	character() vector of file paths containing TCGA exon data usually obtained from the GDC
sampleNames	character() vector of TCGA barcodes to be used as names for the GRangesList output (default NULL)

fileNames	character() vector of file names as downloaded from the Genomic Data Commons Legacy archive (default <code>basename(filepaths)</code>)
getBarcodes	logical(1). Whether to query the GDC API with the <code>filenameToBarcode</code> and obtain the TCGA barcodes from the file names (default <code>TRUE</code>); see details.
rangesColumn	character(1). The name of the column in the data containing the ranges information (default <code>"exon"</code>); see details.
nrows	numeric(1). The number of rows to return from each of the files read in (all rows by default; default <code>Inf</code>)

Details

The `rangesColumn` name in the GDC data files is usually `"exon"` but can be changed with the `rangesColumn` argument, if different. To avoid programmatically obtaining TCGA barcodes from the GDC API, set the `getBarcodes` to `FALSE`. When `getBarcodes` is set to `FALSE`, the file names are used to name the elements of the `GRangesList` output.

Value

A [GRangesList](#) object

Author(s)

M. Ramos

Examples

```
## Load example file found in package
pkgDir <- system.file("extdata", package = "TCGAutils", mustWork = TRUE)
exonFile <- list.files(pkgDir, pattern = "cation\\.txt$", full.names = TRUE)

filePrefix <- "unc.edu.32741f9a-9fec-441f-96b4-e504e62c5362.1755371."

## Add actual file name manually (due to Windows OS restriction)
makeGRangesListFromExonFiles(exonFile,
  fileNames = paste0(filePrefix, basename(exonFile)),
  sampleNames = "TCGA-AA-3678-01A-01R-0905-07")
```

mergeColData

Take a MultiAssayExperiment and include curated variables

Description

This function works on the `colData` of a [MultiAssayExperiment](#) object to merge curated variable columns or other clinical variables that would like to be added. It is recommended that the user run the scripts in the `MultiAssayExperiment.TCGA` repository that build the "enhanced" type of data but not necessary if using different clinical data. Please see the repository's README for more information.

Usage

```
mergeColData(MultiAssayExperiment, colData)
```

Arguments

`MultiAssayExperiment`
A `MultiAssayExperiment` object

`colData`
A `DataFrame` or `data.frame` to merge with clinical data in the `MultiAssayExperiment` object

Value

A `MultiAssayExperiment` object

Examples

```
library(MultiAssayExperiment)

mergeColData(MultiAssayExperiment(), S4Vectors::DataFrame())
```

oncoPrintTCGA

OncoPrint for TCGA Mutation Assays

Description

OncoPrint for TCGA Mutation Assays

Usage

```
oncoPrintTCGA(
  multiassayexperiment,
  matchassay = "*_Mutation-*",
  variantCol = "Variant_Classification",
  brewerPal = "Set3",
  ntop = 25,
  incl.thresh = 0.01,
  rowcol = "Hugo_Symbol"
)
```

Arguments

`multiassayexperiment`
A `MultiAssayExperiment`, usually from `curatedTCGAData`

`matchassay`
`character(1)` The name of the assay containing mutation data, this can be a pattern (e.g., `"_Mutation-"`, the default)

variantCol	character(1) The name of the metadata column containing the mutation categories, usually "Variant_Classification" in TCGA
brewerPal	character(1) The name of the RColorBrewer::brewer.pal palette, (default: "Set3")
ntop	integer(1) The number of the top N genes for displaying based on per-sample mutation frequency
incl.thresh	double(1) The inclusion threshold for empirical mutations, mutations less frequent than this value will not be included
rowcol	character(1) The name of the column in the metadata to annotate the rows with either "Hugo_Symbol" (default) or

Value

An oncoPrint plot of mutations

Examples

```
library(curatedTCGAData)

acc <- curatedTCGAData("ACC", "Mutation", version = "1.1.38", FALSE)

oncoPrintTCGA(acc)
```

sampleTypes	<i>Barcode Sample Type Table</i>
-------------	----------------------------------

Description

A dataset that contains the mappings for sample codes in the TCGA barcodes.

Usage

```
data("sampleTypes")
```

Format

A data frame with 19 rows and 3 variables:

- Code: Two digit code number found in the barcode
- Definition: Long name for the sample type
- Short.Letter.Code: Letter code for the sample type

Value

The TCGA sampleTypes table

Source

<https://gdc.cancer.gov/resources-tcga-users/tcga-code-tables/sample-type-codes>

simplifyTCGA	<i>Functions to convert rows annotations to ranges and RaggedExperiment to RangedSummarizedExperiment</i>
--------------	---

Description

This group of functions will convert row annotations as either gene symbols or miRNA symbols to row ranges based on database resources 'TxDB' and 'org.Hs' packages. It will also simplify the representation of [RaggedExperiment](#) objects to [RangedSummarizedExperiment](#).

Usage

```
simplifyTCGA(obj, keep.assay = FALSE, unmapped = TRUE)

symbolsToRanges(obj, keep.assay = FALSE, unmapped = TRUE)

mirToRanges(obj, keep.assay = FALSE, unmapped = TRUE)

CpGtoRanges(obj, keep.assay = FALSE, unmapped = TRUE)

qreduceTCGA(obj, keep.assay = FALSE, suffix = "_simplified")
```

Arguments

obj	A MultiAssayExperiment object obtained from curatedTCGAData
keep.assay	logical (default FALSE) Whether to keep the SummarizedExperiment assays that have been converted to RangedSummarizedExperiment
unmapped	logical (default TRUE) Include an assay of data that was not able to be mapped in reference database
suffix	character (default "_simplified") A character string to append to the newly modified assay for qreduceTCGA.

Details

The original SummarizedExperiment containing either gene symbol or miR annotations is replaced or supplemented by a [RangedSummarizedExperiment](#) for those that could be mapped to [GRanges](#), and optionally another [SummarizedExperiment](#) for annotations that could not be mapped to [GRanges](#).

Value

A [MultiAssayExperiment](#) with any gene expression, miRNA, copy number, and mutations converted to [RangedSummarizedExperiment](#) objects

qreduceTCGA

Using TxDb.Hsapiens.UCSC.hg19.knownGene as the reference, qreduceTCGA reduces the data by applying either the weightedmean or nonsilent function (see below) to non-mutation or mutation data, respectively. Internally, it uses `RaggedExperiment::qreduceAssay()` to reduce the ranges to the gene-level.

qreduceTCGA will update genome(x) based on the NCBI reference annotation which includes the patch number, e.g., GRCh37.p14, as provided by the seqlevelsStyle setter, seqlevelsStyle(gn) <- "NCBI". qreduceTCGA uses the NCBI genome annotation as the default reference.

```
nonsilent <- function(scores, ranges, qranges)
  any(scores != "Silent")
```

RaggedExperiment mutation objects become a genes by patients RangedSummarizedExperiment object containing '1' if there is a non-silent mutation somewhere in the gene, and '0' otherwise as obtained from the Variant_Classification column in the data.

```
weightedmean <- function(scores, ranges, qranges) {
  isects <- GenomicRanges::pintersect(ranges, qranges)
  sum(scores * BiocGenerics::width(isects)) /
    sum(BiocGenerics::width(isects))
}
```

"CNA" and "CNV" segmented copy number are reduced using a weighted mean in the rare cases of overlapping (non-disjoint) copy number regions.

These functions rely on TxDb.Hsapiens.UCSC.hg19.knownGene and org.Hs.eg.db to map to the 'hg19' NCBI build. Use the liftOver procedure for datasets that are provided against a different reference genome (usually 'hg18'). See an example in the vignette.

Author(s)

L. Waldron, M. Ramos

Examples

```
library(curatedTCGAData)
library(GenomeInfoDb)

accmae <- curatedTCGAData(
  diseaseCode = "ACC",
  assays = c("CNASNP", "Mutation", "miRNASeqGene", "GISTICT"),
  version = "1.1.38",
  dry.run = FALSE
)

## update genome annotation
rex <- accmae[["ACC_Mutation-20160128"]]

## Translate build to "hg19"
tgenome <- vapply(genome(rex), translateBuild, character(1L))
```

```
genome(rex) <- tgenome

accmae[["ACC_Mutation-20160128"]] <- rex

simplifyTCGA(accmae)
```

TCGAbarcode

Parse data from TCGA barcode

Description

This function returns the specified snippet of information obtained from the TCGA barcode.

Usage

```
TCGAbarcode(
  barcodes,
  participant = TRUE,
  sample = FALSE,
  portion = FALSE,
  plate = FALSE,
  center = FALSE,
  index = NULL
)
```

Arguments

<code>barcodes</code>	A character vector of TCGA barcodes
<code>participant</code>	Logical (default TRUE) participant identifier chunk
<code>sample</code>	Logical (default FALSE) includes the numeric sample code of the barcode and the vial letter
<code>portion</code>	Logical (default FALSE) includes the portion and analyte codes of the barcode
<code>plate</code>	Logical (default FALSE) returns the plate value
<code>center</code>	Logical (default FALSE) returns a matrix with the plate and center codes
<code>index</code>	An optional numeric vector indicating barcode positions when split by the delimiter (i.e., hyphen '-'). For example, an index of <code>c(1, 2)</code> corresponds to 'TCGA-ZZ' in TCGA-ZZ-A1A1.

Value

A character vector or data matrix of TCGA barcode information

Author(s)

M. Ramos

Examples

```
barcodes <- c("TCGA-B0-5117-11A-01D-1421-08",  
              "TCGA-B0-5094-11A-01D-1421-08",  
              "TCGA-E9-A295-10A-01D-A16D-09")  
  
## Patient identifiers  
TCGAbarcode(barcodes)  
  
## Sample identifiers  
TCGAbarcode(barcodes, sample = TRUE)
```

TCGAbiospec

Extract biospecimen data from the TCGA barcode

Description

This function uses the full TCGA barcode to return a data frame of the data pertinent to laboratory variables such as vials, portions, analytes, plates and the center.

Usage

```
TCGAbiospec(barcodes)
```

Arguments

barcodes A character vector of TCGA barcodes

Value

A dataframe with sample type, sample code, portion, plate, and center columns.

Author(s)

M. Ramos

Examples

```
example("TCGAbarcode")  
TCGAbiospec(barcodes)
```

TCGAPrimaryTumors	Select primary tumors from TCGA datasets
-------------------	--

Description

Tumor selection is decided using the sampleTypes data. For 'LAML' datasets, the primary tumor code used is "03" otherwise, "01" is used.

Usage

TCGAPrimaryTumors(multiassayexperiment)

Arguments

multiassayexperiment
A [MultiAssayExperiment](#) with TCGA data as obtained from [curatedTCGAData::curatedTCGAData\(\)](#)

Value

A MultiAssayExperiment containing only primary tumor samples

Examples

example(getSubtypeMap)

TCGAPrimaryTumors(gbm)

TCGAsampleSelect	Select samples from barcodes from lookup table
------------------	--

Description

The TCGA barcode contains several pieces of information which can be parsed by the [TCGABarcode](#) function. To select a specific type of sample, enter the appropriate sampleCode argument from the lookup table. See lookup table in data("sampleTypes"). Barcode inputs can be a character vector or a [CharacterList](#) object.

Usage

TCGAsampleSelect(barcodes, sampleCodes)

Arguments

barcodes	Either a TCGA barcode vector or CharacterList containing patient identifiers, sample, portion, plate, and center codes.
sampleCodes	Either a character or numeric vector of TCGA sample codes. See the sampleType dataset.

Value

A logical vector or [LogicalList](#) of the same length as 'barcodes' indicating sample type matches

Examples

```
example("TCGAbarcode")
TCGAsampleSelect(barcodes, c(11, 01))
```

trimColData	<i>Minimize the number of variables in colData</i>
-------------	--

Description

This function removes variables that have a high number of missing data and contain keywords.

Usage

```
trimColData(
  multiassayexperiment,
  maxNAfrac = 0.2,
  keystring = c("portion", "analyte")
)
```

Arguments

multiassayexperiment	A MultiAssayExperiment object with colData
maxNAfrac	(numeric default 0.2) A decimal between 0 and 1 to indicate the amount of NA values allowed per column
keystring	(character) A vector of keywords to match and remove variables

Value

A [MultiAssayExperiment](#) object

Examples

```
example(getSubtypeMap)

(gbm_trimmed <- trimColData(gbm))

head(colData(gbm_trimmed))[1:5]
```

Index

- * **datasets**
 - clinicalNames, [5](#)
 - diseaseCodes, [7](#)
 - sampleTypes, [19](#)
- * **internal**
 - hidden-helpers, [11](#)
 - .getRangesOfCpG (hidden-helpers), [11](#)
 - .getRangesOfMir (hidden-helpers), [11](#)
 - .getRangesOfSYMBOLS (hidden-helpers), [11](#)
 - .makeListRanges (hidden-helpers), [11](#)
 - .makeMiRNAListRanges (hidden-helpers), [11](#)
- barcodeToUUID (ID-translation), [11](#)
- builds, [3](#)
- CharacterList, [5](#), [24](#)
- clinicalNames, [5](#)
- correctBuild (builds), [3](#)
- CpGtoRanges (simplifyTCGA), [20](#)
- curatedTCGAData-helpers, [6](#)
- curatedTCGAData::curatedTCGAData(), [24](#)
- diseaseCodes, [7](#)
- extractBuild (builds), [3](#)
- filenameToBarcode (ID-translation), [11](#)
- findGRangesCols, [8](#)
- generateMap, [9](#)
- GenomicRanges::makeGRangesListFromDataFrame, [15](#)
- getClinicalNames
 - (curatedTCGAData-helpers), [6](#)
- getFileName, [10](#)
- getFirehoseData, [5](#), [7](#), [10](#)
- getSubtypeMap
 - (curatedTCGAData-helpers), [6](#)
- GRanges, [20](#)
- GRangesList, [3](#), [15–17](#)
- hidden-helpers, [11](#)
- ID-translation, [11](#)
- impute::impute.knn, [14](#)
- imputeAssay, [14](#)
- isCorrect (builds), [3](#)
- LogicalList, [25](#)
- makeGRangesListFromCopyNumber, [15](#)
- makeGRangesListFromExonFiles, [16](#)
- mergeColData, [17](#)
- mirToRanges (simplifyTCGA), [20](#)
- MultiAssayExperiment, [3](#), [6](#), [17](#), [18](#), [20](#), [24](#), [25](#)
- oncoPrintTCGA, [18](#)
- qreduceTCGA (simplifyTCGA), [20](#)
- RaggedExperiment, [20](#)
- RaggedExperiment::qreduceAssay(), [21](#)
- RangedSummarizedExperiment, [20](#)
- S4Vectors::DataFrame, [15](#)
- sampleTables (curatedTCGAData-helpers), [6](#)
- sampleTypes, [19](#)
- simplifyTCGA, [20](#)
- SummarizedExperiment, [3](#), [20](#)
- symbolsToRanges (simplifyTCGA), [20](#)
- TCGAbarcodes, [22](#), [24](#)
- TCGAbiospec, [23](#)
- TCGAprimaryTumors, [24](#)
- TCGAsampleSelect, [24](#)
- TCGAsplitAssays
 - (curatedTCGAData-helpers), [6](#)
- TCGAutils (TCGAutils-package), [3](#)
- TCGAutils-package, [3](#)
- translateBuild (builds), [3](#)

trimColData, [25](#)

uniformBuilds (builds), [3](#)

UUIDhistory (ID-translation), [11](#)

UUIDtoBarcode (ID-translation), [11](#)

UUIDtoUUID (ID-translation), [11](#)