

Package ‘geyser’

September 24, 2026

Title Gene Expression displaYer of SummarizedExperiment in R

Version 1.4.0

Description Lightweight Expression displaYer (plotter / viewer) of SummarizedExperiment object in R. This package provides a quick and easy Shiny-based GUI to empower a user to use a SummarizedExperiment object to view

License CC0

LazyData false

biocViews Software, ShinyApps, GUI, GeneExpression

Imports bslib (>= 0.6.0), BiocStyle, ComplexHeatmap, cowplot, dplyr, DT, ggbeeswarm, ggplot2, ggrepel, ggh4x, htmltools, magrittr, pals, RColorBrewer, rlang, R.utils, shiny, shinyjs, S4Vectors, SummarizedExperiment, tibble, tidyselect, tidyr, yaml

Suggests airway, knitr, DESeq2, rmarkdown, stringr, testthat (>= 3.0.0)

Config/testthat/edition 3

VignetteBuilder knitr

Encoding UTF-8

URL <https://github.com/davemcg/geyser>

BugReports <https://github.com/davemcg/geyser/issues>

RoxygenNote 7.3.2

git_url <https://git.bioconductor.org/packages/geyser>

git_branch RELEASE_3_23

git_last_commit 1188907

git_last_commit_date 2026-04-28

Repository Bioconductor 3.23

Date/Publication 2026-09-23

Author David McGaughey [aut, cre] (ORCID:
<<https://orcid.org/0000-0002-9224-2888>>)

Maintainer David McGaughey <mcgaughey@gmail.com>

Contents

.exp_plot	2
.hm_plot	3
apply_config	4
apply_embedded_config	4
apply_pending_group_filters	5
apply_pending_sample_filter	5
create_config_download_handler	6
extract_config_from_metadata	6
geyser	7
setup_config_preset_observer	8
setup_config_upload_observer	8
Index	9

.exp_plot	<i>exp_plot</i>
-----------	-----------------

Description

draws the expression box plot

Usage

.exp_plot(input, rse, data_source_name)

Arguments

- | | |
|------------------|--|
| input | From ui.R |
| rse | The rse object |
| data_source_name | The name of the loaded dataset for the caption |

Details

Makes the box plot for the geyser Shiny app

Value

Returns a list with the \$plot slot holding ggplot object and \$grouping_length contains the number of features to scale the plot

Author(s)

David McGaughey

Examples

```
load(system.file('extdata/tiny_rse.Rdata', package = 'geyser'))
input <- list()
input$feature_col <- "row names"
input$features <- c("TYRP1 (ENSG00000107165.12)", "OPN1LW (ENSG00000102076.9)")
input$groupings <- c('disease')
input$slot <- 'counts'
input$expression_scale <- TRUE
input$color_by <- 'tissue'
input$color_palette <- 'polychrome'
input$show_points <- TRUE
geyser:::exp_plot(input, tiny_rse, "tiny_rse.Rdata")$plot
```

*.hm_plot**hm_plot***Description**

draws the expression heatmap

Usage

```
.hm_plot(input, rse, data_source_name)
```

Arguments

<code>input</code>	From ui.R
<code>rse</code>	rse object
<code>data_source_name</code>	The name of the loaded dataset for the caption

Details

Makes the heatmap for the geyser Shiny app

Value

Returns a ComplexHeatmap object

Author(s)

David McGaughey

Examples

```
load(system.file('extdata/tiny_rse.Rdata', package = 'geyser'))
input <- list()
input$feature_col <- 'row names'
input$features <- c("TYRP1 (ENSG00000107165.12)", "OPN1LW (ENSG00000102076.9)")
input$groupings <- c('disease')
input$slot <- 'counts'
input$expression_scale <- TRUE
input$row_clust <- TRUE
input$col_clust <- TRUE
geyser:::hm_plot(input, tiny_rse, "tiny_rse.Rdata")$plot
```

apply_config	Configuration Helper Functions for Geyser
--------------	---

Description

Functions to handle loading, saving, and applying configurations
Apply a configuration to the Shiny session

Usage

```
apply_config(config, session, rv)
```

Arguments

config	List containing configuration parameters
session	Shiny session object
rv	reactiveValues object containing app state

apply_embedded_config	Apply embedded config from SummarizedExperiment if present
-----------------------	--

Description

Apply embedded config from SummarizedExperiment if present

Usage

```
apply_embedded_config(rse, session, rv)
```

Arguments

rse	SummarizedExperiment object
session	Shiny session object
rv	reactiveValues object

apply_pending_group_filters
Apply pending group filters to dynamic UI

Description

Apply pending group filters to dynamic UI

Usage

```
apply_pending_group_filters(rv, input, session)
```

Arguments

rv	reactiveValues object
input	Shiny input object
session	Shiny session object

apply_pending_sample_filter
Apply pending sample filter to table

Description

Apply pending sample filter to table

Usage

```
apply_pending_sample_filter(rv, input)
```

Arguments

rv	reactiveValues object
input	Shiny input object

```
create_config_download_handler
```

Create configuration download handler

Description

Create configuration download handler

Usage

```
create_config_download_handler(input)
```

Arguments

input	Shiny input object
-------	--------------------

```
extract_config_from_metadata
```

Extract geyser config from SummarizedExperiment metadata

Description

Extract geyser config from SummarizedExperiment metadata

Usage

```
extract_config_from_metadata(rse)
```

Arguments

rse	SummarizedExperiment object
-----	-----------------------------

Value

List containing config or NULL if not found

geyser

geyser

Description

Run shiny app to use SummarizedExperiment object to display genomics data

Usage

```
geyser(  
  rse = NULL,  
  app_name = "geyser",  
  primary_color = "#3A5836",  
  secondary_color = "#d5673e",  
  computer_data_dir = NULL  
)
```

Arguments

<code>rse</code>	SummarizedExperiment object. If NULL (the default), the app will start with a file upload screen.
<code>app_name</code>	Title name that goes on the top left of the Shiny app
<code>primary_color</code>	The title bar color
<code>secondary_color</code>	The plot action button color
<code>computer_data_dir</code>	Optional folder path to existing SummarizedExperiment RDS files.

Value

A Shiny app object

Examples

```
if (interactive()) {  
  load(system.file('extdata/tiny_rse.Rdata', package = 'geyser'))  
  geyser(tiny_rse, "Test RSE")  
}
```

setup_config_preset_observer
<i>Setup configuration preset observer</i>

Description

Setup configuration preset observer

Usage

setup_config_preset_observer(input, session, rv)

Arguments

input	Shiny input object
session	Shiny session object
rv	reactiveValues object

setup_config_upload_observer
<i>Setup configuration upload observer</i>

Description

Setup configuration upload observer

Usage

setup_config_upload_observer(input, session, rv)

Arguments

input	Shiny input object
session	Shiny session object
rv	reactiveValues object

Index

* **internal**

.exp_plot, [2](#)

.hm_plot, [3](#)

.exp_plot, [2](#)

.hm_plot, [3](#)

apply_config, [4](#)

apply_embedded_config, [4](#)

apply_pending_group_filters, [5](#)

apply_pending_sample_filter, [5](#)

create_config_download_handler, [6](#)

extract_config_from_metadata, [6](#)

geyser, [7](#)

setup_config_preset_observer, [8](#)

setup_config_upload_observer, [8](#)