

Package ‘rhdf5client’

September 23, 2026

Title Access HDF5 content from HDF Scalable Data Service

Description This package provides functionality for reading data from HDF Scalable Data Service from within R. The HSDSArray function bridges from HSDS to the user via the DelayedArray interface. Bioconductor manages an open HSDS instance graciously provided by John Readey of the HDF Group.

Version 1.34.2

Suggests knitr, testthat, BiocStyle, DT, rmarkdown

Imports httr, rjson, utils, data.table

Depends R (>= 3.6), methods, DelayedArray

License Artistic-2.0

LazyLoad yes

Collate URL_hds.R indx.R 'rhdf5client2.R' 'Source.R' 'File.R'
'Dataset.R' 'RHDF5Array.R'

VignetteBuilder knitr

Encoding UTF-8

biocViews DataImport, Software, Infrastructure

RoxygenNote 7.3.3

git_url <https://git.bioconductor.org/packages/rhdf5client>

git_branch RELEASE_3_23

git_last_commit 0ed5c74

git_last_commit_date 2026-06-01

Repository Bioconductor 3.23

Date/Publication 2026-09-22

Author Samuela Pollack [aut],
Shweta Gopaulakrishnan [aut],
BJ Stubbs [aut],
Alexey Sergushichev [aut, cre],
Vincent Carey [aut]

Maintainer Alexey Sergushichev <alsergbox@gmail.com>

Contents

as	2
check_hsd	3
dim	3
dimnames	4
extractCompoundJSON	4
extract_array	5
getData	5
getHSDSFileList	6
HSDSArray	7
HSDSArraySeed	8
HSDSDataset	8
HSDSDataset-class	9
HSDSFile	9
HSDSFile-class	10
HSDSMatrix	10
HSDSSource	11
HSDSSource-class	11
isplit	12
listDatasets	12
listDomains	13
rhdf5client	14
rhdf5client-deprecated	14
URL_hsd	15
[,HSDSDataset,numeric,ANY,ANY-method	16
[,HSDSDataset,numeric,numeric,ANY-method	16
Index	18

as

Coercion method from HSDSMatrix to its superclass HSDSArray

Description

Coercion method from HSDSMatrix to its superclass HSDSArray

See Also

Other HSDSArray: [HSDSArray](#), [HSDSMatrix](#)

check_hsd	<i>a test request</i>
-----------	-----------------------

Description

a test request

Usage

```
check_hsd()
```

Value

logical, TRUE if hsd behaving as expected

Examples

```
check_hsd()
```

dim	<i>Obtain dimensions of an object of type HSDSArraySeed</i>
-----	---

Description

(required by DelayedArray seed contract) HDF server content is assumed transposed relative to R matrix layout. This anticipates H5 datasets on the server with rows for experimental samples and columns for *-omic features. The Bioconductor SummarizedExperiment requires *-omic features in rows and samples in columns.

Usage

```
## S4 method for signature 'HSDSArraySeed'  
dim(x)
```

Arguments

x	An object of type HSDSArraySeed
---	---------------------------------

Value

A numeric vector of the dimensions

dimnames	<i>Obtain names of dimensions for an object of type HSDSArraySeed</i>
----------	---

Description

(required by DelayedArray seed contract, returns NULL list)

Usage

```
## S4 method for signature 'HSDSArraySeed'  
dimnames(x)
```

Arguments

x An object of type HSDSArraySeed

Value

A NULL list of length equal to the array dimensionality

extractCompoundJSON	<i>compound operation</i>
---------------------	---------------------------

Description

compound operation

Usage

```
extractCompoundJSON(type, value)
```

Arguments

type	type
value	value

extract_array	<i>Access dataset backed by an HSDSArraySeed</i>
---------------	--

Description

Access dataset backed by an HSDSArraySeed

Usage

```
## S4 method for signature 'HSDSArraySeed'
extract_array(x, index)
```

Arguments

x	An object of type HSDSArraySeed
index	A list of numeric vectors to be accessed, one vector for each dimension of the array object. A NULL vector indicates the entire range of indices in that dimension. A zero-length vector indicates no indices in the relevant dimension. (Accordingly, any zero-length vector of indices will result in an empty array being returned.)

Value

An array containing the data elements corresponding to the indices requested

getData	<i>extract elements of a one or two-dimensional HSDSDataset</i>
---------	---

Description

Fetch data from a remote dataset

Usage

```
getData(dataset, indices, transfermode)

## S4 method for signature 'HSDSDataset,character,character'
getData(dataset, indices, transfermode)

## S4 method for signature 'HSDSDataset,character,missing'
getData(dataset, indices)

## S4 method for signature 'HSDSDataset,list,character'
getData(dataset, indices, transfermode)

## S4 method for signature 'HSDSDataset,list,missing'
getData(dataset, indices)
```

Arguments

dataset	An object of type HSDSDataset, the dataset to access.
indices	The indices of the data to fetch
transfermode	Either 'JSON' or 'binary' (default)

Details

The servers require data to be fetched in slices, i.e., in sets of for which the indices of each dimension are of the form start:stop:step. More complex sets of indices will be split into slices and fetched in multiple requests. This is opaque to the user, but may enter into considerations of data access patterns, e.g., for performance-tuning.

Value

an Array containing the data fetched from the server

Examples

```
if (check_hsd()) {
  s <- HSDSource(URL_hsd())
  f <- HSDFile(s, '/shared/bioconductor/patelGBMSC.h5')
  d <- HSDSDataset(f, '/assay001')
  x <- getData(d, c('1:4', '1:27998'), transfermode='JSON')
  xb <- getData(d, c('1:4', '1:27998'), transfermode='binary')
  # x <- getData(d, c(1:4, 1:27998), transfermode='JSON') # method missing?
  x
  xb
}
```

getHSDSFileList	<i>List files on a directory on HSDS-server</i>
-----------------	---

Description

This functions returns a list of all HDF5-files on the server or all files of the collection

Usage

```
getHSDSFileList(url, directory = NULL)
```

Arguments

url	containing url of the server and root domain.
directory	containing name of the directory

Value

List of all HDF5-files on the server or all files of the collection

Examples

```
if (check_hsd()) {
  url <- 'https://alserglab.wustl.edu/hsds/?domain=/counts'
  getHSDSFileList(url)
}
```

HSDSArray

*A DelayedArray backend for accessing a remote HDF5 server.***Description**

A DelayedArray backend for accessing a remote HDF5 server.

Construct an object of type HSDSArray directly from the data members of its seed

Usage

```
HSDSArray(endpoint, svrtype, domain, dsetname)
```

Arguments

endpoint	URL of remote server
svrtype	type of server, must be either 'hsds' or 'h5serv'
domain	HDF5 domain of H5 file on server
dsetname	complete internal path to dataset in H5 file

Value

An initialized object of type HSDSArray

See Also

Other HSDSArray: [HSDSMatrix](#), [as\(\)](#)

Examples

```
if (check_hsd()) {
  HSDSArray(URL_hsd(),
    "hsds", "/shared/bioconductor/patelGBMSC.h5", "/assay001")
}
```

HSDSArraySeed	<i>HSDSArraySeed for HSDSArray backend to DelayedArray</i>
---------------	--

Description

HSDSArraySeed for HSDSArray backend to DelayedArray
 Construct an object of type HSDSArraySeed

Usage

```
HSDSArraySeed(endpoint, svrtype, domain, dsetname)
```

Arguments

endpoint	URL of remote server
svrtype	type of server, must be either 'hsds' or 'h5serv'
domain	HDF5 domain of H5 file on server
dsetname	complete internal path to dataset in H5 file

Value

An initialized object of type HSDSArraySeed

Slots

endpoint	URL of remote server
svrtype	type of server, must be either 'hsds' or 'h5serv'
domain	HDF5 domain of H5 file on server
dsetname	complete internal path to dataset in H5 file
dataset	object of type HSDSDataset for access to the H5 dataset

HSDSDataset	<i>Construct an object of type HSDSDataset A HSDSDataset is a representation of a dataset in a HDF5 file.</i>
-------------	---

Description

Construct an object of type HSDSDataset A HSDSDataset is a representation of a dataset in a HDF5 file.

Usage

```
HSDSDataset(file, path)
```

Arguments

`file` An object of type `HSDSFile` which hosts the dataset
`path` The complete intrafile path to the dataset

Value

An initialized object of type `HSDSDataset`

Examples

```
if (check_hsd()) {
  src <- HSDSource(URL_hsd())
  f <- HSDSFile(src, '/shared/bioconductor/patelGBMSC.h5')
  d <- HSDSDataset(f, '/assay001')
}
```

<code>HSDSDataset-class</code>	<i>An S4 class to represent a dataset in a HDF5 file.</i>
--------------------------------	---

Description

An S4 class to represent a dataset in a HDF5 file.

Slots

`file` An object of type `HSDSFile`; the file in which the dataset is resident.
`path` The dataset's path in the internal HDF5 hierarchy.
`uuid` The unique unit ID by which the dataset is accessed in the server database system.
`shape` The dimensions of the dataset
`type` The dataset's HDF5 datatype

<code>HSDSFile</code>	<i>Construct an object of type <code>HSDSFile</code></i>
-----------------------	--

Description

A `HSDSFile` is a representation of an HDF5 file the contents of which are accessible exposed by a HDF5 server.

Usage

```
HSDSFile(src, domain)
```

Arguments

`src` an object of type `HSDSSource`, the server which exposes the file
`domain` the domain string; the file's location on the server's file system.

Details

This function is deprecated and will be defunct in the next release.

Value

an initialized object of type `HSDSFile`

Examples

```
if (check_hsd()) {
  src <- HSDSSource(URL_hsd())
  f10x <- HSDSFile(src, '/shared/bioconductor/patelGBMSC.h5')
}
```

<code>HSDSFile-class</code>	<i>An S4 class to represent an HDF5 file accessible from a server.</i>
-----------------------------	--

Description

An S4 class to represent an HDF5 file accessible from a server.

Slots

`HSDSSource` an object of type `HSDSSource`
`domain` the file's domain on the server; more or less, an alias for its location in the external server file system
`dsetdf` a data.frame that caches often-used information about the file
`type` string representing type of the file: "domain" for file and "folder" for directory

<code>HSDSMatrix</code>	<i>DelayedMatrix subclass for a two-dimensional HSDSArray</i>
-------------------------	---

Description

DelayedMatrix subclass for a two-dimensional HSDSArray

See Also

Other HSDSArray: [HSDSArray](#), [as\(\)](#)

HSDSSource	<i>Construct an object of type HSDSSource.</i>
------------	--

Description

A HSDSSource is a representation of a URL which provides access to a HDF5 server (either h5serv or hds.)

Usage

```
HSDSSource(endpoint, type = "hds")
```

Arguments

endpoint	URL for server
type	Type of server software at the source; must be

Details

This function is deprecated and will be defunct in the next release.

Value

An object of type HSDSSource

Examples

```
if (check_hds()) {
  src.hds <- HSDSSource(URL_hds())
}
```

HSDSSource-class	<i>An S4 class to represent a HDF5 server listening on a port.</i>
------------------	--

Description

This class is deprecated and will be defunct in the next release.

Slots

endpoint	URL for server
type	Type of server software at the source; must be either 'h5serv' or (default) 'hds'

isplit

This function is deprecated and will be defunct in the next release.

Description

isplit converts a numeric vector into a list of sequences for compact reexpression

Usage

```
isplit(x)

sproc(spl)
```

Arguments

x	a numeric vector (should be integers)
spl	output of isplit

Value

list of vectors of integers which can be expressed as initial/final/stride triplets
list of colon-delimited strings each with initial/final/stride triplet

Examples

```
inds = c(1:10, seq(25,50,2), seq(200,150,-2))
sproc(isplit(inds))
```

listDatasets

Search inner file hierarchy for datasets

Description

The datasets in an HDF5 file are organized internally by groups. This routine traverses the internal group hierarchy, locates all datasets and prints a list of them. Note that if the file's group hierarchy is complex, this could be time-consuming.

Usage

```
listDatasets(file)
```

Arguments

file	an object of type HSDSFile to be searched
------	---

Details

This function is deprecated and will be defunct in the next release.

Value

a list of inner-paths

Examples

```
if (check_hsd()) {
  src <- HSDSource(URL_hsd())
  f <- HSDFile(src, '/shared/bioconductor/patelGBMSC.h5')
  listDatasets(f)
}
```

listDomains	<i>List files and subdirectories of a domain</i>
-------------	--

Description

The user needs to give the domain to start in. The search will be non-recursive. I.e., output for domain '/home/jreadey/' will not return the files in '/home/jreadey/HDFLabTutorial/'

Usage

```
listDomains(object, rootdir)

## S4 method for signature 'HSDSource,character'
listDomains(object, rootdir)

## S4 method for signature 'HSDSource,missing'
listDomains(object)
```

Arguments

object	An object of type HSDSource
rootdir	A slash-separated directory in the HSDSource file system.

Details

This function is deprecated and will be defunct in the next release.

Value

a vector of domains in the rootdir

Examples

```
src.hsds <- HSDSSource(URL_hsds())
listDomains(src.hsds, '/shared')
```

rhdf5client

rhdf5client: A package for accessing HDFGroup HDF5 servers from R.

Description

The rhdf5client package provides read-only access to HDF5 files maintained on a server. The HDFGroup provides two servers, an obsolescent one called ‘h5serv’ and the newer prototype called ‘hsds’.

Author(s)

Maintainer: Vincent Carey <stvjc@channing.harvard.edu>

Authors:

- Samuela Pollack <spollack@jimmy.harvard.edu>
- Shweta Gopaulakrishnan <reshg@channing.harvard.edu>
- BJ Stubbs <rebjh@channing.harvard.edu>
- Alexey Sergushichev <alsergbox@gmail.com>

rhdf5client-deprecated

Deprecated functions in package ‘rhdf5client’

Description

These functions are provided for compatibility with older versions of ‘rhdf5client’ only, and will be defunct at the next release.

Details

The following functions are deprecated and will be made defunct in the next release:

- URL_h5serv
- URL_hsds
- dsmeta
- getReq
- groups
- setPath

- links
- transfermode
- dataset
- internalDim
- hsdInfo
- domains
- getDatasetUUIDs
- getDatasetAttrs
- getDims
- getHRDF
- H5S_dataset2
- getDatasetSlice
- fetchDatasets
- isplit
- sproc
- listDomains
- listDatasets
- getData

The following classes are deprecated and will be made defunct in the next release:

- H5S_source
- H5S_dataset
- H5S_Array
- H5S_Matrix
- HSDSSource
- HSDSFile
- HSDSDataset

URL_hsd	<i>manage hsd URL</i>
---------	-----------------------

Description

manage hsd URL

Usage

URL_hsd()

Value

URL of hsd server

Examples

URL_hsd()

[,HSDSDataset,numeric,ANY,ANY-method
bracket method for 1d request from HSDSDataset

Description

bracket method for 1d request from HSDSDataset

Usage

```
## S4 method for signature 'HSDSDataset,numeric,ANY,ANY'
x[i, j, ..., drop = TRUE]
```

Arguments

x	object of type HSDSDataset
i	vector of indices (first dimension)
j	not used
...	not used
drop	logical(1) if TRUE return has no array character

Value

an array with the elements requested from the HSDSDataset

[,HSDSDataset,numeric,numeric,ANY-method
bracket method for 2d request from HSDSDataset

Description

bracket method for 2d request from HSDSDataset

Usage

```
## S4 method for signature 'HSDSDataset,numeric,numeric,ANY'
x[i, j, ..., drop = TRUE]
```

Arguments

x	object of type HSDSDataset
i	vector of indices (first dimension)
j	vector of indices (second dimension)
...	not used
drop	logical(1) if TRUE return has no array character

Value

an array with the elements requested from the HSDSDataset

Index

* **HSDSArray**
 as, [2](#)
 HSDSArray, [7](#)
 HSDSMatrix, [10](#)
 [,HSDSDataset,numeric,ANY,ANY-method,
 [16](#)
 [,HSDSDataset,numeric,numeric,ANY-method,
 [16](#)

as, [2](#), [7](#), [10](#)

check_hsd, [3](#)

dim, [3](#)
dim,HSDSArraySeed-method (dim), [3](#)
dimnames, [4](#)
dimnames,HSDSArraySeed-method
 (dimnames), [4](#)

extract_array, [5](#)
extract_array,HSDSArraySeed-method
 (extract_array), [5](#)
extractCompoundJSON, [4](#)

getData, [5](#)
getData,HSDSDataset,character,character-method
 (getData), [5](#)
getData,HSDSDataset,character,missing-method
 (getData), [5](#)
getData,HSDSDataset,list,,missing-method
 (getData), [5](#)
getData,HSDSDataset,list,character-method
 (getData), [5](#)
getData,HSDSDataset,list,missing-method
 (getData), [5](#)
getHSDSFileList, [6](#)

HSDSArray, [2](#), [7](#), [10](#)
HSDSArray-class (HSDSArray), [7](#)
HSDSArraySeed, [8](#)
HSDSArraySeed-class (HSDSArraySeed), [8](#)

HSDSDataset, [8](#)
HSDSDataset-class, [9](#)
HSDSFile, [9](#)
HSDSFile-class, [10](#)
HSDSMatrix, [2](#), [7](#), [10](#)
HSDSMatrix-class (HSDSMatrix), [10](#)
HSDSSource, [11](#)
HSDSSource-class, [11](#)

isplit, [12](#)

listDatasets, [12](#)
listDomains, [13](#)
listDomains,HSDSSource,character-method
 (listDomains), [13](#)
listDomains,HSDSSource,missing-method
 (listDomains), [13](#)

rhdf5client, [14](#)
rhdf5client-deprecated, [14](#)
rhdf5client-package (rhdf5client), [14](#)

sproc (isplit), [12](#)

URL_hsd, [15](#)