

Package ‘Linnorm’

May 9, 2024

Type Package

Title Linear model and normality based normalization and transformation method (Linnorm)

Version 2.28.0

Date 2023-10-12

Author Shun Hang Yip <shunyip@bu.edu>

Maintainer Shun Hang Yip <shunyip@bu.edu>

Description Linnorm is an algorithm for normalizing and transforming RNA-seq, single cell RNA-seq, ChIP-seq count data or any large scale count data. It has been independently reviewed by Tian et al. on Nature Methods (<https://doi.org/10.1038/s41592-019-0425-8>). Linnorm can work with raw count, CPM, RPKM, FPKM and TPM.

Depends R(>= 4.1.0)

License MIT + file LICENSE

Imports Rcpp (>= 0.12.2), RcppArmadillo (>= 0.8.100.1.0), fpc, vegan, mclust, apcluster, ggplot2, ellipse, limma, utils, statmod, MASS, igraph, grDevices, graphics, fastcluster, ggdendro, zoo, stats, amap, Rtsne, gmodels

LinkingTo Rcpp, RcppArmadillo

Suggests BiocStyle, knitr, rmarkdown, markdown, gplots, RColorBrewer, moments, testthat, matrixStats

VignetteBuilder knitr

biocViews ImmunoOncology, Sequencing, ChIPSeq, RNASeq, DifferentialExpression, GeneExpression, Genetics, Normalization, Software, Transcription, BatchEffect, PeakDetection, Clustering, Network, SingleCell

NeedsCompilation yes

LazyData false

URL <https://doi.org/10.1093/nar/gkx828>

RoxygenNote 7.2.3

git_url <https://git.bioconductor.org/packages/Linnorm>

git_branch RELEASE_3_19

git_last_commit 3f0791c

git_last_commit_date 2024-04-30

Repository Bioconductor 3.19

Date/Publication 2024-05-08

Contents

| | |
|------------------------------|-----------|
| Islam2011 | 2 |
| LIHC | 3 |
| LinearRegression | 3 |
| LinearRegressionFP | 4 |
| Linnorm | 5 |
| Linnorm.Cor | 7 |
| Linnorm.DataImput | 9 |
| Linnorm.HClust | 11 |
| Linnorm.HVar | 13 |
| Linnorm.limma | 15 |
| Linnorm.Norm | 16 |
| Linnorm.PCA | 18 |
| Linnorm.SGenes | 20 |
| Linnorm.tSNE | 21 |
| RnaXSim | 23 |
| SEQC | 25 |
| Index | 26 |

| | |
|-----------|--|
| Islam2011 | <i>scRNA-seq data from Islam et al. 2011</i> |
|-----------|--|

Description

GEO accession GSE29087: 92 single cells (48 mouse embryonic stem cells, 44 mouse embryonic fibroblasts and 4 negative controls) were analyzed by single-cell tagged reverse transcription (STRT).

Usage

```
data(Islam2011)
```

Format

A matrix with 22936 rows (genes) and 96 columns (samples). The first 48 columns are ES cells, the following 44 columns are mouse embryonic fibroblasts and the remaining 4 columns and negative controls. Data is in raw counts format.

References

Islam et al. (2011) Genome Res 2011 Jul;21(7):1160-7. PMID: 21543516

| | |
|------|---|
| LIHC | <i>Partial RNA-seq data from TCGA LIHC (Liver Hepatocellular Carcinoma)</i> |
|------|---|

Description

TPM Expression data

Usage

data(LIHC)

Format

A matrix with 25914 rows (genes) and 10 columns (samples). The first 5 columns are Tumor samples, the remaining 5 columns are adjacent Normal samples. They are paired samples from 5 individuals. Data is in TPM format.

References

<https://tcga-data.nci.nih.gov/>

| | |
|------------------|------------------------------------|
| LinearRegression | <i>One Pass Linear Regression.</i> |
|------------------|------------------------------------|

Description

This function performs Linear Regression on the input data with a one pass algorithm implemented in C++. This is for users who only need m and c from the $y=mx + c$ equation. Compared to the lm function, this function is much faster.

Usage

LinearRegression(x, y)

Arguments

| | |
|---|---|
| x | Numeric vector. x values. |
| y | Numeric vector. corresponding y values. |

Details

This function calculates m and c in the linear equation, $y = mx + c$.

Value

This function returns a list with one object, "coefficients". The first element in this object is c; the second element is m in the $y = mx + c$ equation.

Examples

```
x <- 1:10
y <- 1:10
results <- LinearRegression(x,y)
m <- results$coefficients[[2]]
c <- results$coefficients[[1]]
```

LinearRegressionFP *One Pass Linear Regression with fixed point.*

Description

This function performs Linear Regression on the input data with a fixed point. It uses a one pass algorithm implemented in C++. This is for users who only need m and c from the $y=mx + c$ equation. Compared to the lm function, this function is much faster.

Usage

```
LinearRegressionFP(x, y, x1, y1)
```

Arguments

| | |
|----|---|
| x | Numeric vector. x values. |
| y | Numeric vector. corresponding y values. |
| x1 | Numeric. x coordinate of the fixed point. |
| y1 | Numeric. y coordinate of the fixed point. |

Details

This function calculates m and c in the linear equation, $y = mx + c$.

Value

This function returns a list with one object, "coefficients". The first element in this object is c; the second element is m in the $y = mx + c$ equation.

Examples

```
x <- 1:10
y <- 1:10
x1 <- 1
y1 <- 2
results <- LinearRegressionFP(x,y, x1, y1)
m <- results$coefficients[[2]]
c <- results$coefficients[[1]]
```

Linnorm

Linnorm Normalizing Transformation Function

Description

This function performs the Linear model and normality based transformation method (Linnorm) for (sc)RNA-seq expression data or large scale count data.

Usage

```
Linnorm(  
  datamatrix,  
  RowSamples = FALSE,  
  spikein = NULL,  
  spikein_log2FC = NULL,  
  showinfo = FALSE,  
  perturbation = "Auto",  
  Filter = FALSE,  
  minNonZeroPortion = 0.75,  
  L_F_p = 0.3173,  
  L_F_LC_Genes = "Auto",  
  L_F_HC_Genes = 0.01,  
  BE_F_p = 0.3173,  
  BE_F_LC_Genes = "Auto",  
  BE_F_HC_Genes = 0.01,  
  BE_strength = 0.5,  
  max_F_LC = 0.75,  
  DataImputation = FALSE,  
  ...  
)
```

Arguments

datamatrix The matrix or data frame that contains your dataset. Raw Counts, CPM, RPKM, FPKM or TPM are supported. Undefined values such as NA are not supported. It is not compatible with log transformed datasets.

| | |
|-------------------|--|
| RowSamples | Logical. In the datamatrix, if each row is a sample and each column is a feature, set this to TRUE so that you don't need to transpose it. Linnorm works slightly faster with this argument set to FALSE, but it should be negligible for smaller datasets. Defaults to FALSE. |
| spikein | character vector. Names of the spike-in genes in the datamatrix. Defaults to NULL. |
| spikein_log2FC | Numeric vector. Log 2 fold change of the spike-in genes. Defaults to NULL. |
| showinfo | Logical. Show algorithm running information. Defaults to FALSE. |
| perturbation | Integer ≥ 2 or "Auto". To search for an optimal minimal deviation parameter (please see the article), Linnorm uses the iterated local search algorithm which perturbs away from the initial local minimum. The range of the area searched in each perturbation is exponentially increased as the area get further away from the initial local minimum, which is determined by their index. This range is calculated by $10 * (\text{perturbation} \wedge \text{index})$. Defaults to "Auto". |
| Filter | Logical. Should Linnorm filter the dataset in the end results? Defaults to FALSE. |
| minNonZeroPortion | Double ≥ 0.01 , ≤ 0.95 . Minimum non-Zero Portion Threshold. Genes not satisfying this threshold will be removed. For example, if set to 0.75, genes without at least 75 percent of the samples being non-zero will be removed. Defaults to 0.75. |
| L_F_p | Double ≥ 0 , ≤ 1 . Filter genes with standard deviation and skewness less than this p value before applying Linnorm algorithm. Defaults to 0.3173. |
| L_F_LC_Genes | Double ≥ 0.01 , ≤ 0.95 or Character "Auto". Filter this portion of the lowest expressing genes before applying Linnorm algorithm. It can be determined automatically by setting to "Auto". Defaults to "Auto". |
| L_F_HC_Genes | Double ≥ 0.01 , ≤ 0.95 . Filter this portion of the highest expressing genes before applying Linnorm algorithm. Defaults to 0.01. |
| BE_F_p | Double ≥ 0 , ≤ 1 . Filter genes with standard deviation and skewness less than this p value before applying Linnorm's batch effect normalization algorithm. Defaults to 0.3173. |
| BE_F_LC_Genes | Double ≥ 0.01 , ≤ 0.95 or Character "Auto". Filter this portion of the lowest expressing genes before applying Linnorm's batch effect normalization algorithm. It can be determined automatically by setting to "Auto". Defaults to "Auto". |
| BE_F_HC_Genes | Double ≥ 0.01 , ≤ 0.95 . Filter this portion of the highest expressing genes before applying Linnorm's batch effect normalization algorithm. Defaults to 0.01. |
| BE_strength | Double > 0 , ≤ 1 . Before Linnorm transformation, how strongly should Linnorm normalize batch effects? Defaults to 0.5. |
| max_F_LC | Double ≥ 0 , ≤ 0.95 . When L_F_LC or B_F_LC is set to auto, this is the maximum threshold that Linnorm would assign. Defaults to 0.75. |
| DataImputation | Logical. Perform data imputation on the dataset after transformation. Defaults to FALSE. |
| ... | place holder for any new arguments. |

Details

This function normalizes and transforms the input dataset using the Linnorm algorithm.

Value

This function returns a transformed data matrix.

If Filter is set to True, this function will output a list with the following objects:

- Linnorm: The full non-filtered transformed data matrix.
- Keep_Features: The features that survived filtering, users may use it to filter the data.

Examples

```
#Obtain example matrix:
data(LIHC)
#Transformation:
transformedExp <- Linnorm(LIHC)
```

Linnorm.Cor

Linnorm-gene correlation network analysis.

Description

This function first performs Linnorm transformation on the dataset. Then, it will perform correlation network analysis on the dataset.

Usage

```
Linnorm.Cor(
  datamatrix,
  RowSamples = FALSE,
  input = "Raw",
  method = "pearson",
  MZP = 0.5,
  sig.q = 0.05,
  plotNetwork = TRUE,
  plotNumPairs = 5000,
  plotdegree = 0,
  plotname = "networkplot",
  plotformat = "png",
  plotVertexSize = 1,
  plotFontSize = 1,
  plot.Pos.cor.col = "red",
  plot.Neg.cor.col = "green",
  vertex.col = "cluster",
  plotlayout = "kk",
  clusterMethod = "cluster_edge_betweenness",
  ...
)
```

Arguments

| | |
|-------------------------------|---|
| <code>datamatrix</code> | The matrix or data frame that contains your dataset. Raw Counts, CPM, RPKM, FPKM, TPM or Linnorm transformed data are supported. Undefined values such as NA are not supported. |
| <code>RowSamples</code> | Logical. In the datamatrix, if each row is a sample and each column is a feature, set this to TRUE so that you don't need to transpose it. Linnorm works slightly faster with this argument set to TRUE, but it should be negligible for smaller datasets. Defaults to FALSE. |
| <code>input</code> | Character. "Raw" or "Linnorm". In case you have already transformed your dataset with Linnorm, set input into "Linnorm" so that you can put the Linnorm transformed dataset into the "datamatrix" argument. Defaults to "Raw". |
| <code>method</code> | Character. "pearson", "kendall" or "spearman". Method for the calculation of correlation coefficients. Defaults to "pearson". |
| <code>MZP</code> | Double ≥ 0 , ≤ 1 . Minimum non-Zero Portion Threshold for this function. Genes not satisfying this threshold will be removed for correlation calculation. For example, if set to 0.3, genes without at least 30 percent of the samples being non-zero will be considered for this study. Defaults to 0.5. |
| <code>sig.q</code> | Double ≥ 0 , ≤ 1 . Only gene pairs with q values less than this threshold will be included in the "Results" data frame. Defaults to 0.05. |
| <code>plotNetwork</code> | Logical. Should the program output the network plot to a file? An "igraph" object will be included in the output regardless. Defaults to TRUE. |
| <code>plotNumPairs</code> | Integer ≥ 50 . Number of gene pairs to be used in the network plot. Defaults to 5000. |
| <code>plotdegree</code> | Integer ≥ 0 . In the network plot, genes (vertices) without at least this number of degree will be removed. Defaults to 0. |
| <code>plotname</code> | Character. Name of the network plot. File extension will be appended to it. Defaults to "networkplot". |
| <code>plotformat</code> | Character. "pdf" or "png". Network plot output format. Defaults to "png". |
| <code>plotVertexSize</code> | Double > 0 . Controls vertex Size in the network plot. Defaults to 1. |
| <code>plotFontSize</code> | Double > 0 . Controls font Size in the network plot. Defaults to 1. |
| <code>plot.Pos.cor.col</code> | Character. Color of the edges of positively correlated gene pairs. Defaults to "red". |
| <code>plot.Neg.cor.col</code> | Character. Color of the edges of negatively correlated gene pairs. Defaults to "green". |
| <code>vertex.col</code> | Character. "cluster" or a color. This controls the color of the vertices. Defaults to "cluster". |
| <code>plotlayout</code> | Character. "kk" or "fr". "kk" uses Kamada-Kawai algorithm in igraph to assign vertex and edges. It scales edge length with correlation strength. However, it can cause overlaps between vertices. "fr" uses Fruchterman-Reingold algorithm in igraph to assign vertex and edges. It prevents overlaps between vertices better than "kk", but edge lengths are not scaled to correlation strength. Defaults to "kk". |

`clusterMethod` Character. "cluster_edge_betweenness", "cluster_fast_greedy", "cluster_infomap", "cluster_label_prop", "cluster_leading_eigen", "cluster_louvain", "cluster_optimal", "cluster_springlass" or "cluster_walktrap". These are clustering functions from the igraph package. Defaults to "cluster_edge_betweenness".

... arguments that will be passed into Linnorm's transformation function.

Details

This function performed gene correlated study in the dataset by using Linnorm transformation

Value

This function will output a list with the following objects:

- `Results`: A data frame containing the results of the analysis, showing only the significant results determined by "sig.q" (see below).
- `Cor.Matrix`: The resulting correlation matrix between each gene.
- `q.Matrix`: A matrix of q values of each of the correlation coefficient from `Cor.Matrix`.
- `Cluster`: A data frame that shows which gene belongs to which cluster.
- `igraph`: The igraph object for users who want to draw the network plot manually.
- `Linnorm`: Linnorm transformed data matrix.

The "Results" data frame has the following columns:

- `Gene1`: Name of gene 1.
- `Gene2`: Name of gene 2.
- `Cor`: Correlation coefficient between the two genes.
- `p.value`: p value of the correlation coefficient.
- `q.value`: q value of the correlation coefficient.

Examples

```
data(Islam2011)
#Analysis on Islam2011 embryonic stem cells
results <- Linnorm.Cor(Islam2011[,1:48], plotNetwork=FALSE)
```

Linnorm.DataInput

Linnorm Data Imputation Function. (In development)

Description

This function performs data imputation for (sc)RNA-seq expression data or large scale count data. It will treat every zero count in the dataset as missing data and replace them with predicted values.

Usage

```
Linnorm.DataImput(
  datamatrix,
  RowSamples = FALSE,
  showinfo = FALSE,
  MZP = 0.25,
  LC_F = "Auto",
  max_LC_F = 0.75,
  FG_Recov = 0.5,
  method = "euclidean",
  VarPortion = 0.75,
  ...
)
```

Arguments

| | |
|------------|--|
| datamatrix | The matrix or data frame that contains your dataset. It is only compatible with log transformed datasets. |
| RowSamples | Logical. In the datamatrix, if each row is a sample and each column is a feature, set this to TRUE so that you don't need to transpose it. Defaults to FALSE. |
| showinfo | Logical. Show algorithm running information. Defaults to FALSE. |
| MZP | Double ≥ 0 , ≤ 1 . Minimum non-Zero Portion Threshold for this function. Genes not satisfying this threshold will be removed. For example, if set to 0.3, genes without at least 30 percent of the samples being non-zero will be removed. Defaults to 0.25. |
| LC_F | Double ≥ 0.01 , ≤ 0.95 or Character "Auto". Filter this portion of the lowest expressing genes. It can be determined automatically by setting to "Auto". Defaults to "Auto". |
| max_LC_F | Double ≥ 0 , ≤ 0.95 . When LC_F is set to auto, this is the maximum threshold that Linnorm would assign. Defaults to 0.75. |
| FG_Recov | Double ≥ 0 , ≤ 1 . In the low count gene filtering algorithm, recover this portion of genes that are filtered. Defaults to 0.5. |
| method | Character. Method for calculating the distance matrix. This must be one of "euclidean", "maximum", "manhattan", "canberra", "binary", "pearson", "correlation", "spearman" or "kendall". Any unambiguous substring can be given. Defaults to "euclidean". |
| VarPortion | Double > 0 , ≤ 0.95 . Portion of the variance from PCA to be used for data imputation. Defaults to 0.5. |
| ... | place holder for any new arguments. |

Details

This function performs data imputation on the dataset. It first generates a distance matrix using principal components from PCA. Then, by default, using the distance matrix as weight, it predicts missing values from each gene using inverse euclidean distance weighted mean.

Value

This function returns a data matrix.

Examples

```
#Obtain example matrix:
data(Islam2011)
#Transformation:
Transformed <- Linnorm(Islam2011)
#Data imputation
DataInput <- Linnorm.DataImput(Transformed)
```

Linnorm.HClust

Linnorm-hierarchical clustering analysis.

Description

This function first performs Linnorm transformation on the dataset. Then, it will perform hierarchical clustering analysis.

Usage

```
Linnorm.HClust(
  datamatrix,
  RowSamples = FALSE,
  MZP = 0,
  DataImputation = TRUE,
  input = "Raw",
  method_hclust = "ward.D",
  method_dist = "pearson",
  Group = NULL,
  num_Clust = 0,
  Color = "Auto",
  ClustRect = TRUE,
  RectColor = "red",
  fontsize = 0.5,
  linethickness = 0.5,
  plot.title = "Hierarchical clustering",
  ...
)
```

Arguments

`datamatrix` The matrix or data frame that contains your dataset. Raw Counts, CPM, RPKM, FPKM, TPM or Linnorm transformed data are supported. Undefined values such as NA are not supported.

| | |
|----------------|--|
| RowSamples | Logical. In the datamatrix, if each row is a sample and each column is a feature, set this to TRUE so that you don't need to transpose it. Linnorm works slightly faster with this argument set to TRUE, but it should be negligible for smaller datasets. Defaults to FALSE. |
| MZP | Double ≥ 0 , ≤ 1 . Minimum non-Zero Portion Threshold for this function. Genes not satisfying this threshold will be removed from HVG analysis. For example, if set to 0.3, genes without at least 30 percent of the samples being non-zero will be removed. Defaults to 0. |
| DataImputation | Logical. Perform data imputation on the dataset after transformation. Defaults to TRUE. |
| input | Character. "Raw" or "Linnorm". In case you have already transformed your dataset with Linnorm, set input into "Linnorm" so that you can input the Linnorm transformed dataset into the "datamatrix" argument. Defaults to "Raw". |
| method_hclust | Character. Method to be used in hierarchical clustering. (From hclust fastcluster: the agglomeration method to be used. This should be (an unambiguous abbreviation of) one of "ward.D", "ward.D2", "single", "complete", "average", "mcquitty", "median" or "centroid".) Defaults to "ward.D". |
| method_dist | Character. Method to be used in hierarchical clustering. (From Dist amap: the distance measure to be used. This must be one of "euclidean", "maximum", "manhattan", "canberra", "binary", "pearson", "correlation", "spearman" or "kendall". Any unambiguous substring can be given.) Defaults to "pearson". |
| Group | Character vector with length equals to sample size. Each character in this vector corresponds to each of the columns (samples) in the datamatrix. If this is provided, sample names will be colored according to their group. Defaults to NULL. |
| num_Clust | Integer ≥ 0 . Number of clusters in hierarchical clustering. No cluster will be highlighted if this is set to 0. Defaults to 0. |
| Color | Character vector. Color of the groups/clusters in the plot. This vector must be as long as num_Clust, or Group if it is provided. Defaults to "Auto". |
| ClustRect | Logical. If num_Clust > 0 , should a rectangle be used to highlight the clusters? Defaults to TRUE. |
| RectColor | Character. If ClustRect is TRUE, this controls the color of the rectangle. Defaults to "red". |
| fontsize | Numeric. Font size of the texts in the figure. Defaults to 0.5. |
| linethickness | Numeric. Controls the thickness of the lines in the figure. Defaults to 0.5. |
| plot.title | Character. Set the title of the plot. Defaults to "Hierarchical clustering". |
| ... | arguments that will be passed into Linnorm's transformation function. |

Details

This function performs PCA clustering using Linnorm transformation.

Value

It returns a list with the following objects:

- Results: If num_Clust > 0, this outputs a named vector that contains the cluster assignment information of each sample. Else, this outputs a number 0.
- plot: Plot of hierarchical clustering.
- Linnorm: Linnorm transformed data matrix.

Examples

```
#Obtain example matrix:
data(Islam2011)
#Example:
HClust.results <- Linnorm.HClust(Islam2011, Group=c(rep("ESC",48), rep("EF",44), rep("NegCtrl",4)))
```

Linnorm.HVar

Linnorm-Hvar pipeline for highly variable gene discovery.

Description

This function first performs Linnorm transformation on the dataset. Then, it will perform highly variable gene discovery.

Usage

```
Linnorm.HVar(
  datamatrix,
  RowSamples = FALSE,
  spikein = NULL,
  spikein_log2FC = NULL,
  log.p = FALSE,
  sig.value = "p",
  sig = 0.05,
  MZP = 0.25,
  FG_Recov = 0.5,
  plot.title = "Mean vs SD plot",
  ...
)
```

Arguments

| | |
|------------|---|
| datamatrix | The matrix or data frame that contains your dataset. Raw Counts, CPM, RPKM, FPKM or TPM are supported. Undefined values such as NA are not supported. It is not compatible with log transformed datasets. |
| RowSamples | Logical. In the datamatrix, if each row is a sample and each column is a feature, set this to TRUE so that you don't need to transpose it. Linnorm works slightly faster with this argument set to TRUE, but it should be negligible for smaller datasets. Defaults to FALSE. |

| | |
|-----------------------------|---|
| <code>spikein</code> | character vector. Names of the spike-in genes in the datamatrix. Defaults to NULL. |
| <code>spikein_log2FC</code> | Numeric vector. Log 2 fold change of the spike-in genes. Defaults to NULL. |
| <code>log.p</code> | Logical. Output p/q values in log scale. Defaults to FALSE. |
| <code>sig.value</code> | Character. "p" or "q". Use p or q value for highlighting significant genes. Defaults to "p". |
| <code>sig</code> | Double $>0, \leq 1$. Significant level of p or q value for plotting. Defaults to 0.05. |
| <code>MZP</code> | Double $\geq 0, \leq 1$. Minimum non-Zero Portion Threshold for this function. Genes not satisfying this threshold will be removed from HVG analysis. For example, if set to 0.3, genes without at least 30 percent of the samples being non-zero will be removed. Defaults to 0.25. |
| <code>FG_Recov</code> | Double $\geq 0, \leq 1$. In the low count gene filtering algorithm, recover this portion of genes that are filtered. Defaults to 0.5. |
| <code>plot.title</code> | Character. The plot's title. Defaults to "Mean vs SD plot". |
| <code>...</code> | arguments that will be passed into Linnorm's transformation function. |

Details

This function discovers highly variable gene in the dataset using Linnorm transformation.

Value

This function will output a list with the following objects:

- Results: A matrix with the results.
- plot: Mean vs Standard Deviation Plot which highlights significant genes.
- Linnorm: Linnorm transformed data matrix.

The Results matrix has the following columns:

- Transformed.Avg.Exp: Average expression of non-zero Linnorm transformed data.
- Transformed.SD: Standard deviation of non-zero Linnorm transformed data.
- Normalized.Log2.SD.Fold.Change: Normalized log2 fold change of the gene's standard deviation.
- p.value: p value of the statistical test.
- q.value: q value/false discovery rate/adjusted p value of the statistical test.

Examples

```
data(Islam2011)
results <- Linnorm.HVar(Islam2011)
```

Linnorm.limma

*Linnorm-limma pipeline for Differentially Expression Analysis***Description**

This function first performs Linnorm transformation on the dataset. Then, it will perform limma for DEG analysis. Please cite both Linnorm and limma when you use this function for publications.

Usage

```
Linnorm.limma(
  datamatrix,
  design = NULL,
  RowSamples = FALSE,
  MZP = 0,
  output = "DEResults",
  noINF = TRUE,
  robust = FALSE,
  ...
)
```

Arguments

| | |
|------------|---|
| datamatrix | The matrix or data frame that contains your dataset. Raw Counts, CPM, RPKM, FPKM or TPM are supported. Undefined values such as NA are not supported. It is not compatible with log transformed datasets. |
| design | A design matrix required for limma. Please see limma's documentation or our vignettes for more detail. |
| RowSamples | Logical. In the datamatrix, if each row is a sample and each column is a feature, set this to TRUE so that you don't need to transpose it. Linnorm works slightly faster with this argument set to TRUE, but it should be negligible for smaller datasets. Defaults to FALSE. |
| MZP | Double ≥ 0 , ≤ 1 . Minimum non-Zero Portion Threshold for this function. Genes not satisfying this threshold will be removed from HVG analysis. For example, if set to 0.3, genes without at least 30 percent of the samples being non-zero will be removed. Defaults to 0. |
| output | Character. "DEResults" or "Both". Set to "DEResults" to output a matrix that contains Differential Expression Analysis Results. Set to "Both" to output a list that contains both Differential Expression Analysis Results and the transformed data matrix. |
| noINF | Logical. Prevent generating INF in the fold change column by adding the estimated count of one. If it is set to FALSE, zero or INF will be generated if one of the conditions has zero expression. Defaults to TRUE. |
| robust | Logical. In the eBayes function of Limma, run with robust setting with TRUE or FALSE. Defaults to FALSE. |
| ... | arguments that will be passed into Linnorm's transformation function. |

Details

This function performs both Linnorm and limma for users who are interested in differential expression analysis.

Value

If output is set to "DEResults", this function will output a matrix with Differential Expression Analysis Results with the following columns:

- logFC: Log 2 Fold Change
- XPM: Average Expression. If input is raw count or CPM, this column has the CPM unit. If input is RPKM, FPKM or TPM, this column has the TPM unit.
- t: moderated t-statistic
- P.Value: p value
- adj.P.Val: Adjusted p value. This is also called False Discovery Rate or q value.
- B: log odds that the feature is differential

If output is set to Both, this function will output a list with the following objects:

- DEResults: Differential Expression Analysis Results as described above.
- Linnorm: Linnorm transformed data matrix.

Examples

```
#Obtain example matrix:
data(LIHC)
#Create limma design matrix (first 5 columns are tumor, last 5 columns are normal)
designmatrix <- c(rep(1,5),rep(2,5))
designmatrix <- model.matrix(~ 0+factor(designmatrix))
colnames(designmatrix) <- c("group1", "group2")
rownames(designmatrix) <- colnames(LIHC)
#DEG analysis
DEGResults <- Linnorm.limma(LIHC, designmatrix)
```

Linnorm.Norm

Linnorm Normalization Function

Description

This function performs batch effect and library size difference normalization on the input dataset.

Usage

```
Linnorm.Norm(
  datamatrix,
  RowSamples = FALSE,
  spikein = NULL,
  spikein_log2FC = NULL,
  showinfo = FALSE,
  output = "XPM",
  minNonZeroPortion = 0.3,
  BE_F_p = 0.3173,
  BE_F_LC_Genes = "Auto",
  BE_F_HC_Genes = 0.01,
  BE_strength = 0.5,
  max_F_LC = 0.75
)
```

Arguments

| | |
|--------------------------------|---|
| <code>datamatrix</code> | The matrix or data frame that contains your dataset. Raw Counts, CPM, RPKM, FPKM or TPM are supported. Undefined values such as NA are not supported. It is not compatible with log transformed datasets. |
| <code>RowSamples</code> | Logical. In the datamatrix, if each row is a sample and each column is a feature, set this to TRUE so that you don't need to transpose it. Linnorm works slightly faster with this argument set to TRUE, but it should be negligible for smaller datasets. Defaults to FALSE. |
| <code>spikein</code> | character vector. Names of the spike-in genes in the datamatrix. Defaults to NULL. |
| <code>spikein_log2FC</code> | Numeric vector. Log 2 fold change of the spike-in genes. Defaults to NULL. |
| <code>showinfo</code> | Logical. Show algorithm running information. Defaults to FALSE. |
| <code>output</code> | character. "Raw" or "XPM". Output's total count will be approximately the median of the inputs' when set to "Raw". Output CPM (if input is raw counts or CPM) or TPM (if input is RPKM FPKM or TPM) when set to "XPM". |
| <code>minNonZeroPortion</code> | Double ≥ 0 , ≤ 1 . Minimum non-Zero Portion Threshold. Genes not satisfying this threshold will be removed. For exmaple, if set to 0.75, genes without at least 75 percent of the samples being non-zero will be removed. Defaults to 0.75. |
| <code>BE_F_p</code> | Double ≥ 0 , ≤ 1 . Filter genes with standard deviation and skewness less than this p value before applying Linnorm's batch effect normalization algorithm. Defaults to 0.3173. |
| <code>BE_F_LC_Genes</code> | Double ≥ 0.01 , ≤ 0.95 or Character "Auto". Filter this portion of the lowest expressing genes before applying Linnorm's batch effect normalization algorithm. It can be determined automatically by setting to "Auto". Defaults to "Auto". |
| <code>BE_F_HC_Genes</code> | Double ≥ 0 , ≤ 1 . Filter this portion of the highest expressing genes before applying Linnorm's batch effect normalization algorithm. Defaults to 0.01. |

| | |
|-------------|---|
| BE_strength | Double >0, <= 1. How strongly should Linnorm normalize batch effects? Defaults to 0.5. |
| max_F_LC | Double >=0, <= 0.95. When L_F_LC or B_F_LC is set to auto, this is the maximum threshold that Linnorm would assign. Defaults to 0.75. |

Details

This function normalizes the input dataset using the Linnorm algorithm.

Value

This function returns a normalized data matrix.

Examples

```
#Obtain example matrix:
data(LIHC)
#Normalization:
normalizedExp <- Linnorm(LIHC)
```

Linnorm.PCA

Linnorm-PCA Clustering pipeline for subpopulation Analysis

Description

This function first performs Linnorm transformation on the dataset. Then, it will perform Principal component analysis on the dataset and use k-means clustering to identify subpopulations of cells.

Usage

```
Linnorm.PCA(
  datamatrix,
  RowSamples = FALSE,
  input = "Raw",
  MZP = 0,
  HVar_p_value = 0.5,
  DataImputation = TRUE,
  num_PC = 3,
  num_center = c(1:20),
  Group = NULL,
  Coloring = "kmeans",
  pca.scale = FALSE,
  kmeans.iter = 2000,
  plot.title = "PCA K-means clustering",
  ...
)
```

Arguments

| | |
|-----------------------------|--|
| <code>datamatrix</code> | The matrix or data frame that contains your dataset. Raw Counts, CPM, RPKM, FPKM or TPM are supported. Undefined values such as NA are not supported. It is not compatible with log transformed datasets. |
| <code>RowSamples</code> | Logical. In the datamatrix, if each row is a sample and each column is a feature, set this to TRUE so that you don't need to transpose it. Linnorm works slightly faster with this argument set to TRUE, but it should be negligible for smaller datasets. Defaults to FALSE. |
| <code>input</code> | Character. "Raw" or "Linnorm". In case you have already transformed your dataset with Linnorm, set input into "Linnorm" so that you can put the Linnorm transformed dataset into the "datamatrix" argument. Defaults to "Raw". |
| <code>MZP</code> | Double ≥ 0 , ≤ 1 . Minimum non-Zero Portion Threshold for this function. Genes not satisfying this threshold will be removed from the analysis. For example, if set to 0.3, genes without at least 30 percent of the samples being non-zero will be removed. Defaults to 0. |
| <code>HVar_p_value</code> | Double ≥ 0 , ≤ 1 . Highly variable feature p value threshold to be used for tSNE. Defaults to 0.5. |
| <code>DataImputation</code> | Logical. Perform data imputation on the dataset after transformation. Defaults to TRUE. |
| <code>num_PC</code> | Integer ≥ 2 . Number of principal components to be used in K-means clustering. Defaults to 3. |
| <code>num_center</code> | Numeric vector. Number of clusters to be tested for k-means clustering. <code>fpc</code> , <code>vegan</code> , <code>mclust</code> and <code>apcluster</code> packages are used to determine the number of clusters needed. If only one number is supplied, it will be used and this test will be skipped. Defaults to <code>c(1:20)</code> . |
| <code>Group</code> | Character vector with length equals to sample size. Each character in this vector corresponds to each of the columns (samples) in the datamatrix. In the plot, the shape of the points that represent each sample will be indicated by their group assignment. Defaults to NULL. |
| <code>Coloring</code> | Character. "kmeans" or "Group". If Group is not NULL, coloring in the PCA plot will reflect each sample's group. Otherwise, coloring will reflect k means clustering results. Defaults to "Group". |
| <code>pca.scale</code> | Logical. In the <code>prcomp</code> (for Principal component analysis) function, set the "scale." parameter. It signals the function to scale unit variances in the variables before the analysis takes place. Defaults to FALSE. |
| <code>kmeans.iter</code> | Numeric. Number of iterations in k-means clustering. Defaults to 2000. |
| <code>plot.title</code> | Character. Set the title of the plot. Defaults to "PCA K-means clustering". |
| <code>...</code> | arguments that will be passed into Linnorm's transformation function. |

Details

This function performs PCA clustering using Linnorm transformation.

Value

It returns a list with the following objects:

- `k_means`: Output of `kmeans`(for K-means clustering) from the `stat` package. Note: It contains a "cluster" object that indicates each sample's cluster assignment.
- `PCA`: Output of `prcomp`(for Principal component analysis) from the `stat` package.
- `plot`: Plot of PCA clustering.
- `Linnorm`: Linnorm transformed data matrix.

Examples

```
#Obtain example matrix:
data(Islam2011)
#Example:
PCA.results <- Linnorm.PCA(Islam2011)
```

Linnorm.SGenes

Linnorm model stable gene selection tool.

Description

For datasets without spike-ins and for users who do not wish to rely on spike-ins, we provide this model stable gene selection tool.

Usage

```
Linnorm.SGenes(
  datamatrix,
  RowSamples = FALSE,
  showinfo = FALSE,
  minNonZeroPortion = 0.75,
  F_p = 0.3173,
  F_LC_Genes = "Auto",
  F_HC_Genes = 0.01,
  max_F_LC = 0.75
)
```

Arguments

| | |
|-------------------------|--|
| <code>datamatrix</code> | The matrix or data frame that contains your dataset. Raw Counts, CPM, RPKM, FPKM or TPM are supported. Undefined values such as NA are not supported. It is not compatible with log transformed datasets. |
| <code>RowSamples</code> | Logical. In the <code>datamatrix</code> , if each row is a sample and each column is a feature, set this to <code>TRUE</code> so that you don't need to transpose it. Linnorm works slightly faster with this argument set to <code>TRUE</code> , but it should be negligible for smaller datasets. Defaults to <code>FALSE</code> . |

| | |
|-------------------|---|
| showinfo | Logical. Show algorithm running information. Defaults to FALSE. |
| minNonZeroPortion | Double ≥ 0 , ≤ 1 . Minimum non-Zero Portion Threshold. Genes not satisfying this threshold will be removed. For example, if set to 0.75, genes without at least 75 percent of the samples being non-zero will be removed. Defaults to 0.75. |
| F_p | Double ≥ 0 , ≤ 1 . Filter genes with standard deviation and skewness less than this p value. Defaults to 0.3173. |
| F_LC_Genes | Double ≥ 0.01 , ≤ 0.95 or Character "Auto". Filter this portion of the lowest expressing genes. It can be determined automatically by setting to "Auto". Defaults to "Auto". |
| F_HC_Genes | Double ≥ 0 , ≤ 1 . Filter this portion of the highest expressing genes. Defaults to 0.01. |
| max_F_LC | Double ≥ 0 , ≤ 0.95 . When F_LC is set to auto, this is the maximum threshold that Linnorm would assign. Defaults to 0.75. |

Details

This function selects stable genes from the dataset using the Linnorm's algorithm.

Value

This function returns a data matrix that contains stable genes only.

Examples

```
#Obtain example matrix:
data(Islam2011)
#Transformation:
StableGenes <- Linnorm.SGenes(Islam2011)
```

Linnorm.tSNE

Linnorm t-SNE Clustering pipeline for subpopulation Analysis

Description

This function first performs Linnorm transformation on the dataset. Then, it will perform t-distributed stochastic neighbor embedding (t-SNE) dimensionality reduction on the dataset and use k-means clustering to identify subpopulations of cells.

Usage

```
Linnorm.tSNE(
  datamatrix,
  RowSamples = FALSE,
  input = "Raw",
  MZP = 0,
```

```

HVar_p_value = 0.5,
num_PC = 3,
num_center = c(1:20),
Group = NULL,
Coloring = "kmeans",
kmeans.iter = 2000,
plot.title = "t-SNE K-means clustering",
...
)

```

Arguments

| | |
|---------------------------|--|
| <code>datamatrix</code> | The matrix or data frame that contains your dataset. Raw Counts, CPM, RPKM, FPKM or TPM are supported. Undefined values such as NA are not supported. It is not compatible with log transformed datasets. |
| <code>RowSamples</code> | Logical. In the datamatrix, if each row is a sample and each column is a feature, set this to TRUE so that you don't need to transpose it. Linnorm works slightly faster with this argument set to TRUE, but it should be negligible for smaller datasets. Defaults to FALSE. |
| <code>input</code> | Character. "Raw" or "Linnorm". In case you have already transformed your dataset with Linnorm, set input into "Linnorm" so that you can put the Linnorm transformed dataset into the "datamatrix" argument. Defaults to "Raw". |
| <code>MZP</code> | Double ≥ 0 , ≤ 1 . Minimum non-Zero Portion Threshold for this function. Genes not satisfying this threshold will be removed from the analysis. For example, if set to 0.3, genes without at least 30 percent of the samples being non-zero will be removed. Defaults to 0. |
| <code>HVar_p_value</code> | Double ≥ 0 , ≤ 1 . Highly variable feature p value threshold to be used for tSNE. Defaults to 0.5. |
| <code>num_PC</code> | Integer ≥ 2 . Number of principal components to be used in K-means clustering. Defaults to 3. |
| <code>num_center</code> | Numeric vector. Number of clusters to be tested for k-means clustering. <code>fpc</code> , <code>vegan</code> , <code>mclust</code> and <code>apcluster</code> packages are used to determine the number of clusters needed. If only one number is supplied, it will be used and this test will be skipped. Defaults to <code>c(1:20)</code> . |
| <code>Group</code> | Character vector with length equals to sample size. Each character in this vector corresponds to each of the columns (samples) in the datamatrix. In the plot, the shape of the points that represent each sample will be indicated by their group assignment. Defaults to NULL. |
| <code>Coloring</code> | Character. "kmeans" or "Group". If Group is not NA, coloring in the plot will reflect each sample's group. Otherwise, coloring will reflect k means clustering results. Defaults to "Group". |
| <code>kmeans.iter</code> | Numeric. Number of iterations in k-means clustering. Defaults to 2000. |
| <code>plot.title</code> | Character. Set the title of the plot. Defaults to "t-SNE K-means clustering". |
| <code>...</code> | arguments that will be passed into Linnorm's transformation function. |

Details

This function performs t-SNE K-means clustering using Linnorm transformation.

Value

It returns a list with the following objects:

- `k_means`: Output of `kmeans`(for K-means clustering) from the `stat` package. Note: It contains a "cluster" object that indicates each sample's cluster assignment.
- `tSNE`: Output from `Rtsne`.
- `plot`: Plot of t-SNE K-means clustering.
- `Linnorm`: Linnorm transformed data matrix.

Examples

```
#Obtain example matrix:
data(Islam2011)
#Example:
tSNE.results <- Linnorm.tSNE(Islam2011)
```

| | |
|---------|--|
| RnaXSim | <i>This function simulates an RNA-seq dataset based on a given distribution.</i> |
|---------|--|

Description

This function simulates an RNA-seq dataset based on a given distribution.

Usage

```
RnaXSim(  
  datamatrix,  
  distribution = "NB",  
  NumRep = 5,  
  NumDiff = 2000,  
  NumFea = 20000,  
  showinfo = FALSE,  
  DEGlog2FC = "Auto",  
  MaxLibSizelog2FC = 0.5  
)
```

Arguments

| | |
|------------------|--|
| datamatrix | Matrix. The matrix or data frame that contains your dataset. Each row is a feature (or Gene) and each column is a sample (or replicate). Raw Counts, CPM, RPKM, FPKM or TPM are supported. Undefined values such as NA are not supported. It is not compatible with log transformed datasets. This program assumes that all columns are replicates of the same sample. |
| distribution | Character: Defaults to "Poisson". This parameter controls the output distribution of the simulated RNA-seq dataset. It can be one of "Gamma" (Gamma distribution), "Poisson" (Poisson distribution), "LogNorm" (Log Normal distribution) or "NB" (Negative Binomial distribution). |
| NumRep | Integer: The number of replicates. This is half of the number of output samples. Defaults to 3. |
| NumDiff | Integer: The number of Differentially Changed Features. Defaults to 2000. |
| NumFea | Integer: The number of Total Features. Defaults to 20000. |
| showinfo | Logical: should we show data information on the console? Defaults to FALSE. |
| DEGlog2FC | "Auto" or Double: log 2 fold change threshold that defines differentially expressed genes. If set to "Auto," DEGlog2FC is defined at the level where ANOVA can get a q value of 0.05 with the average expression, where the data values are log _{1p} transformed. Defaults to "Auto". |
| MaxLibSizeLog2FC | Double: The maximum library size difference from the mean that is allowed, in terms of log 2 fold change. Set to 0 to prevent program from generating library size differences. Defaults to 0.5. |

Value

This function returns a list that contains a matrix of count data in integer raw count and a vector that shows which genes are differentially expressed. In the matrix, each row is a gene and each column is a replicate. The first NumRep (see parameter) of the columns belong to sample 1, and the last NumRep (see parameter) of the columns belong to sample 2. There will be NumFea (see parameter) number of rows. The top NumCorr of genes will be positively or negatively correlated with each other (randomly); and they are evenly separated into groups. Each group is not intended to be correlated to each other, but, by chance, it can happen.

Examples

```
#Obtain example matrix:
data(SEQC)
expMatrix <- SEQC
#Example for Negative Binomial distribution
simulateddata <- RnaXSim(expMatrix, distribution="NB", NumRep=5, NumDiff = 200, NumFea = 2000)
#Example for Poisson distribution
simulateddata <- RnaXSim(expMatrix, distribution="Poisson", NumRep=5, NumDiff = 200, NumFea = 2000)
#Example for Log Normal distribution
simulateddata <- RnaXSim(expMatrix, distribution="LogNorm", NumRep=5, NumDiff = 200, NumFea = 2000)
#Example for Gamma distribution
simulateddata <- RnaXSim(expMatrix, distribution="Gamma", NumRep=5, NumDiff = 200, NumFea = 2000)
```

SEQC

Partial RNA-seq data from SEQC/MAQC-III Sample A

Description

Raw Count data

Usage

`data(SEQC)`

Format

A matrix with 50227 rows (genes) and 10 columns (samples).

References

SEQC/MAQC-III Consortium. A comprehensive assessment of RNA-seq accuracy, reproducibility and information content by the Sequencing Quality Control Consortium. *Nature biotechnology* 32.9 (2014): 903-914.

Index

* Analysis

Linnorm.PCA, 18
Linnorm.tSNE, 21

* CPM

Linnorm, 5
Linnorm.Cor, 7
Linnorm.HClust, 11
Linnorm.HVar, 13
Linnorm.limma, 15
Linnorm.Norm, 16
Linnorm.PCA, 18
Linnorm.SGenes, 20
Linnorm.tSNE, 21

* Clustering

Linnorm.HClust, 11
Linnorm.PCA, 18
Linnorm.tSNE, 21

* Component

Linnorm.PCA, 18
Linnorm.tSNE, 21

* Count

Linnorm, 5
Linnorm.Cor, 7
Linnorm.HClust, 11
Linnorm.HVar, 13
Linnorm.limma, 15
Linnorm.Norm, 16
Linnorm.PCA, 18
Linnorm.SGenes, 20
Linnorm.tSNE, 21
RnaXSim, 23

* Expression

Linnorm, 5
Linnorm.Cor, 7
Linnorm.HClust, 11
Linnorm.HVar, 13
Linnorm.limma, 15
Linnorm.Norm, 16
Linnorm.PCA, 18

Linnorm.SGenes, 20
Linnorm.tSNE, 21
RnaXSim, 23

* FPKM

Linnorm, 5
Linnorm.Cor, 7
Linnorm.HClust, 11
Linnorm.HVar, 13
Linnorm.limma, 15
Linnorm.Norm, 16
Linnorm.PCA, 18
Linnorm.SGenes, 20
Linnorm.tSNE, 21

* Filter

Linnorm.SGenes, 20

* Gamma

RnaXSim, 23

* K-means

Linnorm.PCA, 18
Linnorm.tSNE, 21

* Linear

LinearRegression, 3
LinearRegressionFP, 4

* Linnorm

Linnorm, 5
Linnorm.Cor, 7
Linnorm.DataImput, 9
Linnorm.HClust, 11
Linnorm.HVar, 13
Linnorm.limma, 15
Linnorm.Norm, 16
Linnorm.PCA, 18
Linnorm.SGenes, 20
Linnorm.tSNE, 21

* Log

RnaXSim, 23

* Negative

RnaXSim, 23

* PCA

- Linnorm.PCA, 18
- Linnorm.tSNE, 21
- * **Parametric**
 - Linnorm, 5
 - Linnorm.Cor, 7
 - Linnorm.HClust, 11
 - Linnorm.HVar, 13
 - Linnorm.limma, 15
 - Linnorm.PCA, 18
 - Linnorm.tSNE, 21
- * **Poisson**
 - RnaXSim, 23
- * **Principal**
 - Linnorm.PCA, 18
 - Linnorm.tSNE, 21
- * **RNA-seq**
 - Linnorm, 5
 - Linnorm.Cor, 7
 - Linnorm.DataImput, 9
 - Linnorm.HClust, 11
 - Linnorm.HVar, 13
 - Linnorm.limma, 15
 - Linnorm.Norm, 16
 - Linnorm.PCA, 18
 - Linnorm.SGenes, 20
 - Linnorm.tSNE, 21
 - RnaXSim, 23
- * **RPKM**
 - Linnorm, 5
 - Linnorm.Cor, 7
 - Linnorm.HClust, 11
 - Linnorm.HVar, 13
 - Linnorm.limma, 15
 - Linnorm.Norm, 16
 - Linnorm.PCA, 18
 - Linnorm.SGenes, 20
 - Linnorm.tSNE, 21
- * **Raw**
 - Linnorm, 5
 - Linnorm.Cor, 7
 - Linnorm.HClust, 11
 - Linnorm.HVar, 13
 - Linnorm.limma, 15
 - Linnorm.Norm, 16
 - Linnorm.PCA, 18
 - Linnorm.SGenes, 20
 - Linnorm.tSNE, 21
 - RnaXSim, 23
- * **Regression**
 - LinearRegression, 3
 - LinearRegressionFP, 4
- * **Simulate**
 - RnaXSim, 23
- * **Simulation**
 - RnaXSim, 23
- * **Stable**
 - Linnorm.SGenes, 20
- * **TPM**
 - Linnorm, 5
 - Linnorm.Cor, 7
 - Linnorm.HClust, 11
 - Linnorm.HVar, 13
 - Linnorm.limma, 15
 - Linnorm.Norm, 16
 - Linnorm.PCA, 18
 - Linnorm.SGenes, 20
 - Linnorm.tSNE, 21
- * **cell**
 - Linnorm.DataImput, 9
- * **coefficient**
 - Linnorm.Cor, 7
- * **constant**
 - LinearRegression, 3
 - LinearRegressionFP, 4
- * **correlation**
 - Linnorm.Cor, 7
- * **data**
 - Linnorm.DataImput, 9
- * **distribution**
 - RnaXSim, 23
- * **embedding**
 - Linnorm.tSNE, 21
- * **hierarchical**
 - Linnorm.HClust, 11
- * **highly**
 - Linnorm.HVar, 13
- * **imputation**
 - Linnorm.DataImput, 9
- * **k-means**
 - Linnorm.PCA, 18
 - Linnorm.tSNE, 21
- * **kendall**
 - Linnorm.Cor, 7
- * **kmeans**
 - Linnorm.PCA, 18
 - Linnorm.tSNE, 21

- * **limma**
 - Linnorm.limma, 15
 - * **missing**
 - Linnorm.DataImput, 9
 - * **neighbor**
 - Linnorm.tSNE, 21
 - * **normalization**
 - Linnorm, 5
 - Linnorm.Cor, 7
 - Linnorm.HClust, 11
 - Linnorm.HVar, 13
 - Linnorm.limma, 15
 - Linnorm.Norm, 16
 - Linnorm.PCA, 18
 - Linnorm.tSNE, 21
 - * **pearson**
 - Linnorm.Cor, 7
 - * **single**
 - Linnorm.DataImput, 9
 - * **slope**
 - LinearRegression, 3
 - LinearRegressionFP, 4
 - * **spearman**
 - Linnorm.Cor, 7
 - * **stochastic**
 - Linnorm.tSNE, 21
 - * **t-SNE**
 - Linnorm.tSNE, 21
 - * **t-distributed**
 - Linnorm.tSNE, 21
 - * **transformation**
 - Linnorm, 5
 - Linnorm.Cor, 7
 - Linnorm.HClust, 11
 - Linnorm.HVar, 13
 - Linnorm.limma, 15
 - Linnorm.PCA, 18
 - Linnorm.tSNE, 21
 - * **value**
 - Linnorm.DataImput, 9
 - * **variable**
 - Linnorm.HVar, 13
 - * **variance**
 - Linnorm.HVar, 13
- Islam2011, 2
- LIHC, 3
- LinearRegression, 3
- LinearRegressionFP, 4
- Linnorm, 5
- Linnorm.Cor, 7
- Linnorm.DataImput, 9
- Linnorm.HClust, 11
- Linnorm.HVar, 13
- Linnorm.limma, 15
- Linnorm.Norm, 16
- Linnorm.PCA, 18
- Linnorm.SGenes, 20
- Linnorm.tSNE, 21
- RnaXSim, 23
- SEQC, 25